

# Weatherguard Roof Tile Paint

Technical Data  
Sheet – F104


## PRODUCT DESCRIPTION & USE

Fleetwood Weatherguard Roof Tile Paint is a smooth exterior emulsion paint of superior quality. It is made on 100% acrylic binder and is formulated to provide excellent exterior properties and adhesion to concrete roof tiles. **THIS PRODUCT IS NOT SUITABLE FOR SLATE ROOF OR ASBESTOS CEMENT ROOF TILES**

## KEY BENEFITS

- A high quality, water-based exterior paint with excellent colour retention properties.
- Excellent adhesion and durability
- .

## AVAILABLE IN SIZES



## COLOUR RANGE

### Fleetwood Weatherguard Roof Tile Paint

Available in various colours.

## VOC CONTENT

Contains max VOC; 45g/l  
Conforms to EU 2010 Directive (Cat A/d) 130g/l

## COMPOSITION (NOMINAL)

**Pigment:** Lightfast Pigments.  
**Binder:** Acrylic Emulsion.  
**Solvent:** Water.

## SOLIDS - SPECIFIC GRAVITY

**Volume Solids** 37.0 % (+/- 2%)  
**Weight Solids** 43.0 % (+/- 2%)  
**Specific Gravity** 1.27 g/l (+/- 0.15)

## SURFACE PREPARATION

Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. Treat aged roof tiles with Fleetwood Masonry Primer. Badly fouled roofs should be treated with Fleetwood Fungicidal Wash to remove all organic growth. Use in accordance with good painting practices

## APPLICATION



Brush, roller, spray & airless spray.  
As with other water-based paints, do not apply in temperatures below 5°C

## SPREADING RATE



As a guide a coverage rate of up to 10m²/litre can be achieved under normal conditions. Coverage will be dependent on the porosity and evenness of the substrate.

## REDUCTION

Reduce by up to 10% as required by application and or equipment.

## SPRAY RECOMMENDATIONS

**Conventional Spray:** Satisfactory through most equipment.  
**Airless Spray:** A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lb/in²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

## DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



**Touch Dry:** 2 hours  
**Recoat:** 2 – 4 hours

This is dependent upon temperature and humidity. Darker colours may take longer

## CLEANING UP



Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.

## PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

## PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. If paint is peeling or badly weathered, clean to sound substrate and treat as new.

## FOLLOW US ON

Online: [www.fleetwood.ie](http://www.fleetwood.ie)

Email: [info@fleetwood.ie](mailto:info@fleetwood.ie)

Phone : 049 8547209

