


PRODUCT DESCRIPTION & USE

Fleetwood Prestige Superior Sheen is a premium quality, low odour emulsion for interior walls and ceilings. It is an acrylic coating with enhanced stain resistance and excellent durability. It provides a low odour, quick drying finish that is resistant to condensation and regular cleaning, making it ideal for all rooms but especially use in kitchens, bathrooms.

KEY BENEFITS

- Quick drying low odour sheen finish
- Outstanding durability - Scrubbable finish.
- Produces a smooth washable surface that resists condensation

AVAILABLE IN SIZES



COLOUR RANGE

Fleetwood Superior Prestige Sheen

Especially designed and developed for Pantone and Vogue colour ranges available only from selected Fleetwood outlets via our tinting systems

VOC CONTENT

Contains max VOC; 52g/l
Conforms to EU 2010 Directive (Cat A/b) 100g/l

COMPOSITION (NOMINAL)

Pigment: Lightfast Pigments.
Binder: Acrylic Modified Copolymer Emulsion.
Solvent: Water.

SOLIDS - SPECIFIC GRAVITY

Volume Solids 39.5% (+/- 2%)
Weight Solids 54.0% (+/- 3%)
Specific Gravity 1.3 g/l (+/- 0.40)

SURFACE PREPARATION

Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Treat powdery surfaces with Fleetwood Masonry Primer. Use in accordance with good painting practices

APPLICATION



Brush, roller, spray & airless spray.
As with other water-based paints, do not apply in temperatures below 8°C

SPREADING RATE



As a guide a coverage rate of up to 12m²/litre can be achieved under normal conditions

REDUCTION

Reduce by up to 10% as required by application and or equipment.

SPRAY RECOMMENDATIONS

Conventional Spray: Satisfactory through most equipment.

Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lb/sq in) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 1-2 hours
Recoat: 3-4 hours

This is dependent upon temperature and humidity. Darker colours may take longer

CLEANING UP



Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.

TINTING INSTRUCTIONS

Tint only with Fleetwood tinting systems

(Base P - Pastel) (Base M - Medium) (Base D - Deep)
(Base B - Accent) some colours may require a primer for optimal opacity P1 P2 P3

PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.

FOLLOW US ON

Online: www.fleetwood.ie/prestige
Email: info@fleetwood.ie
Phone : 049 8547209

