

All Purpose Ready Mixed Filler **Product Information Sheets**

Description

A ready to use, ready mixed filler suitable for both interior and exterior uses. Ideal for repairs to all stonework, timber and plaster. Simple to use, dries white. May be sanded when dry, although this is often unnecessary, as the product is extremely smooth. When using externally, product must be sealed with oil based paint or varnish when dry.

Instructions for Use

Ensure surfaces to be filled are clean, dry and dust free. If necessary stir before use. Apply in a thin layer using a filling knife or spatula, pressing into cavities. If a deeper repair is required, build up the filler in thinner layers. For a perfect finish, fill slightly proud of the surrounding surface and use fine sandpaper to blend in the repair. Exterior repairs should be protected from weather until dry and then over painted with an oil-based paint to protect from weathering. Do not use on surfaces regularly under water.

Cleaning and Storage

Clean tools with water before Filler sets hard. After use, ensure lid is firmly replaced. Protect from frost.

Health and Safety

Do not consume. Keep away from children and animals. If Filler comes into contact with skin, wash with warm water before the Filler dries. Avoid contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice.

Technical Data

Physical State:	Paste
Form Colour:	Opaque white
Odour:	Mild
Specific Gravity:	1.680
Viscosity (Helipath TF /Spd 10):	3200 - 3800
pH:	7.7 – 8.6
Solubility in Water:	Miscible

Packing Specification

Product / Pack Size	Quantity Per Carton	Cartons / Drums Per Pallet.
600 gram Tub	12	80
1 Kg Tub	12	48

Customs Tariff Code

3214 1090

Shipping Classification

Non-hazardous for shipping purposes