



BROOKS MASONRY PAINT

CHARACTERISTICS	APPLICATION	SURFACE PREPARATION
<p>A smooth exterior emulsion paint of superior quality, it is formulated to provide excellent exterior durability and resistance to organic growth.</p>	<p>Temperature (air, surface, material) (at least 4°C above dew point) 10°C to 42°C. Relative Humidity 75% Maximum.</p>	<p>Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease and flaking material. Treat powdery surfaces with Water Based Stabilising Solution.</p>
COLOUR	SPREADING RATE	<p>Steel:- Remove all loose rust, peeling paint, other loosely adhering contaminations per SSPC SP2. Hand tool cleaning. Remove any contamination before applying subsequent coats of material. Prime base steel with an appropriate anti-corrosive primer.</p>
<p>Brilliant White and various colours</p>	<p>10m² / 1 litre</p>	<p>Concrete Block and Masonry:- Surfaces should be thoroughly clean and dry, with mortar and concrete aired for a minimum of 30 days @ 24°C. All loose mortar or other contaminants should be removed prior to application of any coating material. Surface temperatures must be at least 12°C before filling. Use appropriate filler for cracks or imperfections. Allow to dry thoroughly before top coating.</p>
DRYING SCHEDULE	METHODS	<p>Galvanised:- The surface should be exterior weathered for 6 months prior to painting, solvent clean per SSPC-SP1. When weathering is not possible, surface must be solvent cleaned followed by an appropriate etch prime. Rusty galvanised surfaces must be hand tool cleaned per SSPC-SP2. Prime rust areas with appropriate anti-corrosive primer.</p>
<p>(Temperature and humidity dependant) @ 26°C 50% RH @ 4Thou Wet To Touch - 30 mins To Dry - 4 hours</p>	<p>Brush, roller, airless spray Airless Spray:- Minimum pressure 138 bars (2000lb/sq in). Tip Size:- 0.38mm - 0.46mm (15-18 Thou). Filter:- 60 mesh. Angle:- 65 degrees Always flush spray equipment with water prior to applying Water Based Coatings.</p>	PREVIOUSLY PAINTED SURFACES
SPECIFIC GRAVITY	MIXING INSTRUCTIONS	<p>If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.</p>
<p>1.27+/-0.15</p>	<p>Thoroughly mix paint before use by stirring and boxing.</p>	<small>ISSUE NO.1 6/2000</small>
WEIGHT SOLIDS	PERFORMANCE INFORMATION	
<p>45+/-2%</p>	<p>The product is specially designed as an exterior coating for use over block, concrete and other masonry surfaces where a long lasting decorative finish is required.</p>	
VOLUME SOLIDS	CLEAN UP	
<p>30+/-2%</p>	<p>Clean up with soap and water. After clean up be sure to flush spray equipment with solvent to prevent rusting following manufacturers instructions.</p>	
PRECAUTIONS	REDUCTION	
<p>Keep out of reach of children. Ensure good ventilation during application and drying.</p> <p>In case of contact with eyes rinse immediately with plenty of water.</p> <p>To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.</p>	<p>Reduce up to 20% with water as required by application equipment</p>	