

#### SAFETY DATA SHEET

# **Ceiling Paint**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

**Ceiling Paint** 

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

**Paint** 

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

#### Company and address

### **FSW Coatings Ltd.**

Ballaghanea, Virginia,

A82 N267, Co Cavan,

Ireland.

353 49854 7209

#### E-mail

info@fsw.ie

Revision

25/09/2023

**SDS Version** 

1.0

### 1.4. Emergency telephone number

The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am-10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

#### SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

2.2. Label elements

#### Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

-

Prevention

Response

-

Storage

Disposal

-



#### Hazardous substances

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3. Other hazards

### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17-XXXX Index No.: 022-006-00-2	5-10%	Carc. 2, H351	[17]
Calcium carbonate	CAS No.: 471-34-1 EC No.: 207-439-9 REACH: Index No.:	5-10%		
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH: 01-2120764691-48 Index No.: 613-167-00-5	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[17] The classification as a carcinogen is not taken into consideration when classifying the product as the product is not delivered in powder form/contains less than 1 % titanium dioxide on particle form with an aerodynamic diameter  $\leq$  10 µm (CLP, Annex VI, note 10).

#### SECTION 4: First aid measures

### 4.1. Description of first aid measures

## General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Ceiling Paint Page 2 of 11



IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### **Burns**

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### Information to medics

Bring this safety data sheet or the label from this product.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

Some metal oxides

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

### SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

## 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

#### SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.



See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

No specific requirements

### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq$  10 µm] Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust) / 4(respirable dust)

#### Calcium carbonate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

#### Calcium carbonate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable); 4(respirable)

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

#### **DNEL**

### Calcium carbonate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	1.06 mg/m <sup>3</sup>
Long term – Local effects - General population	Inhalation	1.06 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	6.36 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	6.36 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6.1 mg/kg bw/day
Long term – Systemic effects - General population	Oral	6.1 mg/kg bw/day
Short term – Systemic effects - General population	Oral	6.1 mg/kg bw/day
Short term – Systemic effects - General population	Oral	6.1 mg/kg bw/day

## reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 μg/m³
Long term – Local effects - Workers	Inhalation	20 μg/m³
Short term – Local effects - General population	Inhalation	40 μg/m³
Short term – Local effects - Workers	Inhalation	40 μg/m³
Long term – Systemic effects - General population	Oral	90 μg/kgbw/day
Short term – Systemic effects - General population	Oral	110 μg/kgbw/day

titanium dioxide: [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 um]

technical dioxide, [in powder form containing 1 70 of more of particles with derodynamic diameter 2 10 pm]			
Duration:	Route of exposure:	DNEL:	
Long term – Local effects - General population	Inhalation	28 μg/m³	
Long term – Local effects - Workers	Inhalation	170 μg/m³	

#### **PNEC**

Calcium carbonate

Ceiling Paint Page 4 of 11

Route of exposure:	Duration of Exposure:	PNEC:
Sewage treatment plant		100 mg/L
Sewage treatment plant		100 mg/L
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-r	nethyl-2H-isothiazol-3-one (3:1)	
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.39 µg/L
Freshwater sediment		27 μg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 μg/kg
Sewage treatment plant		230 μg/L
Soil		10 μg/kg

#### 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

#### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

#### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements.

#### Individual protection measures, such as personal protective equipment

### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

No specific requirements

#### Skin protection

No specific requirements.

### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN374-3, EN388	



shields.

Туре	Standards		
Safety glasses with side	EN166		



#### SECTION 9: Physical and chemical properties

Ceiling Paint Page 5 of 11



```
9.1. Information on basic physical and chemical properties
   Physical state
      Liquid
   Colour
      White, Opaque
   Odour / Odour threshold
      Faint
  рΗ
   Density (g/cm³)
   Relative density
      1.32
   Kinematic viscosity
      >0.21 cm<sup>2</sup>/s (40 °C)
   Particle characteristics
      Does not apply to liquids.
Phase changes
   Melting point/Freezing point (°C)
      Testing not relevant or not possible due to the nature of the product.
   Softening point/range (waxes and pastes) (°C)
      Does not apply to liquids.
   Boiling point (°C)
      42
  Vapour pressure
      3.2 kPa (20 °C)
   Relative vapour density
      7.5
   Decomposition temperature (°C)
      Stable under normal handling and storage conditions.
Data on fire and explosion hazards
   Flash point (°C)
      Not applicable
   Flammability (°C)
      Not applicable
   Auto-ignition temperature (°C)
      Not applicable
   Lower and upper explosion limit (% v/v)
      Testing not relevant or not possible due to the nature of the product.
Solubility
   Solubility in water
      Partially soluble in cold water
   n-octanol/water coefficient
      Testing not relevant or not possible due to the nature of the product.
   Solubility in fat (g/L)
      Testing not relevant or not possible due to the nature of the product.
9.2. Other information
   Evaporation rate (n-butylacetate = 100)
      Not applicable
   VOC (g/L)
   Other physical and chemical parameters
      Volume Solids 25.0.0% +/- 1.0%. Weight Solids 36.0% +/- 1.0%.
   Oxidizing properties
      Not applicable
```

### SECTION 10: Stability and reactivity

## 10.1. Reactivity

No data available.



#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

**OECD 425** 

Test method: Species: Rat Route of exposure: Oral LD50 Test: Result: >5000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

> μm] Rabbit

Species: Route of exposure: Dermal Test: LD50

Result: >10000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

um1 Rat

Species: Route of exposure: Inhalation Test: LC50 (4 hours) >6.82 mg/L Result:

Product/substance Calcium carbonate

Species: Rat Route of exposure: Oral Test: LD50 Result: 6450 mg/kg

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

# Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.



#### 11.2. Information on other hazards

### Long term effects

None known.

### Endocrine disrupting properties

Not applicable.

#### Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq$  10  $\mu$ m] has been classified by IARC as a group 2B carcinogen.

### SECTION 12: Ecological information

12.1. Toxicity

Duration:

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Test method: OECD 203
Species: Fish
Duration: 96 hours
Test: LC50
Result: >1000 mg/L

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Test method: OECD 202

Species: Crustacean, Daphnia magna

Duration: 48 hours
Test: LC50
Result: >1000 mg/L

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Test method: OECD 201

Species: Algae, Pseudokirchneriella subcapitata

Test: EC50 Result: 61 mg/L

Product/substance Calcium carbonate

Species: Fish
Compartment: Freshwater
Duration: 72 hours
Test: LC50

Result: >56000 mg/L

Product/substance Calcium carbonate

Species: Fish
Compartment: Freshwater
Duration: 28 days
Test: NOEC
Result: 61000 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 201

Species: Fish, Oncorhynchus mykiss

Duration: 96 hours
Test: LC50
Result: 0.22 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 211
Species: Daphnia
Duration: 21 days
Test: NOEC
Result: 0.004 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Ceiling Paint Page 8 of 11

Test method: ISO 10253 2006

Species: Algae, Skeletonema costatum

Duration: 48 hours
Test: NOEC
Result: 0.00064 mg/L

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. Endocrine disrupting properties

Not applicable.

#### 12.7. Other adverse effects

None known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 7 - Carcinogenic

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

#### EWC code

Not applicable.

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

### **SECTION 14: Transport information**

	14.1 UN / I	14.2 D UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

<sup>\*</sup> Packing group

#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

#### 14.6. Special precautions for user

Not applicable.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Restrictions for application

People under the age of 18 shall not be exposed to this product.

### Demands for specific education

No specific requirements.

### SEVESO - Categories / dangerous substances

Not applicable.

### Additional information

Not applicable.

<sup>\*\*</sup> Environmental hazards



#### Sources

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on

classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

### 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H301, Toxic if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H351, Suspected of causing cancer.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound



### vPvB = Very Persistent and Very Bioaccumulative

### Additional information

Not applicable.

# The safety data sheet is validated by

EcoOnline

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en