Product Diamond Seal Gloss
Revision date 19 March 2021

Revision 3



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Diamond Seal Gloss
Other means of identification No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint or paint related material. For industrial use.

Uses advised against No uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd

Virginia Co Cavan Ireland

Tel: 353 49854 7209

Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone + 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Not classified Human health Not classified Environment Not classified

2.2 Label elements

Contains Not applicable

Label in accordance with (EC) no. $\,$

1272/2008

No pictogram required

Signal word No Signal Word

Hazard statements No hazard statements required

Precautionary statements No precautionary statements required

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
2-butoxyethanol	CAS-No.: 111-76-2 EC No.: 203-905-0 REACH Reg No.: 01-2119475108-36-XXXX	Acute Tox 4 - H302, Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319	0.1-0.9%
2-(2-butoxyethoxy)ethanol	CAS-No.: 112-34-5 EC No.: 203-961-6 REACH Reg No.: 01-2119475104-44-XXXX		0.1-0.9%
Alcohols, C16-18, ethoxylated	CAS-No.: 68439-49-6 EC No.: 500-212-8	Acute Tox 4 - H302, Eye Dam. 1 - H318, Aquatic Acute 1 - H400	0.1-0.9%
xylene	CAS-No.: 1330-20-7 EC No.: 215-535-7	Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Flam. Liq 3- H226	0.1-0.9%
ethylbenzene	CAS-No.: 100-41-4 EC No.: 202-849-4	Aquatic Chronic 3 - H412, Acute Tox 4 - H332, Asp. Tox - H304, Flam. Liq 2- H225, STOT RE 2 - H373	<0.1%
ethanol	CAS-No.: 64-17-5 EC No.: 200-578-6	Eye Irrit.2A - H319, Flam. Liq 2- H225	<0.1%
2-methylpropan-1-ol	CAS-No.: 78-83-1 EC No.: 201-148-0	Skin Irrit.2 - H315, Eye Dam. 1 - H318, Flam. Liq 3- H226, STOT SE 3 - H335, STOT SE 3 - H336	<0.1%
methanol	CAS-No.: 67-56-1 EC No.: 200-659-6	Acute Tox 3 - H301, Acute Tox 3 - H311, Acute Tox 3 - H331, Flam. Liq 2- H225, STOT SE 1 - H370	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Methanol: Specific Concentration Limits = STOT SE 1; H370: C >= 10 %, STOT SE 2; H371:

3 % <= C < 10 %.

Section 4: First aid measures

4.1 Description of first aid measures

General information Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if

symptoms persist, always call a doctor.

Inhalation Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort or breathing difficulties develop.

Ingestion Rinse mouth out and then drink plenty of water. Seek medical attention.

Skin contact Remove affected person from source of contamination. Wash exposed area with soap and

water. Get medical attention if irritation develops or persists.

Eye contact Remove contact lenses if present and easy to do so. Hold eye lids open. Rinse with a gentle

stream water for at least 15 minutes. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Inhalation of high concentrations of vapours may cause irritation of the respiratory tract or

dizziness.

Ingestion Prolonged exposure to liquid product may cause irritation to linings of mouth,

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician Treat symptomatically.

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media This product is not flammable. Use fire-extinguishing media appropriate for surrounding

materials. Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing media High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Unusual fire & explosion hazards Specific hazards

During fire, gases hazardous to health may be formed.

No unusual fire or explosion hazards noted. Floors may become slippery, avoid falls.

5.3 Advice for firefighters

Special fire fighting procedures Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires

from safe distance or protected location. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.

Protective equipment for firefighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear protective clothing as described in Section 8 of this safety data sheet. Ensure adequate

ventilation. Do not smoke, use open fire or other sources of ignition.

Follow safe handling advice and personal protective equipment recommendations for normal For emergency responders

use of product.

6.2 Environmental precautions

Environmental precautions Avoid discharge in to drains and water courses.

6.3 Methods and material for containment and cleaning up

Spill clean up methods Stop leak if possible without risk. Wear necessary protective equipment. Absorb spillage with

> non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled

container. Wash thoroughly after dealing with a spillage.

6.4 Reference to other sections

Reference to other sections See section 1 for emergency contact. For personal protection, see section 8. For waste

disposal, see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling Read and follow manufacturer's recommendations. Observe occupational exposure limits and

> minimise the risk of inhalation of vapours and mist. Do not eat, drink or smoke when using the product. Avoid spilling, skin and eye contact. Ensure adequate ventilation. Use proper

personal protection when handling (refer to Section 8).

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a cool, dry and well-ventilated place. Keep

upright, locked up and out of reach of children.

Unspecified storage. Storage class

7.3 Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1. Usage description Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (15mins)	Notes
2-butoxyethanol	OEL	20 ppm	98 mg/m ³	50 ppm	246 mg/m ³	Sk, IOELV
2-(2-butoxyethoxy)ethanol	OEL	10 ppm	67.5 mg/m ³	12 ppm	101.2 mg/m ³	IOELV
xylene	OEL	50 ppm	221 mg/m ³	100 ppm	442 mg/m ³	Sk, IOELV
ethylbenzene	OEL	100 ppm	442 mg/m ³	200 ppm	884 mg/m ³	Sk, IOELV
ethanol	OEL			1000 ppm		
2-methylpropan-1-ol	OEL	50 ppm	150 mg/m ³	75 ppm	225 mg/m ³	
methanol	OEL	200 ppm	260 mg/m ³			

Ingredient comments Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls

Protective equipment



Engineering measures Observe occupational exposure limits and minimize the risk of inhalation of dust.

Respiratory equipmentNo specific recommendation made, but respiratory protection must be used if the general level expected the recommendation made accounts in the specific recommendation of the specific recommendation made.

level exceeds the recommended occupational exposure limit. Use type ABEK (EN 14387) respirator cartridges.

Hand protection Use suitable protective gloves if there is a risk of skin contact. Full contact: Material: Nitrile

rubber; Minimum layer thickness: $0.11 \, \text{mm}$; Breakthrough time: $480 \, \text{min}$. Consult

manufacturer for specific advice.

Eye protection Use equipment for eye protection tested and approved under appropriate government

standards such as EN 166(EU).

Other protection Wear appropriate clothing to prevent any possibility of skin contact. Protective clothing

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the

European norm standard EN 943.

Hygiene measures Wash hands and / or face before breaks and at the end of the shift. Do not eat, drink, or

smoke while using this product. Avoid contact with skin, eyes and clothing.

Process conditionsUse only according to directions. Ensure that eye flushing systems and safety showers are

located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

AppearanceViscous liquid.ColourClear.OdourSlight.

Odour threshold - lower No information available as testing has not been completed.

Odour threshold - upperNo information available as testing has not been completed.

pH-Value, Conc. Solution >8.1

pH-Value, Diluted solution No information available as testing has not been completed.

Melting point May start to solidify at the temperatures below 2°C. This is based on data for the following

ingredient: water

Initial boiling point and boiling

range

>42°C

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability state Non flammable.

Flammability limit - lower(%) No information available as testing has not been completed.

Flammability limit - upper(%) 0%

Vapour pressure Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 3.12 kPa

(23.4 mm Hg) (at 20°C)

Vapour density (air=1) Highest known value: 7.5 (Air = 1) (isobutyric acid, monoester with 2,2, 4-trimethylpentan-

-1,3-diol).

Relative density 1.02

Bulk density No information available as testing has not been completed.

Solubility Partially soluble in cold water.

Decomposition temperature Stable under normal handling and storage conditions

Partition coefficient; n-

Octanol/Water

No information available as testing has not been completed.

Auto ignition temperature (°C) Not applicable.

Viscosity Kinematic (40°C): >0.25 cm²/s

Explosive properties Not classified as explosive.

Oxidising properties The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight No information available as testing has not been completed.

Volatile organic compound 77.00 g/litre

Other information Volume solids: 31.0% +/- 1.0%.

Weight Solids: 33.0 +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity No specific reactivity hazards associated with this product.

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

10.3 Possibility of hazardous reactions

Hazardous reactions For information on hazardous reactions see section 10.1.

Hazardous polymerisationUnknown.Polymerisation descriptionUnknown.

10.4 Conditions to Avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Extremes of temperature and direct

sunlight.

10.5 Incompatible materials

Materials to avoid Do not mix with other chemicals unless listed on directions. Strong oxidising substances.

10.6 Hazardous decomposition products

Hazardous decomposition products When heated, vapours/gases hazardous to health may be formed.

Section 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Toxicological information No toxicological information for the overall finished product.

Acute toxicity (Oral LD50) No information available as testing has not been completed. Acute toxicity (Dermal LD50) No information available as testing has not been completed. No information available as testing has not been completed. Acute toxicity (Inhalation LD50)

Serious eye damage/irritation May cause temporary eye irritation.

Skin corrosion/irritation The product is not classified as a skin corrosion/irritation hazard.

The product is not classified as a respiratory hazard. Respiratory sensitisation Skin sensitisation The product is not classified as a skin sensitisation hazard.

Germ cell mutagenicity The product is not classified as a mutagen.

Carcinogenicity The product is not classified as a carcinogen hazard.

Specific target organ toxicity - Single exposure:

STOT - Single exposure The product is not classified as a single exposure specific target organ toxin.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposure The product is not classified as a repeat exposure specific target organ toxin.

Inhalation Inhalation of high concentrations of vapours may cause irritation of the respiratory tract or

Ingestion Prolonged exposure to liquid product may cause irritation to linings of mouth,

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eve contact May cause temporary eye irritation.

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

Routes of entry Eyes, skin, ingestion or inhalation.

Target organs Eyes, skin, digestive system, respiratory system.

Aspiration hazards: The product is not classified as an aspiration hazard. Reproductive toxicity: The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
2-butoxyethanol	470.00mg/kg Rat	2270.00mg/kg Rat	2.21mg/l (vapours) Rat 4 Hours
methanol	5628.00mg/kg Rat	15800.00mg/kg Rat	64000.00ppmV Rat 4 Hours
2-(2-butoxyethoxy)ethanol	3305.00mg/kg Rat	2764.00mg/kg Rabbit	

11.2 Information on other hazards

Information on other hazards None known.

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish No information available as testing has not been completed. Acute toxicity - Aquatic invertebrates No information available as testing has not been completed. **Acute toxicity - Aquatic plants** No information available as testing has not been completed. **Acute toxicity - Microorganisms** No information available as testing has not been completed. No information available as testing has not been completed. **Chronic toxicity - Fish Chronic toxicity - Aquatic** No information available as testing has not been completed. invertebrates

Chronic toxicity - Aquatic plants No information available as testing has not been completed. **Chronic toxicity - Microorganisms** No information available as testing has not been completed.

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude

the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Not classified as dangerous for the environment according to the criteria of Regulation (EC) Eco toxilogical information

No 1272/2008.

12.2 Persistence and degradability

Degradability

The degradability of the product has not been stated.

Biological oxygen demand Chemical oxygen demand No information available as testing has not been completed. No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential

Bioaccumulation factor

Partition coefficient; n-Octanol/Water No data available on bioaccumulation.

No information available as testing has not been completed. No information available as testing has not been completed.

12.4 Mobility in soil

Mobility

Partially soluble in cold water.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties

The product does not contain any substances with endocrine disrupting properties at a

concentration above or equal to 0.1%.

12.7 Other adverse effects

Other adverse effects

None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
2-butoxyethanol	ILC50 1490.00mg/l Freshwater Fish	EC50 48 Hours 1001.00mg/l Daphnia magna	
methanoi	LC50 96 Hours 13200.00mg/l Onchorhynchus mykiss (Rainbow Trout)		
2-(2-butoxyethoxy)ethanol	L	EC50 48 Hours >100.00mg/l Daphnia magna	

Section 13: Disposal considerations

Waste management

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

13.1 Waste treatment methods

Disposal methods

Dispose of waste and residues in accordance with local authority requirements, and in accordance with all local, national and international regulations. For waste disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information

14.1 UN number or ID number

UN no. (ADR) Not applicable.
UN no. (IMDG) Not applicable.
UN no. (IATA) Not applicable.

14.2 UN proper shipping name

ADR proper shipping name
IMDG proper shipping name
IATA proper shipping name
Not applicable.
Not applicable.

14.3 Transport hazard class(es)

ADR class Not applicable.

IMDG class Not applicable.

IATA class Not applicable.

Transport labels Not applicable

14.4 Packing group

ADR/RID/ADN packing group

IMDG packing group

IATA packing group

Not applicable.

Not applicable.

14.5 Environmental hazards

ADR No IMDG No IATA No

14.6 Special precautions for user

EMS Not applicable.
Emergency action code Not applicable.
Hazard no. (ADR) Not applicable.
Tunnel restriction code Not applicable.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals

(REACH).

Approved code of practice 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents)

Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens)

Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment No chemical safety assessment has been carried out.

Section 16: Other information

General information This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.

Revision comments This is a third issue. [3]Information updated. [4]Information updated. [5]Information

This is a third issue. [3]Information updated. [4]Information updated. [5]Information updated. [6]Information updated.

[10]Information updated. [11]Information updated. [12]Information updated. [15]Information

updated.

Revision date 19 March 2021 **Supersedes date** 26 October 2017

Revision 3

Safety data sheet status Approved.

Hazard statements in full

H302Harmful if swallowed.H312Harmful in contact with skin.H315Causes skin irritation.H319Causes serious eye irritation.

H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.
H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
Н373	May cause damage to organs through prolonged or repeated exposure .
H335	May cause respiratory irritation.
Н336	May cause drowsiness or dizziness.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs .

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.