

TILES

All In One Paint & Primer

| CHARACTERISTICS: | APPLICATION: | THINING: |
|---|---|--|
| <p>FLEETWOOD TILES all in one paint & primer is a water based single pack coating formulated to provide excellent adhesion for ceramic tiles.</p> | <p>Stir thoroughly before use and apply using a synthetic brush or mohair roller. Apply 2 coats. Do not apply in temperatures below 10°C.</p> <p>Apply with a synthetic (nylon, polyester or blend) bristle brush, roller, pad applicator or airless sprayer</p> | <p>Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.</p> <p>Conventional spray application: Add up to 1 part clean water to 2.5 parts paint.</p> <p>Airless spray application: Add up to 1 part clean water to 5 parts paint.</p> |
| <p>RECOMMENDED USE: FLEETWOOD TILES all in one paint & primer is designed to rejuvenate and transform your kitchen or bathroom tiles leaving a highly durable, mould resistant, water-proof finish.</p> | | |
| <p>AVAILABILITY: 1.0 – 2.5 litre</p> | <p>SURFACE PREPARATION</p> <p>To get the best results, ensure surfaces to be painted are sound, clean and dry and free from all defective or poorly adhering material such as dirt, grease or wax. Remove any existing dirt, grease, mould or mildew before painting. If you are concerned about existing mould and mildew first treat the area with Fleetwood Mould Remover.</p> <p>If there is heavy contamination wash the area thoroughly with a detergent such as sugar soap. Allow to dry before coating. Repair damaged grouted areas before coating.</p> | <p>SPRAY RECCOMENDATIONS:</p> <p>Conventional Spray: Satisfactory through most equipment.</p> <p>Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars with a spray tip size of 0.43mm and a spray tip angle of 60°C</p> |
| <p>FINISH: Soft Sheen</p> | | |
| <p>COLOUR: White</p> | | |
| <p>SPECIFIC GRAVITY: 1.29 +/- 0.2</p> | | |
| <p>VOC: 44g/litre</p> | | |
| <p>VOLUME SOLIDS: 38%</p> | | |
| <p>SPREADING RATE: 12m² per litre</p> | | |
| <p>DRYING TIME: Touch Dry 1 hour Recoat 4 hours</p> | | |
| <p>PRECAUTIONS: Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.</p> | | |
| | | |