

uPVC & Plastic Primer

CHARACTERISTICS:	APPLICATION:	THINING:
FLEETWOOD uPVC & Plastic Primer is a quick drying interior/exterior undercoat.	Stir thoroughly before use and apply using a synthetic brush or mohair roller.	Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.
RECOMMENDED USE:	Apply 2 coats and sand gently between coats. Do not apply in temperatures below 10°C.	Conventional spray application: Add up to 1 part clean water to 2.5 parts paint.
FLEETWOOD uPVC & Plastic Primer is suitable for uPVC and plastic surfaces giving excellent adhesion This product has been formulated to give a sound base for Fleetwood top-coats such as Advanced Satinwood or Gloss		Airless spray application: Add up to 1 part clean water to 5 parts paint.
AVAILABILITY:	SURFACE PREPARATION	VOC:
0.5 – 1.0 litre	To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease or wax. To ensure good adhesion it is important to sand previously unpainted surfaces to provide a good key. Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.	16g/litre
FINISH:		SPRAY RECCOMENDATIONS:
Flat matt		Conventional Spray: Satisfactory through most equipment.
COLOUR:		Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars with a spray tip size of 0.43mm and a spray tip angle of 60°C
White		
SPECIFIC GRAVITY:		
1.29 +/- 0.2		
VOLUME SOLIDS:		
34%		
SPREADING RATE:		
12m ² per litre		
DRYING TIME:		CLEAN UP:
Touch Dry 30 minutes		Clean up with soap and water. After clean-up be sure to flush any spray equipment with solvent to prevent rusting.
Recoat 4 hours		
PRECAUTIONS:		
Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.		