

WOOD

Soft Hardwood & MDF Primer

CHARACTERISTICS:	APPLICATION:	THINING:
FLEETWOOD WOOD Soft Hardwood & MDF Primer is a quick drying interior/exterior Primer Undercoat.	Stir thoroughly before use and apply using a synthetic brush or mohair roller. Apply 2 coats and sand gently between coats. Do not apply in temperatures below 10 ⁰ C.	Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.
RECOMMENDED USE:		Conventional spray application: Add up to 1 part clean water to 2.5 parts paint. Airless spray application: Add up to 1 part clean water to 5 parts paint.
FLEETWOOD WOOD Soft, Hardwood & MDF Primer is suitable for all new or previously painted hardwood, softwood or un-laminated MDF. This product has been formulated to give a sound base for Fleetwood top-coats such as Advanced Satinwood or Gloss		
AVAILABILITY:	SURFACE PREPARATION	VOC:
0.5 – 1.0 – 2.5 litre	To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease or wax. Remove all existing mould and mildew before painting. If you are concerned about existing mould and mildew first treat the area with Fleetwood Mould Remover. Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible and then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre - 1960s paint surfaces over wood and metal as they may contain harmful lead. Spot prime all nail heads and metal fixings with 1 coat of an appropriate metal primer.	16g/litre
FINISH:		SPRAY RECCOMENDATIONS:
Flat matt		Conventional Spray: Satisfactory through most equipment.
COLOUR:		Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars with a spray tip size of 0.43mm and a spray tip angle of 60°C
White		
SPECIFIC GRAVITY:		
1.29 +/- 0.2		
VOLUME SOLIDS:		
34%		
SPREADING RATE:		
12m ² per litre		
DRYING TIME:		
Touch Dry 30 minutes		
Recoat 4 hours		
PRECAUTIONS:		CLEAN UP:
Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.		Clean up with soap and water. After clean-up be sure to flush any spray equipment with solvent to prevent rusting.