

SAFETY DATA SHEET

Extra Plus Sheen

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Trade name Extra Plus Sheen 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture Paint Uses advised against None known. 1.3. Details of the supplier of the safety data sheet Company and address FSW Coatings Ltd. Ballaghanea, Virginia, A82 N267, Co Cavan, Ireland. 353 49854 7209 E-mail info@fsw.ie Revision 08/11/2023 SDS Version 1.0 1.4. Emergency telephone number The National Poisons Information Centre (NPIC) Public: +353 (0) 1 809 2166 (7 days a week, 8am- 10pm) Healthcare professionals: +353 (0) 1 809 2566 (24 h service) See also section 4 "First aid measures" SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Not classified according to Regulation (EC) No. 1272/2008 (CLP). 2.2. Label elements Hazard pictogram(s) Not applicable. Signal word Not applicable. Hazard statement(s) Not applicable. Precautionary statement(s) General Prevention Response Storage Disposal Hazardous substances



titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] Additional labelling

EUH208, Contains 2-methylisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one,

2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

Product/substance	Identifiers	% w/w	Classification	Note
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17-XXXX Index No.: 022-006-00-2	15-25%	Carc. 2, H351	[17]
Calcium carbonate	CAS No.: 1317-65-3 EC No.: 215-279-6 REACH: Index No.:	5-10%		[19]
1,2-benzisothiazol-3(2H)- one;1,2-benzisothiazolin-3- one	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: Index No.: 613-088-00-6	0.01-0.049%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH: 01-2120764691-48 Index No.: 613-167-00-5	0.001-0.0014%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[17] The classification as a carcinogen is not taken into consideration when classifying the product as the product is not delivered in powder form/contains less than 1 % titanium dioxide on particle form with an aerodynamic diameter \leq 10 µm (CLP, Annex VI, note 10).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures General information



In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections



See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area. See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust) / 4(respirable dust)

Calcium carbonate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

Propane-1,2-diol

Long term exposure limit (8 hours) (mg/m³): 470 (total (vapour and particulates)) / 10(particulates) Long term exposure limit (8 hours) (ppm): 150 (total (vapour and particulates))

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

DNEL

Propane-1,2-diol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	10 mg/m³
Long term – Local effects - Workers	Inhalation	10 mg/m³
Long term – Systemic effects - General population	Inhalation	50 mg/m³
Long term – Systemic effects - Workers	Inhalation	168 mg/m ³
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one	and 2-methyl-2H-isothiazol-3-one (3:1)
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 µg/m³
Long term – Local effects - Workers	Inhalation	20 µg/m³
Short term – Local effects - General population	Inhalation	40 µg/m³
Short term – Local effects - Workers	Inhalation	40 µg/m³
Long term – Systemic effects - General population	Oral	90 µg/kgbw/day
Short term – Systemic effects - General population	Oral	110 µg/kgbw/day
titanium dioxide; [in powder form containing 1 % or mo	re of particles with aerodynamic di	ameter ≤ 10 µm]
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	28 µg/m³
Long term – Local effects - Workers	Inhalation	170 µg/m³



Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		260 mg/L
Freshwater sediment		572 mg/kg
Intermittent release (freshwater)		183 mg/L
Marine water		26 mg/L
Marine water sediment		57.2 mg/kg
Sewage treatment plant		20 g/L
Soil		50 mg/kg

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.39 µg/L
Freshwater sediment		27 µg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L
Soil		10 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

No specific requirements.

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN374-3, EN388	

Eye protection



Standards

Safety glasses with side EN166 shields.

Туре



SECTION 9: Physical and chemical properties

```
9.1. Information on basic physical and chemical properties
  Physical state
      Liquid
  Colour
      White, Various colours
  Odour / Odour threshold
      Faint
  рΗ
      8.6
  Density (g/cm<sup>3</sup>)
  Relative density
      1.25
  Kinematic viscosity
      >0.21 cm<sup>2</sup>/s (40 °C)
  Particle characteristics
      Does not apply to liquids.
Phase changes
  Melting point/Freezing point (°C)
      2
  Softening point/range (waxes and pastes) (°C)
      Does not apply to liquids.
  Boiling point (°C)
      42
  Vapour pressure
      (Weighted average, 23.4 mm Hg) 3.12 kPa (20 °C)
  Relative vapour density
      7.5
  Decomposition temperature (°C)
      Stable under normal handling and storage conditions.
Data on fire and explosion hazards
  Flash point (°C)
      Testing not relevant or not possible due to nature of the product.
  Flammability (°C)
      Not applicable - the product is not classified as flammable.
  Auto-ignition temperature (°C)
      Testing not relevant or not possible due to nature of the product.
  Lower and upper explosion limit (% v/v)
      Testing not relevant or not possible due to the nature of the product.
Solubility
  Solubility in water
      Partially soluble in cold water
  n-octanol/water coefficient
      Testing not relevant or not possible due to the nature of the product.
  Solubility in fat (g/L)
      Testing not relevant or not possible due to the nature of the product.
9.2. Other information
  Evaporation rate (n-butylacetate = 100)
      Testing not relevant or not possible due to nature of the product.
  VOC (g/L)
      19
```



Other physical and chemical parameters Volume Solids 27.0.0% +/- 1.0%. Weight Solids 42.0% +/- 1.0%. Oxidizing properties Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

- 10.3. Possibility of hazardous reactions
- None known.

10.4. Conditions to avoid None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Test method: Species: Route of exposure: Test: Result:	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] OECD 425 Rat Oral LD50 >5000 mg/kg
Product/substance Species: Route of exposure: Test: Result:	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] Rabbit Dermal LD50 >5000 mg/kg
Product/substance Species: Route of exposure: Test: Result:	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Rat Inhalation LC50 (4 hours) >6.8 mg/L
Product/substance	Calcium carbonate
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg
Product/substance	Propane-1,2-diol
Species:	Rat
Route of exposure:	Oral
Result:	22000 mg/kg
Product/substance	Propane-1,2-diol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg



Product/substance	Propane-1,2-diol
Species:	Rabbit
Route of exposure:	Inhalation
Test:	LC50 (2 hours)
Result:	>317 mg/L

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances considered to have hormone-disrupting properties in relation to health.

Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] has been classified by IARC as a group 2B carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m]
Species:	Fish, Pimephales promelas
Duration:	96 hours
Test:	LC50
Result:	>1000 mg/L
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m]
Test method:	OECD 202
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	LC50
Result:	>100 mg/L
Product/substance	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10
	µm]
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	EC50
Result:	16 mg/L
Result.	lo ng/L
Product/substance	Propane-1,2-diol
Species:	Fish, Oncorhynchus mykiss



Duration:	96 hours
Test:	LC50
Result:	40613 mg/L
Product/substance	Propane-1,2-diol
Species:	Daphnia, Ceriodaphnia dubia
Duration:	48 hours
Test:	EC50
Result:	18340 mg/L
Product/substance	Propane-1,2-diol
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	96 hours
Test:	EC50
Result:	19000 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 201
Species:	Fish, Oncorhynchus mykiss
Duration:	96 hours
Test:	LC50
Result:	0.22 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 211
Species:	Daphnia
Duration:	21 days
Test:	NOEC
Result:	0.004 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	ISO 10253 2006
Species:	Algae, Skeletonema costatum
Duration:	48 hours
Test:	NOEC
Result:	0.00064 mg/L
2.2. Persistence and degra No data available.	
2.3. Bioaccumulative pote Product/substance Potential bioaccumulation: LogPow: BCF:	Propane-1,2-diol
vPvB.	es not contain any substances considered to meet the criteria classifying them as PBT and/or
2.6. Endocrine disrupting This mixture/product do to the environment.2.7. Other adverse effects None known.	es not contain any substances considered to have endocrine-disrupting properties in relation
SECTION 13: Disposal cons	siderations

13.1. Waste treatment methods Product is covered by the regulations on hazardous waste. HP 7 – Carcinogenic Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste. EWC code Not applicable.



Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
ATA Packing	-	-	-	-	-	-
14.6. Spe Not aj 14.7. Ma	al inforn angerou ecial pre oplicable	nation s goods according to ADR, IATA and cautions for user e. ansport in bulk according to IMO ins				
SECTIO	N 15: Re	gulatory information				
Restri Pe Dema No SEVES No Additi No Sourc Co Re cla Re Re	ctions fo ople und nds for : o specific O - Cate t applica onal info t applica es mmissic gulation ssificatio gulation gistratio	or application der the age of 18 shall not be expose specific education requirements. gories / dangerous substances able. ormation able. on Regulation (EU) No 1357/2014 of 1 (EC) No 1272/2008 of the European on, labelling and packaging of substa	8 December 2014 on waste. Parliament and of the Council of 16 D ances and mixtures (CLP). Parliament and of the Council of 18 D	0ecembe	er 2008 (
SECTIO	N 16: Ot	ner information				
Full text	of H-phr	ases as mentioned in section 3				

EUH071, Corrosive to the respiratory tract.

- H301, Toxic if swallowed.
- H302, Harmful if swallowed.
- H310, Fatal in contact with skin.
- H314, Causes severe skin burns and eye damage.
- H315, Causes skin irritation.
- H317, May cause an allergic skin reaction.
- H318, Causes serious eye damage.
- H319, Causes serious eye irritation.
- H330, Fatal if inhaled.
- H351, Suspected of causing cancer.
- H400, Very toxic to aquatic life. H410, Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road



ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CE = Conformité Européenne (European conformity) CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EuPCS = European Product Categorisation System EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer (IARC) IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVBC = Unknown or variable composition, complex reaction products or of biological materials VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Additional information Not applicable. The safety data sheet is validated by EcoOnline Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en