

SAFETY DATA SHEET

Extra Plus Vinyl Matt

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Extra Plus Vinyl Matt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint or Paint related Material.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

FSW Coatings Ltd.

Ballaghanea, Virginia, A82 N267, Co Cavan,

Ireland.

353 49854 7209

E-mail

info@fsw.ie

Revision

15/11/2023

SDS Version

1.0

1.4. Emergency telephone number

The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am-10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

Prevention

Response

Storage

Disposal

Hazardous substances



titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17-XXXX Index No.: 022-006-00-2	5-10%	Carc. 2, H351	[17]
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH: 01-2120764691-48 Index No.: 613-167-00-5	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[17] The classification as a carcinogen is not taken into consideration when classifying the product as the product is not delivered in powder form/contains less than 1 % titanium dioxide on particle form with an aerodynamic diameter \leq 10 μ m (CLP, Annex VI, note 10).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Extra Plus Vinyl Matt Page 2 of 12



Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature



No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust) / 4(respirable dust)

Talc (Mg3H2(SiO3)4)

Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust)/ 0.8(respirable dust)

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust) / 4(respirable dust)

Calcium carbonate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust) / 4(respirable dust)

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

DNEL

Calcium carbonate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	1.06 mg/m³
Long term – Local effects - Workers	Inhalation	6.36 mg/m ³
Long term – Systemic effects - General population	Oral	6.1 mg/kg bw/day
Short term – Systemic effects - General population	Oral	6.1 mg/kg bw/day

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 μg/m³
Long term – Local effects - Workers	Inhalation	20 μg/m³
Short term – Local effects - General population	Inhalation	40 μg/m³
Short term – Local effects - Workers	Inhalation	40 μg/m³
Long term – Systemic effects - General population	Oral	90 μg/kgbw/day
Short term – Systemic effects - General population	Oral	110 μg/kgbw/day

Talc (Mg3H2(SiO3)4)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	2.27 mg/cm ²
Long term – Local effects - Workers	Dermal	4.54 mg/cm ²
Long term – Systemic effects - General population	Dermal	21.6 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	43.2 mg/kg bw/day
Long term – Local effects - General population	Inhalation	1.8 mg/m³
Long term – Local effects - Workers	Inhalation	3.6 mg/m ³
Long term – Systemic effects - General population	Inhalation	1.08 mg/m ³
Long term – Systemic effects - Workers	Inhalation	2.16 mg/m ³
Short term – Local effects - General population	Inhalation	1.8 mg/m³

Extra Plus Vinyl Matt Page 4 of 12



141.26 mg/L

141.26 mg/L

3.13 mg/kg

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Short term – Local effects - Workers	Inhalation	3.6 mg/m ³
Short term – Systemic effects - General population	Inhalation	1.08 mg/m ³
Short term – Systemic effects - Workers	Inhalation	2.16 mg/m ³
Long term – Systemic effects - General population	Oral	160 mg/kg bw/day
Short term – Systemic effects - General population	Oral	160 mg/kg bw/day
titanium dioxide; [in powder form containing 1 % or mo	re of particles with aerodynamic diar	meter ≤ 10 µm]
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	28 μg/m³
Long term – Local effects - General population	Inhalation	28 μg/m³
Long term – Local effects - General population	Inhalation	28 μg/m³
Long term – Local effects - Workers	Inhalation	170 μg/m³
Long term – Local effects - Workers	Inhalation	170 μg/m³
Long term – Local effects - Workers	Inhalation	170 μg/m³
Route of exposure: Sewage treatment plant	Duration of Exposure:	100 mg/L
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one	and 2 mathyl 2H isathianal 2 ana /2:	3
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		2 20 ug/l
		3.39 µg/L
Freshwater sediment		27 μg/kg
Freshwater sediment Intermittent release (freshwater)		
		27 μg/kg
Intermittent release (freshwater)		27 μg/kg 3.39 μg/L
Intermittent release (freshwater) Intermittent release (marine water)		27 μg/kg 3.39 μg/L 3.39 μg/L
Intermittent release (freshwater) Intermittent release (marine water) Marine water		27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L
Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment		27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L 27 μg/kg
Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment Sewage treatment plant		27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L 27 μg/kg 230 μg/L
Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment Sewage treatment plant Soil	Duration of Exposure:	27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L 27 μg/kg 230 μg/L
Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment Sewage treatment plant Soil Talc (Mg3H2(SiO3)4)	Duration of Exposure:	27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L 27 μg/kg 230 μg/L 10 μg/kg
Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment Sewage treatment plant Soil Talc (Mg3H2(SiO3)4) Route of exposure:	Duration of Exposure:	27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L 27 μg/kg 230 μg/L 10 μg/kg
Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment Sewage treatment plant Soil Talc (Mg3H2(SiO3)4) Route of exposure: Air	Duration of Exposure:	27 μg/kg 3.39 μg/L 3.39 μg/L 3.39 μg/L 27 μg/kg 230 μg/L 10 μg/kg PNEC: 10 mg/m³

8.2. Exposure controls

Marine water sediment

Marine water

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Intermittent release (marine water)

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and

Extra Plus Vinyl Matt Page 5 of 12



emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

No specific requirements.

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN374-3, EN388	

Eye protection

Туре	Standards

Safety glasses with side EN166 shields.





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Viscous, White

Odour / Odour threshold

Faint

рН

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

Relative density

1.46

Kinematic viscosity

0.21 cm²/s (40 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Vapour pressure

3.2 kPa (20 °C)

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)



Stable under normal handling and storage conditions.

Data on fire and explosion hazards

Flash point (°C)

Not applicable

Flammability (°C)

Not applicable

Auto-ignition temperature (°C)

Not applicable

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Slightly soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (q/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

Not applicable

VOC (g/L)

9

Other physical and chemical parameters

Volume Solids 34.0% +/- 1.0%. Weight Solids 54.0% +/- 1.0%.

Oxidizing properties

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Species: Rat Route of exposure: Oral

Result: 10000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Test method: OECD 425
Species: Rat
Route of exposure: Oral
Test: LD50
Result: >5000 mg/kg

Extra Plus Vinyl Matt Page 7 of 12



Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

µm]

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >5000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm] Rat

Rat

Species: Rat
Route of exposure: Inhalation
Test: LC50 (4 hours)
Result: >6.8 mg/L

Product/substance Calcium carbonate

Species:

Route of exposure: Oral
Test: LD50
Result: >2000 mg/kg

Product/substance Calcium carbonate

Test method: OECD 402
Species: Rat
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Species: Rat
Route of exposure: Oral
Test: LD50
Result: >5000 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m] has been classified by IARC as a group 2B carcinogen.



Talc (Mg3H2(SiO3)4) has been classified by IARC as a group 3 carcinogen.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] has been classified by IARC as a group 2B carcinogen.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] has been classified by IARC as a group 2B carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 Product/substance

um1

Species: Fish, Pimephales promelas

Duration: 96 hours Test: LC50 Result: >1000 mg/L

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

Test method: **OECD 202**

Species: Daphnia, Daphnia magna

Duration: 48 hours Test: LC50 >100 mg/L Result:

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

Species: Algae, Pseudokirchneriella subcapitata

Duration: 72 hours Test: EC50 Result: 16 mg/L

Product/substance Calcium carbonate

OECD 201 Test method:

Algae, Desmodesmus subspicatus Species:

Duration: 72 hours Test: EC50 Result: >14 mg/L

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

µm] **OECD 203** Test method: Fish 96 hours

Duration: Test: LC50 Result: >100 mg/L

Species:

Test method: Species:

Duration: Test:

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm] OECD 202 Daphnia 48 hours

EC50

>100 mg/L Result:

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: **OECD 201**

Fish, Oncorhynchus mykiss Species:

96 hours **Duration:** Test: LC50 Result: 0.22 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: **OECD 211** Species: Daphnia **Duration:** 21 days

Page 9 of 12 Extra Plus Vinyl Matt



Test: NOEC Result: 0.004 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: ISO 10253 2006

Species: Algae, Skeletonema costatum

Duration: 48 hours
Test: NOEC
Result: 0.00064 mg/L

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 7 - Carcinogenic

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 14.5 Other PG* Env** information:
ADR		-	
IMDG		-	
IATA		-	

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Extra Plus Vinyl Matt Page 10 of 12

^{**} Environmental hazards



Not applicable.

Additional information

Not applicable.

Sources

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract. H301, Toxic if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H351, Suspected of causing cancer.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average



UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

Christopher Murray

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en