

PRODUCT DESCRIPTION & USE

Fleetwood Timber Guard is a premium quality fence and shed treatment formulated to colour and protect rough sawn timber. This special formulation is water repellent and resist fading it also offers protection to exterior timber from the sun's harmful UV rays

KEY BENEFITS

- Easy application
- Quick drying
- Safe for use near plants and harmless to animals when dry

AVAILABLE IN SIZES



COLOURRANGE

Fleetwood Timber Guard

Available in various packaged colours.

VOC CONTENT

Contains max VOC; 13g/l
Conforms to EU 2010 Directive (Cat A/e) 130g/l

COMPOSITION (NOMINAL)

Pigment: Lightfast Pigments.
Binder: Copolymer emulsion
Solvent: Water.

SOLIDS - SPECIFIC GRAVITY

Volume Solids 6.5 % (+/- 2%)
Weight Solids 7.5 % (+/- 2%)
Specific Gravity 1.0 g/l (+/- 0.1)

SURFACE PREPARATION

Surfaces to be painted must be in sound condition. Ensure all timber is clean, dry and free from surface coatings, such as paint, varnish or polish. If the timber is affected by mould, lichen, algae or moss, use a fungicidal pre-treatment prior to application of Fleetwood Garden Timber Guard.

SPREADING RATE



As a guide approximately 4m²/l on rough sawn or 12m²/l on smooth planed depending on the nature and porosity of the surface being painted.

APPLICATION



Stir Fleetwood Garden Timber Guard thoroughly before and during use. Apply liberally and evenly onto exposed surfaces. Wash off any splashes on plants otherwise the foliage may be stained.

One coat is required on sound new timber, but two coats will increase the longevity. Old weathered timber or porous timber may require two coats. Do not apply to wet wood, or in temperatures below 10°C or when rain is imminent. The final colour will depend on the colour and porosity of the surface

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 45 minutes
Recoat: 1 – 2 hours

This is dependent upon temperature and humidity. Darker colours may take longer. 26°C to 50% RH @ 4 Thou wet.

CLEANING UP



Clean up with soap and water. After cleaning up be sure was brushes and equipment thoroughly. Dispose of can in accordance with local authority guidelines.

PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.

FOLLOW US ON

Online: www.fleetwood.ie
Email: info@fleetwood.ie
Phone: 049 8547209

