


### PRODUCT DESCRIPTION & USE

**Jacobi Antirust No.1** is a fast-drying lead-free rust-inhibitive alkyd metal primer

### KEY BENEFITS

- A high-quality alkyd based primer
- Suitable for interior and exterior use.
- Excellent opacity.
- Excellent adhesion

### AVAILABLE IN SIZES



### COLOUR RANGE

Jacobi Antirust No.1  
Grey

### VOC CONTENT

Contains max VOC; 339g/l  
Conforms to EU 2010 Directive (Cat A/g) 350g/l

### COMPOSITION (NOMINAL)

Pigment: Lightfast Pigments.  
Binder: Long oil alkyd resin  
Solvent: De-aromatized white spirit

### SOLIDS - SPECIFIC GRAVITY

Volume Solids 49.0% (+/- 2%)  
Weight Solids 65.0% (+/- 2%)  
Specific Gravity 1.30g/l (+/- 0.02)

### SURFACE PREPARATION

Surface must be dry and in sound condition. Remove oil, dust, loose rust, peeling paint or other contamination to ensure good adhesion.

Iron and Steel: For maximum durability of paint system, prepare the steel for painting in accordance with SSPC-SP6 Commercial Blast Cleaning. Minimum surface preparation should be no less than SSPC-SP2 Hand Tool Cleaning or SSPC-SP3 Power Tool Cleaning

### APPLICATION



This product may be spray applied but for H&S reasons related to all solvent-based paints, spray application is not recommended. As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

### SPREADING RATE



As a guide, a coverage rate of up to 15m<sup>2</sup> per litre can be achieved under normal conditions

### TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### SPRAY RECOMMENDATIONS

Conventional Spray: Satisfactory through most equipment.  
Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm<sup>2</sup> (2000 lb/sq in) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

### DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 4 - 6 hours  
Recoat: 16 -24 hours  
Hard Dry - 48 hours

This is dependent upon temperature and humidity. Darker colours may take longer.  
26°C to 50% RH @ 4 Thou wet

### CLEANING UP



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Dispose of cans and waste paint in accordance with local authority guidelines

### TINTING INSTRUCTIONS

Tint only with Fleetwood tinting systems

### PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. Flammable- keep away from sources of ignition. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.

### PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new. Wire brush galvanised steel to remove corrosion and degrease with suitable degreasing agent

### FOLLOW US ON

Online: [www.fleetwood.ie](http://www.fleetwood.ie)  
Email: [info@fleetwood.ie](mailto:info@fleetwood.ie)  
Phone: 049 8547209

