FLEETWOOD

- for COLOURFUL LIVES -

ProductPrestige SatinwoodRevision date19 March 2021Revision1

Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking				
1.1 Product identifier				
Prestige Satinwood				
No information available.				
1.2 Relevant identified uses of the substance or mixture and uses advised against				
Paint or paint related material.				
Any other purpose.				
1.3 Details of the supplier of the safety data sheet				
FSW Coatings Ltd.				
Virginia				
Co Cavan Ireland				
Tel: 353 49854 7209				
info@fsw.ie				
1.4 Emergency telephone number				
+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)				

Section 2: Hazards identification

2.1 Classification of the substance or mixture

	Classification (EC 1272/2008) Physical and chemical hazards Human health Environment	Not classified Not classified Not classified
<u>2.2</u>]	Label elements	
	Contains	Not applicable
	Label in accordance with (EC) no. 1272/2008	No pictogram required
	Signal word	No Signal Word
	Hazard statements	No hazard statements required
	Precautionary statements	No precautionary statements required
	EUH statements	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-XXXX		10-20%
Limestone	CAS-No.: 1317-65-3 EC No.: 215-279-6		1-5%
propane-1,2-diol	CAS-No.: 57-55-6 EC No.: 200-338-0 REACH Reg No.: 01-2119456809-23-0000		1-5%
glyoxal % ethandial %	CAS-No.: 107-22-2 EC No.: 203-474-9	Skin Irrit.2 - H315, Skin. Sens 1 - H317, Eye Irrit.2A - H319, Acute Tox 4 - H332, Muta. 2- H341	<0.1%
formaldehyde 100 %	CAS-No.: 50-00-0 EC No.: 200-001-8	Acute Tox 3 - H301, Acute Tox 2 - H310, Skin Corr. 1B - H314, Skin. Sens 1 - H317, Acute Tox 3 - H331, Muta. 2- H341, Carc. 1B - H350	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives. Formaldehyde: Specific Concentration Limits = Eye Irrit. 2; H319: 5 % <= C < 25 %, STOT SE 3; H335: C >= 5 %, Skin Corr. 1B; H314: C >= 25 %, Skin Irrit. 2; H315: 5 % <= C < 25 %, Skin Sens. 1; H317: C >= 0,2 %. This product is not classified as a carcinogen due to the liquid state of the product H351 as

This product is not classified as a carcinogen due to the liquid state of the product. H351 as related to Titanium Dioxide is only applicable in powdered form.

Section 4: First aid measures

<u>4.1 Description of first aid measures</u>

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor.
Inhalation	Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort or breathing difficulties develop.
Ingestion	Rinse mouth out and then drink plenty of water. Seek medical attention.
Skin contact	Remove affected person from source of contamination. Wash exposed area with soap and water. Get medical attention if irritation develops or persists.
Eye contact	Remove contact lenses if present and easy to do so. Hold eye lids open. Rinse with a gentle stream water for at least 15 minutes. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

The severity of the symptoms described will vary dependent on the concentration and the
length of exposure.
Inhalation of high concentrations of vapours may cause irritation of the respiratory tract or
dizziness.
Prolonged exposure to liquid product may cause irritation to linings of mouth,
Prolonged contact may cause redness, irritation and dry skin.
May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Section 5: Firefighting measures			
5.1 Extinguishing media			
Extinguishing media	This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry powder or carbon dioxide.		
Unsuitable extinguishing media	High volume water jet.		

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Unusual fire & explosion hazards Specific hazards	During fire, gases hazardous to health may be formed. No unusual fire or explosion hazards noted. Floors may become slippery, avoid falls.
5.3 Advice for firefighters	
Special fire fighting procedures	Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires from safe distance or protected location. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective eq	uipment and emergency procedures		
For non-emergency personnel For emergency responders	Wear protective clothing as described in Section 8 of this safety data sheet. Ensure adequate ventilation. Do not smoke, use open fire or other sources of ignition. Follow safe handling advice and personal protective equipment recommendations for normal		
	use of product.		
6.2 Environmental precautions			
Environmental precautions	Avoid discharge in to drains and water courses.		
6.3 Methods and material for containm	ent and cleaning up		
Spill clean up methods	Stop leak if possible without risk. Wear necessary protective equipment. Absorb spillage with non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage.		
6.4 Reference to other sections			
Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.		
Section 7: Handling and storage			
7.1 Precautions for safe handling			
Handling	Read and follow manufacturer's recommendations. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Do not eat, drink or smoke when using the product. Avoid spilling, skin and eye contact. Ensure adequate ventilation. Use proper personal protection when handling (refer to Section 8).		
7.2 Conditions for safe storage, including	ng any incompatibilities		
Storage precautions	Store in tightly closed original container in a cool, dry and well-ventilated place. Keep upright, locked up and out of reach of children.		
Storage class	Unspecified storage.		
7.3 Specific end use(s)			
Specific end use(s) Usage description	The identified uses for this product are detailed in Section 1. Use only according to directions. Replace and tighten cap after use.		

Section 8: Exposure controls/Personal protection


8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (2	15mins)	Notes
titanium dioxide	OEL		10 mg/m ³			
titanium dioxide	OEL		4 mg/m ³			
Limestone	OEL					
Limestone	OEL		4 mg/m ³			
propane-1,2-diol	OEL	150 ppm	470 mg/m ³			
propane-1,2-diol	OEL		10 mg/m ³			
glyoxal % ethandial %	OEL		0.1(IFV) mg/m ³			
formaldehyde 100 %	OEL	0.3 ppm	0.37 mg/m ³	0.6 ppm	0.738 mg/m ³	BOELV, Carc 1B, Sens, Limit value 0.5ppm/0.62mg/m3 for the healthcare, funeral and embalming sectors until 11 July 202420.

Ingredient comments

Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls



Engineering measures	Observe occupational exposure limits and minimize the risk of inhalation of dust.
Respiratory equipment	No specific recommendation made, but respiratory protection must be used if the general
	level exceeds the recommended occupational exposure limit. Use type ABEK (EN 14387) respirator cartridges.
	1 5
Hand protection	Use suitable protective gloves if there is a risk of skin contact. Full contact: Material: Nitrile
	rubber; Minimum layer thickness: 0.11mm ; Breakthrough time: 480 min. Consult
	manufacturer for specific advice.
Eye protection	Use equipment for eye protection tested and approved under appropriate government
	standards such as EN 166(EU).
Other protection	Wear appropriate clothing to prevent any possibility of skin contact. Protective clothing
	should be selected based on the task being performed and the risks involved and should be
	approved by a specialist before handling this product. The selected clothing must satisfy the
	European norm standard EN 943.
Hygiene measures	Wash hands and / or face before breaks and at the end of the shift. Do not eat, drink, or
	smoke while using this product. Avoid contact with skin, eyes and clothing.
Process conditions	Use only according to directions. Ensure that eye flushing systems and safety showers are
	located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Colour Odour	Viscous liquid. White and various colours. Slight.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	>8.1
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	May start to solidify at the temperatures below 2°C.This is based on data for the following ingredient: water
Initial boiling point and boiling range	>42°C

Flas	sh point	Not applicable.
Eva	poration rate	Not applicable.
Flai	mmability state	Non flammable
Flai	mmability limit - lower(%)	No information available as testing has not been completed.
Flai	mmability limit - upper(%)	0%
Vap	oour pressure	Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 3.12 kPa (23.4 mm Hg) (at 20°C)
Vap	oour density (air=1)	Highest known value: 7.5 (Air = 1) (isobutyric acid, monoester with 2,2, 4-trimethylpentan1,3-diol).
Rela	ative density	1.31
Bul	k density	No information available as testing has not been completed.
Solu	ubility	Partially soluble in cold water.
Dec	composition temperature	Stable under normal handling and storage conditions
	tition coefficient; n- anol/Water	No information available as testing has not been completed.
Aut	o ignition temperature (°C)	Not applicable.
Viso	cosity	Kinematic (40° C): >0.21 cm ² /s
Exp	losive properties	Not classified as explosive.
Oxi	dising properties	The product does not meet the criteria to be classified as oxidising.
9.2 Other information		
Mol	lecular weight	No information available as testing has not been completed.
Vola	atile organic compound	49.00 g/litre
Oth	er information	Volume solids: 39.0% +/- 1.0%
		Weight Solids: 53.0% +/- 1.0%.

Section 10: Stability and reactivity		
10.1 Reactivity		
Reactivity	No specific reactivity hazards associated with this product.	
10.2 Chemical stability		
Stability	Stable under normal temperature conditions and recommended use.	
10.3 Possibility of hazardous reactions		
Hazardous reactions Hazardous polymerisation Polymerisation description	For information on hazardous reactions see section 10.1. Unknown. Unknown.	
10.4 Conditions to Avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition. Extremes of temperature and direct sunlight.	
10.5 Incompatible materials		

```
Materials to avoid
```

Do not mix with other chemicals unless listed on directions. Strong oxidising substances.

10.6 Hazardous decomposition products

Hazardous decomposition products When heated, vapours/gases hazardous to health may be formed.

Section 11: Toxicological information

11.1 Information on hazard classses as defined in Regulation (EC) No. 1272/2008		
Toxicological information	No toxicological information for the overall finished product.	
Acute toxicity (Oral LD50) Acute toxicity (Dermal LD50) Acute toxicity (Inhalation LD50)	No information available as testing has not been completed. No information available as testing has not been completed. No information available as testing has not been completed.	
Serious eye damage/irritation	May cause temporary eye irritation.	
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.	
Respiratory sensitisation Skin sensitisation	The product is not classified as a respiratory hazard. The product is not classified as a skin sensitisation hazard.	
Germ cell mutagenicity	The product is not classified as a mutagen.	
Carcinogenicity	The product is not classified as a carcinogen hazard.	
Specific target organ toxicity - Single exposure:STOT - Single exposureThe product is not classified as a single exposure specific target organ toxin.Specific target organ toxicity - Repeated exposure:The product is not classified as a repeat exposure specific target organ toxin.STOT - Repeated exposureThe product is not classified as a repeat exposure specific target organ toxin.		
Inhalation	Inhalation of high concentrations of vapours may cause irritation of the respiratory tract or dizziness.	
Ingestion Skin contact Eye contact Waste management	Prolonged exposure to liquid product may cause irritation to linings of mouth, Prolonged contact may cause redness, irritation and dry skin. May cause temporary eye irritation. When handling waste, consideration should be made to the safety precautions applying to handling of the product.	
Routes of entry Target organs	Eyes, skin, ingestion or inhalation. Eyes, skin, digestive system, respiratory system.	
Aspiration hazards: Reproductive toxicity:	The product is not classified as an aspiration hazard. The product is not classified as a reproductive hazard.	

Name	LD50 oral	LD50 dermal	LD50 inhalation
propane-1,2-diol	22000.00mg/kg Rat	>2000.00mg/kg Rabbit	
formaldehyde 100 %	>200.00mg/kg Rat		
glyoxal % ethandial %	7070.00mg/kg Rat	10000.00mg/kg Rabbit	

11.2 Information on other hazards

Information on other hazards

None known.

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - FishNo information available as testing has not been completed.Acute toxicity - Aquatic invertebratesNo information available as testing has not been completed.Acute toxicity - Aquatic plantsNo information available as testing has not been completed.Acute toxicity - MicroorganismsNo information available as testing has not been completed.Chronic toxicity - FishNo information available as testing has not been completed.Chronic toxicity - AquaticNo information available as testing has not been completed.

invertebrates Chronic toxicity - Aquatic plants Chronic toxicity - Microorganisms Ecotoxicity Eco toxilogical information	No information available as testing has not been completed. No information available as testing has not been completed. The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.	
12.2 Persistence and degradability		
Degradability Biological oxygen demand Chemical oxygen demand	The degradability of the product has not been stated. No information available as testing has not been completed. No information available as testing has not been completed.	
12.3 Bioaccumulative potential		
Bioaccumulative potential Bioaccumulation factor Partition coefficient; n- Octanol/Water	No data available on bioaccumulation. No information available as testing has not been completed. No information available as testing has not been completed.	
12.4 Mobility in soil		
Mobility	Partially soluble in cold water.	
12.5 Results of PBT and vPvB assessment		
Results of PBT and vPvB assessment	The product does not contain any PBT or vPvB Substances.	
12.6 Endocrine disrupting properties		

Endocrine disrupting properties The product does not contain any substances with endocrine disrupting properties at a concentration above or equal to 0.1%.

12.7 Other adverse effects

Other adverse effects

None known.

	Acute toxicity (Fish)	invertebrates)	Acute toxicity (Aquatic plants)
propane-1,2-diol	LC50 96 Hours 40613.00mg/l Onchorhynchus mykiss (Rainbow Trout)		

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
3.1 Waste treatment methods	
Disposal methods	Dispose of waste and residues in accordance with local authority requirements, and in accordance with all local, national and international regulations. For waste disposal, use licensed industrial waste disposal agent.

Section 14: Transport information	
14.1 UN number or ID number	
UN no. (ADR) UN no. (IMDG) UN no. (IATA)	Not applicable. Not applicable. Not applicable.
14.2 UN proper shipping name	
ADR proper shipping name	Not applicable.

IMDG proper shipping name	Not applicable.		
IATA proper shipping name	Not applicable.		
<u>14.3 Transport hazard class(es)</u>			
ADR class	Not applicable.		
IMDG class	Not applicable.		
IATA class	Not applicable.		
Transport labels	Not applicable		
<u>14.4 Packing group</u>			
ADR/RID/ADN packing group	Not applicable.		
IMDG packing group	Not applicable.		
IATA packing group	Not applicable.		
14.5 Environmental hazards			
ADR	No		
IMDG	No		
IATA	No		
14.6 Special precautions for user			
EMS	Not applicable.		
Emergency action code	Not applicable.		
Hazard no. (ADR)	Not applicable.		
Tunnel restriction code	Not applicable.		

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
15.2 Chemical safety assessment	

Chemical safety assessment No chemical safety assessment has been carried out.

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a first issue.
Revision date	19 March 2021
Revision	1
Safety data sheet status	Approved.
ard statements in full	
	Causes serious are irritation
Н319	Causes serious eye irritation.
H319 H317	May cause an allergic skin reaction.
Н319	5

H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
EUH071	Corrosive to the respiratory tract.
H311	Toxic in contact with skin.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H410	Very toxic to aquatic life with long lasting effects.
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects .
H331	Toxic if inhaled.
H350	May cause cancer .
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray
	or mist.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.