

PRODUCT DESCRIPTION & USE

Ridgeway Spraycoat is a high-hiding vinyl matt paint designed to give maximum opacity. It is water-based, easy to apply and dries to a tough hard-wearing finish.

KEY BENEFITS

- Low odour
- Brilliant white matt finish
- High opacity

AVAILABLE IN SIZES



COLOUR RANGE

Ridgeway Spraycoat

Available in white and may be tinted using the Colour Answers Tinting system.

VOC CONTENT

Contains max VOC; 10 g/l
Conforms to EU 2010 Directive (Cat A/a) 30g/l

COMPOSITION (NOMINAL)

Pigment: Lightfast Pigments.
Binder: Vinyl acrylic
Solvent: Water.

SOLIDS - SPECIFIC GRAVITY

Volume Solids 29.5 % (+/- 2%)
Weight Solids 50.5 % (+/- 2%)
Specific Gravity 1.40 g/l (+/- 0.2)

SURFACE PREPARATION

Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease and flaking material. Treat powdery surfaces with Fleetwood Masonry Primer. Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Treat powdery surfaces with Fleetwood Masonry Primer. Use in accordance with good painting practices.

APPLICATION



Temperature (air, surface, material) (at least 4°C above dew point) 10°C to 42°C. Relative Humidity 75% maximum.

SPREADING RATE



As a guide a coverage rate of up to 12m²/litre can be achieved on non-porous surfaces under normal conditions.

REDUCTION

Reduce by up to 10% as required by application and/or equipment.

SPRAY RECOMMENDATIONS

Conventional Spray: Satisfactory through most equipment.
Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lbs/in²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 30 Mins

Recoat: 2-4 hours

This is dependent upon temperature and humidity. Darker colours may take longer. 26°C to 50% RH @ 4 Thou wet.

CLEANING UP



Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.

TINTING INSTRUCTIONS

Tint only with Fleetwood tinting systems

PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes, rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

PREVIOUSLY PAINTED SURFACES

All surfaces to be painted should be clean, dry and free from loose and flaking material. Glossy surfaces must be rubbed down to provide a key. Stir well before use. Avoid overspreading. For best results use a good quality synthetic brush. If using a roller, lay off to avoid pin-holing.

FOLLOW US ON

Online: www.fleetwood.ie

Email: info@fleetwood.ie

Phone: 049 8547209

