

#### SAFETY DATA SHEET

# Soft Sheen Base

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

Soft Sheen Base

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

**Paint** 

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

### Company and address

### **FSW Coatings Ltd.**

Ballaghanea, Virginia,

A82 N267, Co Cavan,

Ireland.

353 49854 7209

E-mail

info@fsw.ie

Revision

08/11/2023

SDS Version

1.0

### 1.4. Emergency telephone number

The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am-10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

### 2.2. Label elements

# Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

## Precautionary statement(s)

General

Prevention

# Response

# Storage

# Disposal

Hazardous substances





titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Additional labelling

EUH208, Contains 2-methylisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one,

2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3. Other hazards

#### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17-XXXX Index No.: 022-006-00-2	15-25%	Carc. 2, H351	[17]
Calcium carbonate	CAS No.: 1317-65-3 EC No.: 215-279-6 REACH: Index No.:	5-10%		[19]
1,2-benzisothiazol-3(2H)- one;1,2-benzisothiazolin-3- one	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: Index No.: 613-088-00-6	0.01-0.049%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH: 01-2120764691-48 Index No.: 613-167-00-5	0.0010-0.0014%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[17] The classification as a carcinogen is not taken into consideration when classifying the product as the product is not delivered in powder form/contains less than 1 % titanium dioxide on particle form with an aerodynamic diameter  $\leq$  10  $\mu$ m (CLP, Annex VI, note 10).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

### SECTION 4: First aid measures

# 4.1. Description of first aid measures General information

Soft Sheen Base Page 2 of 11



In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

### Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Rurns

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### Information to medics

Bring this safety data sheet or the label from this product.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

Some metal oxides

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

### SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

Soft Sheen Base



See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

No specific requirements

### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq$  10 µm] Long term exposure limit (8 hours) (mg/m³): 10(total inhalable dust) / 4(respirable dust)

#### Calcium carbonate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

#### Propane-1,2-diol

Long term exposure limit (8 hours) (mg/m³): 470 (total (vapour and particulates)) / 10(particulates) Long term exposure limit (8 hours) (ppm): 150 (total (vapour and particulates))

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

#### **DNEL**

Propane-1,2-diol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	10 mg/m³
Long term – Local effects - Workers	Inhalation	10 mg/m³
Long term – Systemic effects - General population	Inhalation	50 mg/m³
Long term – Systemic effects - Workers	Inhalation	168 mg/m³

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 μg/m³
Long term – Local effects - Workers	Inhalation	20 μg/m³
Short term – Local effects - General population	Inhalation	40 μg/m³
Short term – Local effects - Workers	Inhalation	40 μg/m³
Long term – Systemic effects - General population	Oral	90 μg/kgbw/day
Short term – Systemic effects - General population	Oral	110 μg/kgbw/day

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Duration:	,	Route of exposure:	DNEL:
Long term – Local effects - General population		Inhalation	28 μg/m³
Long term – Local effects - Workers		Inhalation	170 μg/m³

Soft Sheen Base Page 4 of 11



#### **PNEC**

Propane-	1,2-diol	
----------	----------	--

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		260 mg/L
Freshwater sediment		572 mg/kg
Intermittent release (freshwater)		183 mg/L
Marine water		26 mg/L
Marine water sediment		57.2 mg/kg
Sewage treatment plant		20 g/L
Soil		50 mg/kg

#### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.39 µg/L
Freshwater sediment		27 μg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 μg/kg
Sewage treatment plant		230 μg/L
Soil		10 μg/kg

### 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

#### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements.

# Individual protection measures, such as personal protective equipment

### Generally

Use only CE marked protective equipment.

#### Respiratory Equipment

No specific requirements

### Skin protection

No specific requirements.

#### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN374-3, EN388	

#### Eye protection

Soft Sheen Base Page 5 of 11



Type Standards

Safety glasses with side EN166 shields.



### SECTION 9: Physical and chemical properties

```
9.1. Information on basic physical and chemical properties
  Physical state
      Liquid
      White, Various colours
  Odour / Odour threshold
      Faint
  рΗ
      8.6
  Density (g/cm³)
  Relative density
      1.25
  Kinematic viscosity
      >0.21 cm<sup>2</sup>/s (40 °C)
  Particle characteristics
      Does not apply to liquids.
Phase changes
  Melting point/Freezing point (°C)
      2
  Softening point/range (waxes and pastes) (°C)
      Does not apply to liquids.
  Boiling point (°C)
      42
  Vapour pressure
      (Weighted average, 23.4 mm Hg) 3.12 kPa (20 °C)
  Relative vapour density
      7.5
  Decomposition temperature (°C)
      Stable under normal handling and storage conditions.
Data on fire and explosion hazards
  Flash point (°C)
      Testing not relevant or not possible due to nature of the product.
  Flammability (°C)
      Not applicable - the product is not classified as flammable.
  Auto-ignition temperature (°C)
      Testing not relevant or not possible due to nature of the product.
  Lower and upper explosion limit (% v/v)
      Testing not relevant or not possible due to the nature of the product.
Solubility
  Solubility in water
      Partially soluble in cold water
  n-octanol/water coefficient
      Testing not relevant or not possible due to the nature of the product.
  Solubility in fat (g/L)
      Testing not relevant or not possible due to the nature of the product.
9.2. Other information
  Evaporation rate (n-butylacetate = 100)
      Testing not relevant or not possible due to nature of the product.
  VOC (g/L)
      19
```



### Other physical and chemical parameters

Volume Solids 27.0.0% +/- 1.0%. Weight Solids 42.0% +/- 1.0%.

### Oxidizing properties

Not applicable

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Test method: OECD 425
Species: Rat
Route of exposure: Oral
Test: LD50
Result: >5000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]
Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >5000 mg/kg

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm] Rat

Species: Rat
Route of exposure: Inhalation
Test: LC50 (4 hours)
Result: >6.8 mg/L

Product/substance Calcium carbonate

Species: Rat
Route of exposure: Oral
Test: LD50

Result: >5000 mg/kg

Product/substance Propane-1,2-diol Species: Rat

Route of exposure: Oral

Result: 22000 mg/kg

Product/substance Propane-1,2-diol

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg

Soft Sheen Base Page 7 of 11





Product/substance Propane-1,2-diol Species: Rabbit Route of exposure: Inhalation LC50 (2 hours) Result: >317 mg/L

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eve damage/irritation

Based on available data, the classification criteria are not met.

### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### Long term effects

None known.

### Endocrine disrupting properties

This mixture/product does not contain any substances considered to have hormone-disrupting properties in relation to health.

#### Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq$  10 µm] has been classified by IARC as a group 2B carcinogen.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

µm]

Species: Fish, Pimephales promelas

Duration: 96 hours
Test: LC50
Result: >1000 mg/L

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

μm]

Test method: OECD 202

Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: LC50
Result: >100 mg/L

Product/substance titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

um1

Species: Algae, Pseudokirchneriella subcapitata

Duration: 72 hours
Test: EC50
Result: 16 mg/L

Product/substance Propane-1,2-diol

Species: Fish, Oncorhynchus mykiss

Soft Sheen Base Page 8 of 11



 Duration:
 96 hours

 Test:
 LC50

 Result:
 40613 mg/L

Product/substance Propane-1,2-diol

Species: Daphnia, Ceriodaphnia dubia

 Duration:
 48 hours

 Test:
 EC50

 Result:
 18340 mg/L

Product/substance Propane-1,2-diol

Species: Algae, Pseudokirchneriella subcapitata

Duration: 96 hours
Test: EC50
Result: 19000 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 201

Species: Fish, Oncorhynchus mykiss

 Duration:
 96 hours

 Test:
 LC50

 Result:
 0.22 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 211
Species: Daphnia
Duration: 21 days
Test: NOEC
Result: 0.004 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: ISO 10253 2006

Species: Algae, Skeletonema costatum

Duration: 48 hours
Test: NOEC
Result: 0.00064 mg/L

# 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

Product/substance Propane-1,2-diol Potential bioaccumulation: No data available.

LogPow: -0.92

BCF: No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

None known.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 7 - Carcinogenic

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

#### **EWC** code

Not applicable.

Soft Sheen Base Page 9 of 11

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

### **SECTION 14: Transport information**

	14.1 UN /	14.2 ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

<sup>\*</sup> Packing group

#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

Not applicable.

#### Sources

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

Nο

#### SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H351, Suspected of causing cancer.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

<sup>\*\*</sup> Environmental hazards





ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

### Additional information

Not applicable.

# The safety data sheet is validated by

EcoOnline

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en