

## TECHNICAL DATA F430

## **DAMP**

## & Water Mark Primer

FLEETWOOD DAMP and Water Mark Primer is a solvent based primer with relatively little odour.  RECOMMENDED USE:  FLEETWOOD DAMP and Water Mark Primer is designed to seal in and obliterate watermarks and staining caused by leaking pipes or damp and prevent their reappearance on the surface  AVAILABILITY:  0.5 - 1.0 - 2.5litre  FinnSH:  1.48 +/- 0.1  Volume SOLIDS:  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  SPREADING RATE:  9m² per litre  VOC:  270g/litre  PREADING RATE:  10 by a howe 41  PRECAUTIONS:  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying, in case of contact with eyes rise imse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.  Sir thoroughly before use and apply using a synthetic brush or mohair roller. Apply 2 coats. Do not apply in temperatures below 10°C.  For Health & Safety reasons; relating to all solvent based paints, spray application is not recommended.  SURFACE PREPARATION:  CLEAN UP:  After use, remove as much product as possible from equipment before cleaning with brush cleaner.  White spirit.  Sin defective or poorly achering material such as sugar soap. I	CHARACTERIS	TICS	APPLICATION:		COMPOS	SITION:
Mark Primer is a solvent based primer with relatively little odour.  RECOMMENDED USE:  FLEETWOOD DAMP and Water Mark Primer is designed to seal in and obliterate watermarks and staining caused by leaking pipes or damp and prevent their reappearance on the surface  AVAILABILITY:  0.5 - 1.0 - 2.5litre  FIRT matt  COLOUR:  Flat matt  COLOUR:  White  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying: in case of contact with eyes.  To remove splashes from skin use soap and water or a recognised skin-cleaner. Do not take internally.  Apply using a synthetic brush or mohair roller. Apply 2 coats. Do not apply 1 temperatures below 10°C.  For Health & Safety reasons; relating to all solvent based paints, spray application is not recommended.  AWAILABILITY:  To get the best results, ensure surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  PLASH POINT:  Above 41 °C (closed cup)  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  Proceedings and water or a recognised skin, elementally.					OCIVII O	OTTION.
prime with relatively little doubt.  FLEETWOOD DAMP and Water Mark Primer is designed to seal in and obliterate watermarks and staining caused by leaking pipes or damp and prevent their eappearance on the surface application is not recommended.  AVAILABILITY:  SURFACE PREPARATION:  Flat matt  COLOUR:  White  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying; in case of contact with eyes.  Flat math defective or poorly adhering material such as dirt, grease or wax.  If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying; in case of contact with eyes.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not atake internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not atake internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not atake internally.	Mark Primer is a solvent based		apply using a synthetic brush or mohair roller. Apply 2 coats. Do not apply in temperatures below 10°C. For Health & Safety reasons; relating		Pigment: Lightfast Pigments.	
recommended used in and obliterate watermarks and staining caused by leaking pipes or damp and prevent their reappearance on the surface  AVAILABILITY:  0.5 - 1.0 - 2.5 litre reappearance on the surface  SURFACE PREPARATION:  To get the best results, ensure surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  SPREADING RATE:  9m² per litre VOC:  270g/litre  DRYING TIME:  DRYING TIME:  DRYING TIME:  DRYING TIME:  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying, in case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.					Binder:	Alkyd.
FILEETWOOD DAMP and Water Mark Primer is designed to seal in and obliterate watermarks and staining caused by leaking pipes or damp and prevent their reappearance on the surface all solvent based paints, spray application is not recommended.  AVAILABILITY:  O.5 - 1.0 - 2.5litre  FINISH:  To get the best results, ensure surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  SPECIFIC GRAVITY:  I.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  Allow the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.	RECOMMENDED USE:					•
For Health & Safety reasons; relating to all solvent based paints, spray application is not recommended.  AVAILABILITY:  O.5 – 1.0 – 2.5litre  FINISH:  OIT	Mark Primer is designed to seal in and obliterate watermarks and staining caused by leaking pipes or				Solvent. Write Spirit.	
to all solvent based paints, spray application is not recommended.  AVAILABILITY:  0.5 – 1.0 – 2.5 litre  FINISH:  To get the best results, ensure surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  270g/litre  DRYING TIME:  Touch Dry 2 hours Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.						
reappearance on the surface  AVAILABILITY:  0.5 - 1.0 - 2.5litre  FINISH:  To get the best results, ensure surface to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Donot take intermally.  SURFACE PREPARATION:  CLEAN UP:  After use, remove as much product as possible from equipment before cleaning with brush cleaner.  When finished with this paint container please dispose of responsibly, your local authority provides bring centres where paint and empty cans can be deposited.  OVERCOATING:  FLEETWOOD DAMP and Water Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  For remove splashes from skin use soap and water or a recognised skin cleaner. Do not take intermally.						
AVAILABILITY:  0.5 – 1.0 – 2.5litre FINISH:  To get the best results, ensure surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre VOC:  2770g/litre  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take intermally.  SURFACE PREPARATION:  To get the best results, ensure surfaces to de positive, cleaning with brush cleaner.  When finished with this paint container please dispose of responsibly, your local authority provides bring centres where paint and empty cans can be deposited.  OVERCOATING:  FLASH POINT:  Above 41  OC (closed cup)  For ceilings it is recommended to apply Fleetwood Ceiling Paint.						
FINISH:  Flat matt  COLOUR:  White  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or on a take internally.  To get the best results, ensure surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  If there is heavy soiling it is recommended that the surface to be prime dis washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  After use, remove as much product as possible from equipment before cleaning with brush cleaner.  When finished with this paint container please dispose of responsibly, your local authority provides bring centres where paint and empty cans can be deposited.  OVERCOATING:  FLEETWOOD DAMP and Water Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.						
FINISH:  Flat matt  COLOUR:  White  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use sound, clean relatively dry and free from all defective or poorly adhering material surface so wax.  If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  Above 41  OVERCOATING:  FLEETWOOD DAMP and Water Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  For remove splashes from skin use soap and water or a recognised skin cleaner.	AVAILABILITY:		SURFACE PREPARATION:		CLEAN UP:	
FINISH:  Flat matt  COLOUR:  White  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventitation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use sona and water or a recognised skin cleaner.  Surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  FLASH POINT:  Above 41 °C (closed cup)  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.	0.5 - 1.0 - 2.5litre		surfaces to be painted are sound, clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.		possible from equipment before cleaning with brush cleaner.  When finished with this paint container please dispose of responsibly, your local authority provides bring centres where paint and empty cans can be deposited.	
COLOUR:  White  SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  Clean relatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  When finished with this paint container please dispose of responsibly, your local authority provides bring centres where paint and empty cans can be deposited.  OVERCOATING:  FLEETWOOD DAMP and Water Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  For cemondatively dry and free from all defective or poorly adhering material such as dirt, grease or wax.  When finished with this paint container please dispose of responsibly, your local authority provides bring centres where paint and empty cans can be deposited.  OVERCOATING:  FLEETWOOD DAMP and Water  Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.	FINISH:					
SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  410w the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use such as dirt, grease or wax.  If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  Above 41  OVERCOATING:  FLETWOOD DAMP and Water Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.  For remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.	Flat matt					
SPECIFIC GRAVITY:  1.48 +/- 0.1  VOLUME SOLIDS:  60%  SPREADING RATE:  9m² per litre  VOC:  270g/litre  DRYING TIME:  Touch Dry 2 hours Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.	COLOUR:					
If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.    VOC:	White					
Tecommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  Touch DS:  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  To remove splashes from skin use soap and water or a recognised skin cleaner.	SPECIFIC GRAVITY:					
primed is washed thoroughly with a detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.						
SPREADING RATE:  9m² per litre  VOC:  270g/litre  270g/litre  DRYING TIME:  Touch Dry 2 hours Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  detergent such as sugar soap. If mould is present pre-treat with Fleetwood Mould Remover.  Allow the surface to dry completely before priming.  FLASH POINT:  Above 41 °C (closed cup)  For ceilings it is recommended to apply Fleetwood Ceiling Paint.						
SPREADING RATE:						
VOC:  Allow the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  Mould Remover.  Allow the surface to dry completely before priming.  Above 41  OC (closed cup)  For ceilings it is recommended to apply Fleetwood Ceiling Paint.					OVERCO	DATING:
Allow the surface to dry completely before priming.  DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  Allow the surface to dry completely before priming.  Mark Primer provides an ideal base coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.	·					
DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  before priming.  Coat for subsequent water based or solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.	VOC:					
DRYING TIME:  Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  solvent based topcoats.  For ceilings it is recommended to apply Fleetwood Ceiling Paint.		270g/litre		,	coat for sul	bsequent water based or
Touch Dry 2 hours  Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.  Above 41  OC (closed cup)  For ceilings it is recommended to apply Fleetwood Ceiling Paint.	DRYING TIME:		, ,		solvent based topcoats.	
Recoat overnight  PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.		2 hours		°C (closed cup)		
PRECAUTIONS:  Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.			ADOVE TI	o (cioseu cup)	_	
Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.					apply Fleet	twood Ceiling Paint.
good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.						
drying. In case of contact with eyes rinse immediately with plenty of water.  To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.						
To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.	drying. In case of contact with eyes					
soap and water or a recognised skin cleaner. Do not take internally.	rinse immediately w	rim pienty of water.				
cleaner. Do not take internally.						
Contains no added lead.	cleaner. Do not take	e internally.				
	Contains no added	lead.				