

STAINS

Blocking Primer

CHARACTERISTICS:	APPLICATION:	THINING:
FLEETWOOD Stains Blocking Primer is a quick drying interior stain preventative primer.	Stir thoroughly before use and apply using a synthetic brush or mohair roller. Apply 2 coats. Do not apply in temperatures below 10°C.	Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint. Conventional spray application: Add up to 1 part clean water to 2.5 parts paint. Airless spray application: Add up to 1 part clean water to 5 parts paint.
RECOMMENDED USE:		
FLEETWOOD Stains Blocking Primer is a multi-surface primer designed to seal in common stains such as coffee, tea, wine, permanent marker, grease spots, crayons and ketchup from bleeding through into the top-coat.		
AVAILABILITY:	SURFACE PREPARATION	VOC:
0.5 – 1.0 – 2.5litre	To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease or wax. If there is heavy soiling it is recommended that the surface to be primed is washed thoroughly with a detergent such as sugar soap. Allow the surface to dry completely before priming. Stain ghosting can sometimes be present in the primer coat but this will not migrate into the top-coat	16g/litre
FINISH:		SPRAY RECCOMENDATIONS:
Flat matt		Conventional Spray: Satisfactory through most equipment.
COLOUR:		Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars with a spray tip size of 0.43mm and a spray tip angle of 60°C
White		
SPECIFIC GRAVITY:		
1.29 +/- 0.2		
VOLUME SOLIDS:		
34%		
SPREADING RATE:		
12m ² per litre		
DRYING TIME:		
Touch Dry 30 minutes		
Recoat 4 hours		
PRECAUTIONS:	CLEAN UP:	
Keep out of reach of children. Ensure good ventilation during application and drying. In case of contact with eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.	Clean up with soap and water. After clean-up be sure to flush any spray equipment with solvent to prevent rusting.	