



# Fleetwood

## TECHNICAL DATA

# F821

# TOPLINE VINYL MATT EMULSION

CHARACTERISTICS	APPLICATION	SURFACE PREPARATION
A Vinyl Matt Emulsion especially formulated for the professional painter. This product provides a combination of excellent coverage, whiteness and application. Matt finish for all colours plus a Brilliant White.	Temperature (air, surface, material) (at least 4°C above dew point) 10°C to 42°C. Relative Humidity 75% Maximum.	Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease and flaking material. Treat powdery surfaces with Water Based Stabilising Solution.
<b>DRYING SCHEDULE</b> (Temperature and humidity dependant) @ 26°C 50% RH @ 4 Thou wet. To Touch:- 30 mins To Dry:- 4 hours	<b>SPREADING RATE</b> 150m <sup>2</sup> /10lt 75m <sup>2</sup> /5lt 37.5m <sup>2</sup> /2.5lt	Steel:- Remove all loose rust, peeling paint, other loosely adhering contaminations per SSPC SP2. Hand tool cleaning. Remove any contamination before applying subsequent coats of material. Prime base steel with an appropriate anti-corrosive primer.
<b>SPECIFIC GRAVITY</b> 1.41+/-0.01	<b>METHODS</b> Brush, roller, airless spray. Airless Spray:- Minimum pressure 138 bars (2000lb.sq in). Tip Size:- 0.38mm - 0.46mm (15-18 Thou). Filter:- 60 mesh. Angle:- 65 degrees Always flush spray equipment with water prior to applying Water Based Coatings.	Concrete Block and Masonry:- Surfaces should be thoroughly clean and dry, with mortar and concrete aired for a minimum of 30 days @ 24°C. All loose mortar or other contaminants should be removed prior to application of any coating material. Surface temperatures must be at least 12°C before filling. Use appropriate filler for cracks or imperfections. Allow to dry thoroughly before top coating.
<b>WEIGHT SOLIDS</b> 49+/-1%	<b>MIXING INSTRUCTIONS</b> Thoroughly mix paint before use by stirring and boxing.	<b>PREVIOUSLY PAINTED SURFACES</b> If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.
<b>VOLUME SOLIDS</b> 29+/-1%	<b>TINTING INSTRUCTIONS</b> Tint only with the Fleetwood Tinting System.	
<b>PRECAUTIONS</b> <i>Keep out of reach of children. Ensure good ventilation during application and drying.</i>  <i>In case of contact with eyes rinse immediately with plenty of water.</i>  <i>To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.</i>	<b>CLEAN UP</b> Clean up with soap and water. After clean up be sure to flush spray equipment with solvent to prevent rusting following manufacturers instructions	
	<b>REDUCTION</b> Reduce up to 20% with water as required by application equipment.	

ISSUE NO.1 6/2000

Fleetwood Paints Ltd/FSW Coatings Ltd., Virginia, Co.Cavan. Ireland. Tel +353 49 8547209 Fax +353 49 8547470

Email: [info@fleetwood.ie](mailto:info@fleetwood.ie) [info@fsw.ie](mailto:info@fsw.ie) Web: [www.fleetwood.ie](http://www.fleetwood.ie)