Product Fleetwood Weathercover

Revision date 18 May 2017

Revision 1



Safety Data Sheet (SDS)

Section 1: Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Product name Fleetwood Weathercover Synonyms, Trade names No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint or paint related material.

Uses advised against Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd

Virginia Co Cavan Ireland

Tel: 353 49854 7209

Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone + 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Not classified Human health Not classified

Environment Aquatic Chronic 3 - H412

2.2 Label elements

Contains Not applicable

Label in accordance with (EC) no.

1272/2008

No pictogram required

Signal word No Signal Word

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements Prevention

P273 Avoid release to the environment.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
Limestone	CAS-No.: 1317-65-3 EC No.: 215-279-6		10-30%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0002		1-10%
Talc (Mg3H2(SiO3)4)	CAS-No.: 14807-96-6 EC No.: 238-877-9		1-10%
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	CAS-No.: 25265-77-4 EC No.: 246-771-9 REACH Reg No.: 01-2119441305-48-0002		1-10%
Alcohols C10-16, ethoxylated propoxylated	CAS-No.: 69227-22-1 EC No.: REACH Reg No.: 02-2119752839-21-0000		0-1%
diiron trioxide	CAS-No.: 1309-37-1 EC No.: 215-168-2		0-1%
2,2'-oxydiethanol	CAS-No.: 111-46-6 EC No.: 203-872-2 REACH Reg No.: 01-2119457857-21-0000	Acute Tox 4 - H302, STOT RE 2 - H373	0-1%
diuron (ISO) 3-(3,4-dichlorophenyl),1-dimethylurea	CAS-No.: 330-54-1 EC No.: 206-354-4	Acute Tox 4 - H302, Carc. 2 - H351, STOT RE 2 - H373, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	0-1%
zinc oxide	CAS-No.: 1314-13-2 EC No.: 215-222-5 REACH Reg No.: 01-2119463881-32-0000	Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	0-1%
MICA	CAS-No.: 12001-26-2 EC No.:		0-1%
cristobalite	CAS-No.: 14464-46-1 EC No.: 238-455-4	STOT RE 1 - H372	0-1%
Quartz (SiO2)	CAS-No.: 14808-60-7 EC No.: 238-878-4		0-1%

The full text for all hazard statements are displayed in section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures

4.1 Description of first aid measures

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if General information

> symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during

rescue.

Inhalation Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort or breathing difficulties develop.

Ingestion If this product is ingested, remove victim immediately from source of exposure. Provide fresh

air, warmth and rest, preferably in comfortable upright sitting position. Never give anything by mouth to an unconscious person. Rinse mouth out and then drink plenty of water. Seek

medical attention.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing and

shoes and wash before reuse. Wash exposed area with soap and water. Continue to rinse for

at least 15 minutes. Get medical attention if irritation develops or persists.

Eye contact Avoid contaminating unaffected eye. Remove contact lenses if present and easy to do so.

Hold eye lids open. Rinse with a gentle stream water for at least 15 minutes. Seek medical

attention.

4.2 Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Inhalation of mist or vapor may cause respiratory tract irritation.

May cause discomfort if swallowed. May cause stomach pain or vomiting. Ingestion

Skin contact Eye contact

Prolonged contact may cause redness, irritation and dry skin.

Prolonged contact may cause redness and/or tearing.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician Treat symptomatically.

Section 5: Fire-fighting measures

5.1 Extinguishing media

Extinguishing media Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry

powder or carbon dioxide.

Unsuitable extinguishing media

None noted.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Unusual fire & explosion hazards When heated, vapours/gases hazardous to health may be formed. No unusual fire or explosion hazards noted.

Specific hazards

In case of fire, toxic gases may be formed (COx, NOx). Avoid breathing fumes. Do not allow

run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special fire fighting procedures

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires from safe distance or protected location. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so. Protective equipment for firefighters Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard

EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation

> of vapours and contact with skin and eyes. Eliminate all sources of ignition. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Wash hands after

Follow safe handling advice and personal protective equipment recommendations for normal For emergency responders

use of product.

6.2 Environmental precautions

Environmental precautions Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency

or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Ventilate and evacuate the area. Stop leak if possible without risk. Wear necessary protective Spill clean up methods

> equipment. Absorb spillage with non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in

a suitably labelled container.

6.4 Reference to other sections

Reference to other sections See section 1 for emergency contact. For personal protection, see section 8. For waste

disposal, see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment. Do not use contact lenses. Keep away from heat, sparks and open flame. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Do not eat, drink or smoke when using the product.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a cool, dry and well-ventilated place. Keep

upright, locked up and out of reach of children. Store in cool dry areas away from direct

sunlight or sources of ignition.

Storage class Unspecified storage.

7.3 Specific end use(s)

Specific end use(s)The identified uses for this product are detailed in Section 1.Usage descriptionUse only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (1	5mins)	Notes
Limestone	OEL		10 mg/m ³			Total inhalable dust.
Limestone	OEL		4 mg/m ³			Total respirable dust.
titanium dioxide	OEL		10 mg/m ³			Total inhalable dust.
titanium dioxide	OEL		4 mg/m ³			Respirable dust.
Talc (Mg3H2(SiO3)4)	OEL		10 mg/m ³			Total inhalable dust.
Talc (Mg3H2(SiO3)4)	OEL		0.8 mg/m^3			Respirable dust.
diiron trioxide	OEL		5 mg/m ³		10 mg/m ³	Fume (as Fe.)
diiron trioxide	OEL		10 mg/m ³			Total inhalable dust.
diiron trioxide	OEL		4 mg/m ³			Respirable dust.
2,2'-oxydiethanol	OEL	23 ppm	100 mg/m ³			
diuron (ISO) 3-(3,4-dichlorophenyl),1-dimethylurea	OEL		10 mg/m ³			
zinc oxide	OEL		2 (R) mg/m ³		10 mg/m ³	Fume.
MICA	OEL		10 mg/m ³	·		Total inhalable dust.
MICA	OEL		0.8 mg/m^3			Respirable dust.
cristobalite	OEL		0.1 mg/m^3			Respirable dust.
Quartz (SiO2)	OEL		0.1 mg/m ³			Respirable dust.

Ingredient comments

Ireland, Occupational Exposure Limits 2016.

8.2 Exposure Controls

Protective equipment





Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN 143 should be used, and suitable respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. ABEK (EN 14387). Consult manufacturer for specific advice.

Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use respiratory protection as specified by an industrial hygienist or other qualified professional if concentrations exceed the limits listed in Section 8

Hand protection

Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe:

EN374) is recommended. Gloves must be inspected prior to use.

Suggested material: Nitrile rubber. Break through time: >480 minutes. Minimum layer thickness: 0.33 mm. Chloroprene. Breakthrough time: >480 minutes. Minimum layer

thickness: 0.6 mm. Consult manufacturer for specific advice.

Eye protection Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment

for eye protection tested and approved under appropriate government standards such as EN

166(EU).

Other protection Wear appropriate clothing to prevent skin contact. Protective clothing should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Hygiene measures Immediately take off any contaminated clothing and launder before re-use. Wash promptly if

skin becomes contaminated. Wash hands after handling. Do not eat, drink, or smoke while

using this product.

Process conditions Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

AppearanceViscous liquid.ColourWhite. Opaque.OdourFaint odour.

Odour threshold - lower No information available.

Odour threshold - upper No information available.

pH-Value, Conc. Solution 7.5 - 9.0.

pH-Value, Diluted solution No information available.

Melting point May start to solidify at temperatures below 2°C. This is based on data for the following

ingredient: Water.

Initial boiling point and boiling

range

38.00 °C

Flash point Closed cup: Not applicable. (Product does not sustain combustion.)

Evaporation rate No information available.

Flammability state Non flammable.

Flammability limit - lower(%) Not applicable.

Flammability limit - upper(%) Not applicable.

Vapour pressure Highest known value: 3.2 kPa (23.8 mmHg) at 20°C (water). Weighted average: 3.12 kPa

(23.4 mmHg) at 20 $^{\circ}$ C.

Vapour density (air=1) Highest known value: 7.5 (Air=1); (isobutryic acid, monoester with 2,2, 4-trimethylpentan-

1,3-diol.)

Relative density 1.55g/cm³ @ 20.00 °C

Bulk density No information available.

Solubility Partially soluble in cold water.

Decomposition temperature No information available.

Partition coefficient; n-

Octanol/Water

No information available.

Auto ignition temperature (°C) Not applicable.

Viscosity Kinematic (40°C): >0.21 cm2/s.

Explosive properties Not classified as explosive.

Oxidising properties The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight No information available.

Volatile organic compound 4.00 g/litre

Other information Volume solids: 38% +/- 1.0%.

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity Reaction with: strong oxidising substances and acids.

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

10.3 Possibility of hazardous reactions

Hazardous reactions None under normal processing.

Hazardous polymerisationUnknown.Polymerisation descriptionUnknown.

10.4 Conditions to Avoid

Conditions to avoid Protect from frost. Avoid exposure to high temperatures or direct sunlight.

10.5 Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Do not mix with other chemicals unless listed on

directions.

10.6 Hazardous decomposition products

 $\textbf{Hazardous decomposition products} \quad \text{Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or a supplied of the composition of th$

vapours

Section 11: Toxicological information

11.1 Information on toxicological effects

Toxicological information No toxicological information for the overall finished product.

Acute toxicity (Oral LD50) No information available.
Acute toxicity (Dermal LD50) No information available.
Acute toxicity (Inhalation LD50) No information available.

Serious eye damage/irritation May cause temporary eye irritation.

Skin corrosion/irritation No information available.

Respiratory sensitisationNo information available. **Skin sensitisation**No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Specific target organ toxicity - Single exposure:

STOT - Single exposure No information available.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposureNo information available.

Inhalation Inhalation of mist or vapor may cause respiratory tract irritation.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Prolonged contact may cause redness and/or tearing.

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product. The generation of waste should be avoided or minimised wherever possible. Avoid pouring into drains or waterways. Avoid contaminating the ground or water with waste. Where practical, waste or surplus material should be recovered and recycled.

Routes of entry No information available. **Target organs** No target organs specified.

Aspiration hazards: No information available. **Reproductive toxicity:** No information available.

Name	LD50 oral	LD50 dermal	LD50 inhalation
MICA	500.00mg/kg Rat		
titanium dioxide	10000.00mg/kg Rat		
Kaolin, calcined	>2000.00mg/kg Rat		
oxydipropyl dibenzoate	9800.00mg/kg Rat	>2000.00mg/kg Rat	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	6500.00mg/kg Rat	15200.00mg/kg Rabbit	

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish

Acute toxicity - Aquatic invertebrates

Acute toxicity - Aquatic plants

Acute toxicity - Aquatic plants

Acute toxicity - Microorganisms

Chronic toxicity - Fish

Chronic toxicity - Aquatic

No information available.

No information available.

No information available.

inverte brates

Chronic toxicity - Aquatic plants Chronic toxicity - MicroorganismsNo information available.
No information available.

Ecotoxicity

The product contains a substance which is harmful to a quatic life with long lasting effects.

Eco toxilogical information No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

Degradability The degradability of the product has not been stated.

Biological oxygen demandNo information available.
Chemical oxygen demand
No information available.

12.3 Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Bioacculmation factor No information available.
Partition coefficient; n- No information available.

Octanol/Water

12.4 Mobility in soil

Mobility No information available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Other adverse effects

Other adverse effects None known.

Name Acute toxicity (Fish) Acute toxicity (Aquatic invertebrates) (Aquatic	,
--	---

titanium dioxide		EC50 48 Hours >1000.00mg/l Daphnia magna	
oxydipropyl dibenzoate	LC50 96 Hours 3.70mg/l Freshwater Fish	EC50 48 Hours 19.30mg/l Daphnia magna	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	LC50 96 Hours >19.00mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 147.80mg/l Daphnia magna	
diuron (ISO) 3-(3,4-dichlorophenyl),1-dimethylurea	LC50 96 Hours 14.70mg/l Onchorhynchus mykiss (Rainbow Trout)	IEC50 48 Hours 1 40mg/l	EC50 72 Hours 0.02mg/l Scenedesmus Subspicatus
zinc oxide	LC50 96 Hours 0.14mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 0.17mg/l Daphnia magna	72 Hours 0.14mg/l Selenastrum Capricornutum

Section 13: Disposal considerations

Waste management

When handling waste, consideration should be made to the safety precautions applying to handling of the product. The generation of waste should be avoided or minimised wherever possible. Avoid pouring into drains or waterways. Avoid contaminating the ground or water with waste. Where practical, waste or surplus material should be recovered and recycled.

13.1 Waste treatment methods

Disposal methods

Dispose of waste and residues in accordance with local authority requirements. Empty containers or liners may retain some product residues. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14: Transport information

14.1 UN number

UN no. (ADR)
UN no. (IMDG)
Not applicable.
UN no. (IATA)
Not applicable.

14.2 UN proper shipping name

ADR proper shipping name
IMDG proper shipping name
Not applicable.
IATA proper shipping name
Not applicable.

14.3 Transport hazard class(es)

ADR class Not applicable.

IMDG class Not applicable.

IATA class Not applicable.

Transport labels Not applicable

14.4 Packing group

ADR/RID/ADN packing group Not applicable.
IMDG packing group Not applicable.
IATA packing group Not applicable.

14.5 Environmental hazards

ADR No IMDG No IATA No

14.6 Special precautions for user

EMS Not applicable.
Emergency action code Not applicable.
Hazard no. (ADR) Not applicable.
Tunnel restriction code Not applicable.

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th

May 2010 amending regulation (EC) No 1907/2006.

Approved code of practice 2016 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of

the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005).

Chemical safety assessment No chemical safety assessment has been carried out.

Section 16: Other information

General information This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.

Revision commentsThis is a first issue. **Revision date**18 May 2017

Revision 1

Safety data sheet status Approved.

Hazard statements in full

H412 Harmful to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.
H301 Toxic if swallowed.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.