

# Teak Oil


## PRODUCT DESCRIPTION & USE

Fleetwood Teak Oil is a solvent-borne protective finish formulated to replace essential oils necessary to prevent wood from drying, warping and splitting.

## KEY BENEFITS

- A hard wearing solvent-based semi-gloss finish
- Clear liquid

## AVAILABLE IN SIZES



## VOC CONTENT

Contains max VOC; 465g/l  
Conforms to EU 2010 Directive (Cat A/f) 700g/l

## SPECIFIC GRAVITY

Specific Gravity 0.83 g/l (+/- 0.1)

## SURFACE PREPARATION

Ensure that the wood to be treated is thoroughly clean, dry, and free from resinous matter or loose particles. Clean oily timber with White Spirit. Rub down the surface with abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

## APPLICATION



Apply Fleetwood Teak Oil liberally by using a cloth or brush. Remove excess Linseed Oil after 10-15 minutes with a clean cloth. Up to 3 coats may be required for bare timber, rubbing previous coat with fine sandpaper for a key; use 1 coat for maintenance of existing coating. On exterior wood the first coat should be allowed to dry without wiping..

## SPREADING RATE



As a guide a coverage rate of up to 15 - 20m<sup>2</sup> per litre can be achieved depending on the porosity of the timber.

## TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

## DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



**Touch Dry:** 5-6 hours  
**Recoat:** 16 -24 hours

This is dependent upon temperature and humidity. Darker colors may take longer. 26°C to 50% RH @ 4 Thou wet.

## CLEANING UP



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Dispose of cans and waste paint in accordance with local authority guidelines

## PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. Flammable- keep away from sources of ignition. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

## FOLLOW US ON

Online: [www.fleetwood.ie](http://www.fleetwood.ie)  
Email: [info@fleetwood.ie](mailto:info@fleetwood.ie)  
Phone: 049 8547209

