



TECHNICAL DATA SHEET

TDS: FSW B63 - A

FSW CHLORINATED RUBBER THINNERS

DESCRIPTION:

FSW Chlorinated Rubber Thinners is a C8 – C10 aromatic hydrocarbon solvent mixture

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

RECOMMENDED USE:

FSW Chlorinated Rubber Thinners is used as a slow evaporating thinner/brushwash for FSW Chlorinated base paints

FLASH POINT:

41 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

AVAILABILITY:

1 & 2.5 Litre

N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

FINISH:

N/A

MINIMUM OVERCOATING TIME:

N/A

COLOUR:

Clear thin liquid

APPLICATION SPECIAL CONDITIONS:

N/A

TYPICAL S.G. (SPECIFIC GRAVITY):

0.86 @ 20 °C

VOC CONTENT:

860 g / litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

VOLUME SOLIDS:

N/A

APPLICATION DETAILS:

Application N/A
restrictions

WET FILM THICKNESS W.F.T

N/A

Method: N/A

DRY FILM THICKNESS D.F.T

N/A

Thinner N/A
(Max vol):

EXPECTED SPREADING RATE:

N/A

Nozzle size: N/A

For further advice contact Fleetwood Technical Services on +353 49 8547209
The physical constants are subject to normal manufacturing tolerances.

CHLORINATED RUBBER THINNERS

Nozzle pressure: N/A

ISSUED:

01 September 2014

Cleaning solvent: N/A

Recoat interval: N/A

REVISION

0

HEALTH AND SAFETY:

Safety data sheets to accompany this product and associated base paints

FL-V607 - CHLORINATED RUBBER THINNERS - SDS11711

B63C1144 - CHLORINATED RUBBER CLEAR BASE - SDS11703

B63W1344 - CHLORINATED RUBBER MID-TONE BASE - SDS11704

B63W1144 - CHLORINATED RUBBER WHITE BASE - SDS11705

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on +353 49 8547209.

For further advice contact Fleetwood Technical Services on +353 49 8547209
The physical constants are subject to normal manufacturing tolerances.