

# SAFETY DATA SHEET B63W1144 - CHLORINATED RUBBER WHITE BASE

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name B63W1144 - CHLORINATED RUBBER WHITE BASE

Product number B63W1144

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PAINT BASE FOR TINTING SYSTEM

#### 1.3. Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd

Virginia Co Cavan Ireland

+353 49854 7209 +353 49854 7470

Contact person Technical Department -, 9.00 to 17.00 hrs Mon - Fri., as above

# 1.4. Emergency telephone number

Emergency telephone + 353 49854 7209 FSW Coatings Ltd (09.00 - 17.00 hrs Monday - Friday)

**SDS No.** 20836 (replaces 11705)

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

# Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H335, H336

Environmental hazards Aquatic Chronic 2 - H411

# 2.2. Label elements

## **Pictogram**







Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## B63W1144 - CHLORINATED RUBBER WHITE BASE

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing vapour/ spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains HYDROCARBONS, C9, AROMATICS, HYDROCARBONS, C9-C11, <2% AROMATICS

Supplementary precautionary statements

P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to

extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

# 3.2. Mixtures

## HYDROCARBONS, C9, AROMATICS 30-60%

CAS number: — EC number: 918-668-5 REACH registration number: 01-

2119455851-35-xxxx

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Flam. Liq. 3 - H226
 Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.

Flam. Liq. 3 - H226 STOT SE 3 - H335, H336

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

Chlorinated polymer 20 10-30%

CAS number: 9006-03-5

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

Titanium Dioxide 10-30%

CAS number: 13463-67-7 EC number: 236-675-5 REACH registration number: 01-

2119489379-17-xxxx

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

## B63W1144 - CHLORINATED RUBBER WHITE BASE

# HYDROCARBONS, C9-C11, <2% AROMATICS

5-10%

CAS number: — EC number: 919-857-5 REACH registration number: 01-

2119463258-33-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226 Xn;R65. R10,R66,R67.

STOT SE 3 - H336 Asp. Tox. 1 - H304

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

**General information** Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. If breathing stops, provide artificial respiration. Place unconscious person on their

side in the recovery position and ensure breathing can take place.

**Ingestion** Get medical attention immediately. Do not induce vomiting.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use

solvents or thinners

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 10 minutes. Consult a physician for specific advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

Get medical attention promptly if symptoms occur after washing.

# 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

# SECTION 5: Firefighting measures

# 5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use

water jet as an extinguisher, as this will spread the fire.

# 5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m3. Oxides of carbon. Oxides of nitrogen. Fire creates: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon

monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx).

#### 5.3. Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory

protection is worn during removal of spillages in confined areas.

# 6.2. Environmental precautions

# B63W1144 - CHLORINATED RUBBER WHITE BASE

#### **Environmental precautions**

Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

## 6.3. Methods and material for containment and cleaning up

#### Methods for cleaning up

Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

#### 6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

#### Usage precautions

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Vapours may accumulate on the floor and in low-lying areas. Use explosion proof electric equipment. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep container tightly closed. Keep containers upright. Protect from light. Store in closed original container at temperatures between 5°C and 25°C. Store away from the following materials: Oxidising materials. Acids. Alkalis.

#### Storage class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate , marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

# 7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

# 8.1. Control parameters

Occupational exposure limits

#### HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m³ vapour

## Chlorinated polymer 20

Long-term exposure limit (8-hour TWA): WEL 10 mg/m3 total dust

#### **Titanium Dioxide**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit

# HYDROCARBONS, C9, AROMATICS

**DNEL** Consumer - Oral; Long term systemic effects: 11 mg/kg/day

Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Inhalation; Long term systemic effects: 32 mg/m³ Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m³

PNEC No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this

endpoint are intended for single substances and are not appropriate for the risk

assessment of this complex substance.

Titanium Dioxide (CAS: 13463-67-7)

**DNEL** Industry - Inhalation; Long term local effects: 10 mg/m³

Consumer - Oral; Long term systemic effects: 700 mg/kg/day

PNEC - Fresh water; 0.184 mg/l

- marine water; 0.0184 mg/l

Sediment (Freshwater); >=1000 mg/kgSediment (Marinewater); >=100 mg/kg

Soil; 100 mg/kgSTP; 100 mg/kg

## Chlorinated Paraffin 48 (CAS: 63449-39-8)

**DNEL** Industry - Inhalation; Long term systemic effects: 2.35 mg/m³

Industry - Dermal; Long term systemic effects: 20 mg/kg/day Consumer - Oral; Long term systemic effects: 0.167 mg/kg/day Consumer - Dermal; Long term systemic effects: 8.3 mg/kg/day

PNEC - Fresh water; 0.003 mg/l

- marine water; 0.001 mg/l

- STP; 60 mg/l

- Sediment (Freshwater); 5710 mg/kg

- Soil; 4640 mg/kg

# HYDROCARBONS, C9-C11, <2% AROMATICS

**DNEL** Consumer - Oral; Long term systemic effects: 300 mg/kg/day

Industry - Inhalation; Long term systemic effects: 1500 mg/m³ Industry - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Inhalation; Long term systemic effects: 900 mg/m³

imalation, Long term systemic enests. See high

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk

assessment of this complex substance.

# 8.2. Exposure controls

**PNEC** 

# Protective equipment







## B63W1144 - CHLORINATED RUBBER WHITE BASE

Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure

limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Polyvinyl alcohol (PVA). Thickness: 0.2 - 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Appearance Viscous liquid. Coloured liquid.

Colour Various colours

Odour Organic solvents.

Odour threshold Not determined.

**pH** Technically not feasible.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point 40 approx.°C Closed cup.

Evaporation rate Not determined.

Evaporation factor Not determined.

Upper/lower flammability or

explosive limits

: 0.8

Other flammability Not determined.

Vapour pressure Not determined.

Vapour density heavier than air

**Relative density** 1.00 - 1.10 @ @ 20 C°C

Solubility(ies) Insoluble in water

## B63W1144 - CHLORINATED RUBBER WHITE BASE

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity 3.0 (ICI Rotothinner) P @ 25 C°C

**Explosive properties** Not determined.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not determined.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 560 - 620 depending on colour g/litre.

#### SECTION 10: Stability and reactivity

# 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

# 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not determined.

# 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Acids. Oxidising agents.

# 10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

# 10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

**products** other toxic gases or vapours.

## SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems.

**Inhalation** May cause respiratory system irritation. Vapours in high concentrations are narcotic.

Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. The product contains organic solvents. Overexposure may depress the

central nervous system, causing dizziness and intoxication.

Ingestion Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause

irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea. May cause nausea, headache, dizziness and intoxication.

# B63W1144 - CHLORINATED RUBBER WHITE BASE

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. Repeated exposure

may cause skin dryness or cracking. May cause allergic contact eczema.

**Eye contact** Irritation of eyes and mucous membranes.

Route of exposure Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Toxicological information on ingredients.

# HYDROCARBONS, C9, AROMATICS

Acute toxicity - oral

Acute toxicity oral (LD₅o

3,492.0

mg/kg)

**Species** Rat

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

**ATE oral (mg/kg)** 3,492.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 3,160.0

mg/kg)

Species Rabbit

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation

6,193.0

(LC<sub>50</sub> vapours mg/l)

**Species** Rat

Notes (inhalation LC50) Based on available data the classification criteria are not met.

ATE inhalation (vapours

6,193.0

mg/l)

Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye Based on available data the classification criteria are not met.

damage/irritation

Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

## B63W1144 - CHLORINATED RUBBER WHITE BASE

**IARC carcinogenicity** None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity -

fertility

Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness

or dizziness.

Target organs Respiratory system, lungs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may

be the result if vomited material containing solvents reaches the lungs.

General information The severity of the symptoms described will vary dependent on the concentration

and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Irritation of nose, throat

and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high

concentrations are narcotic.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach

contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis.

**Skin contact** Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.

**Eye contact** May cause temporary eye irritation.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs Central nervous system Respiratory system, lungs

**Chlorinated Paraffin 70** 

Acute toxicity - dermal

Acute toxicity dermal (LD₅ 10.0

mg/kg)

Species Rabbit

Chlorinated Paraffin 48

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

11,700.0

# B63W1144 - CHLORINATED RUBBER WHITE BASE

**Species** Rat

11,700.0 ATE oral (mg/kg)

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 13,900.0

mg/kg)

**Species** Rabbit

ATE dermal (mg/kg) 13,900.0

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute toxicity - oral

Acute toxicity oral (LD₅o

5,100.0

mg/kg)

**Species** Rat

ATE oral (mg/kg) 5,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 5,100.0

mg/kg)

**Species** Rabbit

5,100.0 ATE dermal (mg/kg)

Acute toxicity - inhalation

Acute toxicity inhalation

5,100.0

(LC<sub>50</sub> vapours mg/l)

**Species** Rat

ATE inhalation (vapours

mg/l)

5,100.0

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye

Not irritating.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. This substance has no evidence of mutagenic

properties.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

## B63W1144 - CHLORINATED RUBBER WHITE BASE

Reproductive toxicity

Reproductive toxicity -

Fertility: -, Inhalation, Rat This substance has no evidence of toxicity to

**fertility** reproduction.

Reproductive toxicity -

Developmental toxicity: -:, Inhalation, Rat This substance has no evidence of

**development** toxicity to reproduction.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

**Aspiration hazard** Kinematic viscosity <= 20.5 mm2/s.

.

**Inhalation** Vapours may cause drowsiness and dizziness. Central nervous system depression.

Ingestion Harmful: danger of serious damage to health by prolonged exposure if swallowed.

**Skin contact** Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact No specific health hazards known.

Route of exposure Inhalation Dermal

# SECTION 12: Ecological information

**Ecotoxicity** There are no data on the ecotoxicity of this product. The product contains substances which

are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic

environment

# 12.1. Toxicity

# Ecological information on ingredients.

# HYDROCARBONS, C9, AROMATICS

**Toxicity** Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC50, 48 hours: 3.2 mg/l, Daphnia magna

Acute toxicity - microorganisms

EC<sub>50</sub>, 48 hours: 2.9 mg/l,

# HYDROCARBONS, C9-C11, <2% AROMATICS

Acute aquatic toxicity

Acute toxicity - fish LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)

Substance did not cause acute toxicity to fish

Acute toxicity - aquatic

invertebrates

Substance did not cause acute toxicity to the freshwater invertebrates

EC<sub>50</sub>, 48 hours: >1000 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, > 72 hours: 1000 mg/l, Freshwater algae

Substance did not cause acute toxicity to the freshwater green algae

# B63W1144 - CHLORINATED RUBBER WHITE BASE

**Acute toxicity -** EC<sub>50</sub>, >: 100 mg/l, Activated sludge

microorganisms

Chronic aquatic toxicity

Chronic toxicity - fish early NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

Chronic toxicity - aquatic

invertebrates

NOEC, 28 days: 0.23 mg/l, Daphnia magna

# 12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

HYDROCARBONS, C9, AROMATICS

Persistence and

degradability

The degradability of the product is not known.

Biodegradation - 78%: 28 days

HYDROCARBONS, C9-C11, <2% AROMATICS

Persistence and

degradability

The product is readily biodegradable.

**Phototransformation** Oxidises rapidly by photo-chemical reactions in air

**Biodegradation** - 80 Degradation (%): 28 days

Test - 301F Ready Biodegradability - Manometric Respiratory Test

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

HYDROCARBONS, C9, AROMATICS

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Chlorinated Paraffin 70

Bioaccumulative potential BCF: > 20 < 1,

Partition coefficient log Pow: 17

HYDROCARBONS, C9-C11, <2% AROMATICS

**Bioaccumulative potential** The product contains potentially bioaccumulating substances.

Partition coefficient log Pow: 5 - 6.7

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

# B63W1144 - CHLORINATED RUBBER WHITE BASE

# Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

Mobility No data available.

HYDROCARBONS, C9-C11, <2% AROMATICS

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces. Readily absorbed into soil.

Adsorption/desorption

coefficient

Not available.

Surface tension 24.5 mN/m @ 20°C

# 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

# Ecological information on ingredients.

# HYDROCARBONS, C9, AROMATICS

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

#### **Chlorinated Paraffin 70**

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

# HYDROCARBONS, C9-C11, <2% AROMATICS

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

## 12.6. Other adverse effects

Other adverse effects

The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

## Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

Other adverse effects None known.

# HYDROCARBONS, C9-C11, <2% AROMATICS

Other adverse effects Not known.

# SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Avoid the spillage or runoff entering drains, sewers or watercourses.

#### Waste class

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

# SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR

and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263 UN No. (IMDG) 1263 UN No. (ICAO) 1263

# 14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

PAINT: Contains Hydrocarbons, C9, Aromatics, Class 3, PGIII, (38 C), MARINE

POLLUTANT)

Proper shipping name (IMDG) PAINT: Contains Hydrocarbons, C9, Aromatics, Class 3, PGIII, (38 C), MARINE

POLLUTANT)

Proper shipping name (ICAO) PAINT: Contains Hydrocarbons, C9, Aromatics, Class 3, PGIII, (38 C), MARINE

POLLUTANT)

# 14.3. Transport hazard class(es)

ADR/RID class 3
IMDG class 3
ICAO class/division 3

Transport labels



# 14.4. Packing group

ADR/RID packing group III
IMDG packing group III
ICAO packing group III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



# 14.6. Special precautions for user

**EmS** F-E, S-E

Tunnel restriction code (D/E)

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.

CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.

GHS: Globally Harmonized System.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

PNEC: Predicted No Effect Concentration.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity

Aquatic Acute = Hazardous to the aquatic environment (acute)
Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Repr. = Reproductive toxicity

Resp. Sens. = Respiratory sensitisation

Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

Revision comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No.

2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.

**Issued by** Technical Dept. (P.E.)

Revision date 03/04/2019

Revision 2.0

Supersedes date 11/05/2015

SDS number 20836

SDS status Approved.

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Signature Initials .....

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.