

Product FLEETWOOD ULTRA TOUGH OXIDE - GREY
 Revision date 15 January 2021
 Revision 2



Safety Data Sheet (SDS)
 according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name FLEETWOOD ULTRA TOUGH OXIDE - GREY
Other means of identification 3K6X-1E6Q-N20F-XD3M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint or paint related material.
Uses advised against No uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd
 Virginia
 Co Cavan
 Ireland
 Tel: 353 49854 7209
Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone + 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)
National emergency telephone number Outside those hours, contact National Poisons Information Centre, Beaumont Hospital.
 Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare
 Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)
 Physical and chemical hazards Flam. Liq 3- H226
 Human health STOT SE 3 - H336
 Environment Not classified

2.2 Label elements

Contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 nonane
 octane

Label in accordance with (EC) no. 1272/2008



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.

Precautionary statements **Prevention**
 P233 Keep container tightly closed.
 P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
Response

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

EUH statements

EUH208 Contains butanone oxime. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-XXXX	Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	40-50%
Limestone	CAS-No.: 1317-65-3 EC No.: 215-279-6		10-20%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0002		1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
butanone oxime	CAS-No.: 96-29-7 EC No.: 202-496-6	Acute Tox 4 - H312, Skin. Sens 1 - H317, Eye Dam. 1 - H318, Carc. 2 - H351	0.1-0.9%
cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6	Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412, Eye Irrit.2A - H319, Repr. 2 - H361, Skin. Sens 1 A- H317, Repr. 1B- H360	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Butanone oxime: Acute Toxicity Estimates (ATE)- dermal: ATE = 1100 mg/kg (-) oral: ATE = 100 mg/kg (-).

Propionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % <= C < 25 %, STOT SE 3; H335: C >= 10 %, Skin Corr. 1B; H314: C >= 25 %, Skin Irrit. 2; H315: 10 % <= C < 25 %.

Section 4: First aid measures

4.1 Description of first aid measures

General information

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.

Inhalation

If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing is difficult, give oxygen. If breathing has stopped or the exposed person experiences difficulty in breathing, administer artificial respiration and seek immediate medical assistance.

Ingestion

Rinse mouth thoroughly. Provide fresh air, warmth and rest. Do not induce vomiting. Never

Skin contact	give anything by mouth if victim is unconscious, is rapidly losing consciousness or is convulsing. Seek medical advice (show the label where possible). If vomiting occurs, the head should be kept low so that stomach content doesn't enter the lungs. Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues after rinsing.
Eye contact	Do not rub eye. Avoid contaminating unaffected eye. Remove contact lenses if present and easy to do so. Promptly wash eye(s) with plenty of water while lifting the eye lids. Rinse with a gentle stream water for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. Inhalation of vapours may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	When heated, toxic and corrosive vapours/gases may be formed
Unusual fire & explosion hazards	No unusual fire or explosion hazards noted.
Specific hazards	If heated, harmful vapours may be formed.

5.3 Advice for firefighters

Special fire fighting procedures	Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires from safe distance or protected location. Do not scatter spilled material with more water than needed to fight the fire Do not get water inside container
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke, use open fire or other sources of ignition. Make safe all sources of ignition. Avoid contact with skin and eyes. Ensure adequate ventilation. Use non-sparking hand tools and explosion proof electrical equipment. Avoid inhalation of dust and vapours
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions

Environmental precautions	Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.
----------------------------------	--

6.3 Methods and material for containment and cleaning up**Spill clean up methods**

Stop leak if possible without risk. Wear necessary protective equipment. Absorb spillage with non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage.

6.4 Reference to other sections**Reference to other sections**

See section 1 for emergency contact. For personal protection, see section 8 For waste disposal, see section 13.

Section 7: Handling and storage**7.1 Precautions for safe handling****Handling**

Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment. Avoid spilling, skin and eye contact. Do not use contact lenses. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Ensure adequate ventilation. Vapours are heavier than air and may spread along floors. Do not eat, drink or smoke when using the product.

7.2 Conditions for safe storage, including any incompatibilities**Storage precautions**

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep upright. Keep locked up and out of reach of children. Avoid storing for very long periods. Keep container tightly sealed when not in use.

Storage class

Flammable liquid storage.

7.3 Specific end use(s)**Specific end use(s)**

The identified uses for this product are detailed in Section 1.

Usage description

Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection**8.1 Control parameters**

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
Limestone	OEL		4 mg/m ³			respirable dust
Limestone	OEL		10 mg/m ³			total inhalable dust
titanium dioxide	OEL		10 mg/m ³			
titanium dioxide	OEL		4 mg/m ³			
butanone oxime	OEL	3 ppm	10 mg/m ³	10 ppm	33 mg/m ³	Sens.
nonane	OEL	200 ppm	1050 mg/m ³			
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	IOELV
octane	OEL	300 ppm	1450 mg/m ³			

Ingredient comments

Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls**Protective equipment****Engineering measures**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

Use type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Use

Hand protection	respirators and components tested and approved under appropriate government standards such as CEN (EU). Use suitable protective gloves if there is a risk of skin contact. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Change gloves regularly. Suggested material: Nitrile rubber gloves. Minimum breakthrough time / gloves: 480 min. Minimum layer thickness: 0.7mm.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.
Hygiene measures	DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Process conditions	Keep container tightly sealed when not in use. Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Grey.
Odour	Hydrocarbon, (slight).
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	No information available as testing has not been completed.
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	May start to solidify at the following temperature: -15°C This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Weighted average: -58.56°C
Initial boiling point and boiling range	>142°C
Flash point	Closed cup 42°C
Evaporation rate	Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics) Weighted average: 0.03 compared with butyl acetate
Flammability state	Liquid
Flammability limit - lower(%)	Greatest known range: Lower: 0.6% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Flammability limit - upper(%)	Greatest known range: Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Vapour pressure	Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha(petroleum), hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20°C)
Vapour density (air=1)	Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Relative density	1.08
Bulk density	No information available as testing has not been completed.
Solubility	Insoluble in cold water
Decomposition temperature	Stable under normal handling and storage conditions.

Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Viscosity	Kinematic (40°C): >0.22 cm ² /s
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	No information available as testing has not been completed.
Volatile organic compound	389.00 g/litre
Other information	Weight Solids: 48.0 +/- 1.0% Volume solids: 56.0% +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	No specific reactivity hazards associated with this product.
-------------------	--

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
------------------	---

10.3 Possibility of hazardous reactions

Hazardous reactions	For information on hazardous reaction see section 10.1.
Hazardous polymerisation	Unknown.
Polymerisation description	Unknown.

10.4 Conditions to Avoid

Conditions to avoid	Avoid exposure to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5 Incompatible materials

Materials to avoid	Do not mix with other chemicals unless listed on directions.
---------------------------	--

10.6 Hazardous decomposition products

Hazardous decomposition products	None under normal conditions.
---	-------------------------------

Section 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Toxicological information	No toxicological information for the overall finished product.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.
Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	Product is not classified as an eye irritant.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is not classified as a skin sensitisation hazard.

Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is not classified as a repeat exposure specific target organ toxin.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. Inhalation of vapours may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
Routes of entry	Eyes, skin, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system.
Aspiration hazards:	The product is not classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
nonane			3200.00ppmV Rat 4 Hours 17000.00mg/m ³ Rat 4 Hours
Limestone	>5000.00mg/kg Rat		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat	>5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
octane			25260.00ppmV Rat 4 Hours 118.00g/m ³ Rat 4 Hours
titanium dioxide	10000.00mg/kg Rat		

11.2 Information on other hazards

Information on other hazards	None known.
-------------------------------------	-------------

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.

12.4 Mobility in soil

Mobility	Insoluble in cold water.
-----------------	--------------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties The product does not contain any substances with endocrine disrupting properties at a concentration above or equal to 0.1%.

12.7 Other adverse effects

Other adverse effects None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
Limestone	LC50 96 Hours >10000.00mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours >1000.00mg/l Daphnia magna	EC50 72 Hours >200.00mg/l Scenedesmus Subspicatus
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 96 Hours >100.00ppm Freshwater Fish	LC50 48 Hours >100.00ppm Daphnia magna	
propionic acid	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 22.70ppm Daphnia magna	EC50 96 Hours 43.00mg/l
butanone oxime	LC50 48 Hours 560.00mg/l LC50 96 Hours 46.00mg/l Lepomis macrochirus (Bluegill)	LC50 48 Hours 750.00mg/l Daphnia magna	LC50 72 Hours 83.00mg/l

Section 13: Disposal considerations

Waste management When handling waste, consideration should be made to the safety precautions applying to handling of the product.

13.1 Waste treatment methods

Disposal methods Dispose of waste and residues in accordance with local authority requirements, and in accordance with all local, national and international regulations.

Section 14: Transport information**14.1 UN number or ID number**

UN no. (ADR)	UN1263
UN no. (IMDG)	UN1263
UN no. (IATA)	UN1263

14.2 UN proper shipping name

ADR proper shipping name	PAINT or PAINT RELATED MATERIAL
IMDG proper shipping name	PAINT or PAINT RELATED MATERIAL
IATA proper shipping name	PAINT

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels

**14.4 Packing group**

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-E
Emergency action code	A3 A72 A192
Hazard no. (ADR)	30
Tunnel restriction code	(D/E)

14.7 Maritime transport in bulk according to IMO instruments**Section 15: Regulatory information****15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Reach Regulation (EC) No 453/2010. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment	No chemical safety assessment has been carried out.
-----------------------------------	---

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	[1]Information updated. [2]Information updated. [3]Information updated. This is a first issue. [4]Information updated. [5]Information updated. [6]Information updated. [7]Information updated. [8]Information updated. [9]Information updated. [10]Information updated. [11]Information updated. [12]Information updated. [15]Information updated.
Revision date	15 January 2021
Revision	2
Safety data sheet status	Approved.

Hazard statements in full

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child .
H312	Harmful in contact with skin.

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer .
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child .
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H315	Causes skin irritation.
H411	Toxic to aquatic life with long lasting effects.
H410	Very toxic to aquatic life with long lasting effects.
H314	Causes severe skin burns and eye damage.
H225	Highly flammable liquid and vapour.
EUH208	Contains butanone oxime. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.