**Product** 10 Year Exterior Woodstain **Revision date** 07 November 2019

1

- Revision

# FLEETWOOD - for COLOURFUL LIVES -

# Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

# Section 1: Identification of the substance/preparation and of the company/undertaking

#### **1.1 Product identifier**

**Product name** Synonyms, Trade names

**10 Year Exterior Woodstain** No information available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint or paint related material.
Uses advised against	No uses advised against are identified.

#### **1.3 Details of the supplier of the safety data sheet**

Supplier	FSW Coatings Ltd
	Virginia
	Co Cavan
	Ireland
	Tel: 353 49854 7209
Contact person	info@fsw.ie
1.4 Emergency telephone number	
Emergency telephone	+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

#### Section 2: Hazards identification

#### 2.1 Classification of the substance or mixture

<b>Classification (EC 1272/2008)</b> Physical and chemical hazards Human health Environment	Not classified Not classified Aquatic Chronic 3 - H412
2.2 Label elements	
Contains	Not applicable
Label in accordance with (EC) no. 1272/2008	No pictogram required
Signal word	No Signal Word
Hazard statements	H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	<b>Prevention</b> P273 Avoid release to the environment. <b>Disposal</b> P501 Dispose of contents/ container to local authorities in accordance with local regulations.

#### 2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients

# 3.1 Substance

Not applicable.

#### 3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
2-(2-butoxyethoxy)ethanol	CAS-No.: 112-34-5 EC No.: 203-961-6 REACH Reg No.: 01-2119475104-44-XXXX		· <1%
2-butoxyethanol	CAS-No.: 111-76-2 EC No.: 203-905-0 REACH Reg No.: 01-2119475108-36-XXXX	Acute Tox 4 - H302, Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319	<1%
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	CAS-No.: 25265-77-4 EC No.: 246-771-9 REACH Reg No.: 01-2119441305-48-0002		<1%
Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo- 3.3.1]nonane-1,5-dicarboxylate-kN3,kN7]-, chloride	CAS-No.: 478945-46-9 EC No.:	Acute Tox 3 - H301, Skin. Sens 1 - H317, STOT RE 2 - H373, Aquatic Chronic 3 - H412	<1%
tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione	CAS-No.: 5395-50-6 EC No.: 226-408-0	Skin. Sens 1 - H317	<1%
2-aminoethanol ethanolamine > 5%	CAS-No.: 141-43-5 EC No.: 205-483-3	Acute Tox 4 - H302, Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Corr. 1B - H314, STOT SE 3 - H335	<1%
diuron (ISO) 3-(3,4-dichlorophenyl)-1,1-dimethylurea	CAS-No.: 330-54-1 EC No.: 206-354-4	Acute Tox 4 - H302, Carc. 2 - H351, STOT RE 2 - H373, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	<0.1%
2,2',2''-nitrilotriethanol	CAS-No.: 102-71-6 EC No.: 203-049-8		<1%
zinc oxide	CAS-No.: 1314-13-2 EC No.: 215-222-5 REACH Reg No.: 01-2119463881-32-0000	Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	<1%
formaldehyde %	CAS-No.: 50-00-0 EC No.: 200-001-8	Acute Tox 3 - H301, Acute Tox 2 - H310, Skin Corr. 1B - H314, Skin. Sens 1 - H317, Acute Tox 3 - H331, Muta. 2- H341, Carc. 1B - H350	<0.1%

The full text for all hazard statements are displayed in section 16.

**Composition comments** 

The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures

## **<u>4.1 Description of first aid measures</u>**

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort or breathing difficulties develop.
Ingestion	If this product is ingested, remove victim immediately from source of exposure. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position. Never give anything by mouth to an unconscious person. Rinse mouth out and then drink plenty of water. Seek medical attention.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing and shoes and wash before reuse. Wash exposed area with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation develops or persists.
Eye contact	Avoid contaminating unaffected eye. Remove contact lenses if present and easy to do so. Hold eye lids open. Rinse with a gentle stream water for at least 15 minutes. Seek medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Inhalation of mist or vapor may cause respiratory tract irritation.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Prolonged contact may cause redness and/or tearing.

#### **<u>4.3 Indication of any immediate medical attention and special treatment needed</u>**

Notes to the physician	Treat symptomatically.
------------------------	------------------------

Section 5: Fire-fighting measures		
5.1 Extinguishing media		
Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry powder or carbon dioxide.	
Unsuitable extinguishing media	None noted.	
5.2 Special hazards arising from the sub	ostance or mixture	
Hazardous combustion products Unusual fire & explosion hazards Specific hazards	When heated, vapours/gases hazardous to health may be formed. No unusual fire or explosion hazards noted. In case of fire, toxic gases may be formed (COx, NOx). Avoid breathing fumes. Do not allow run-off from fire fighting to enter drains or water courses.	
5.3 Advice for firefighters		
Special fire fighting procedures	Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires from safe distance or protected location. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.	
Protective equipment for firefighters	<b>s</b> Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

#### Section 6: Accidental release measures

## **<u>6.1 Personal precautions, protective equipment and emergency procedures</u>**

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Eliminate all sources of ignition. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Wash hands after
For emergency responders	use. Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions		
Environmental precautions	Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.	
6.3 Methods and material for contain	ment and cleaning up	
Spill clean up methods	Ventilate and evacuate the area. Stop leak if possible without risk. Wear necessary protective equipment. Absorb spillage with non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.	
6.4 Reference to other sections		
Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.	
Section 7: Handling and storage		
7.1 Precautions for safe handling		
Handling	Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment. Do not use contact lenses. Keep away from heat, sparks and open flame. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Do not eat, drink or smoke when using the product.	
7.2 Conditions for safe storage, inclue	ding any incompatibilities	
Storage precautions	Store in tightly closed original container in a cool, dry and well-ventilated place. Keep	

Storage precautions	Store in tightly closed original container in a cool, dry and well-ventilated place. Keep upright, locked up and out of reach of children. Store in cool dry areas away from direct
	sunlight or sources of ignition.
Storage class	Unspecified storage.
7.3 Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.
Usage description	Use only according to directions. Replace and tighten cap after use.
Usage description	Use only according to unections. Replace and lighten cap after use.

Section 8:	Exposure	controls/Personal	protection
			P

# 8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes	
2-(2-butoxyethoxy)ethanol	OEL	10 ppm	67.5 mg/m <sup>3</sup>	15 ppm	101.2 mg/m <sup>3</sup>	IOELV	
2-(2-butoxyethoxy)ethanol	WEL	10 ppm	67.5 mg/m <sup>3</sup>	15 ppm	101.2 mg/m <sup>3</sup>		
2-butoxyethanol	OEL	20 ppm	98 mg/m <sup>3</sup>	50 ppm	246 mg/m <sup>3</sup>	Sk , IOELV	
2-butoxyethanol	WEL	25 ppm	123 mg/m <sup>3</sup>	50 ppm	246 mg/m <sup>3</sup>	Sk, BMGV	
2-aminoethanol ethanolamine > 5%	OEL	1 ppm	2.5 mg/m <sup>3</sup>	3 ppm	7.6 mg/m <sup>3</sup>	Sk, IOELV	
2-aminoethanol ethanolamine > 5%	WEL	1 ppm	2.5 mg/m <sup>3</sup>	3 ppm	7.6 mg/m <sup>3</sup>	Sk	
diuron (ISO) 3-(3,4-dichlorophenyl) ,1-dimethylurea	OEL		10 mg/m <sup>3</sup>				
diuron (ISO) 3-(3,4-dichlorophenyl) ,1-dimethylurea	OEL		10 mg/m <sup>3</sup>				
2,2',2''-nitrilotriethanol	OEL		5 mg/m <sup>3</sup>				
zinc oxide	OEL		2(R) mg/m <sup>3</sup>		10 mg/m <sup>3</sup>		
formaldehyde %	OEL	0.2 ppm		0.4 ppm		Carc.1B, Sens.	
formaldehyde %	WEL	2 ppm	2.5 mg/m <sup>3</sup>	2 ppm	2.5 mg/m <sup>3</sup>		

**Ingredient comments** 

Ireland, Occupational Exposure Limits 2018. Workplace Exposure Limits Guidance Note EH40/2005.

## 8.2 Exposure Controls

**Protective equipment** 



Engineering measures	Provide adequate ventilation, including appropriate local extraction, to ensure that the
Respiratory equipment	defined occupational exposure limit is not exceeded. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN 143 should be used, and suitable respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. ABEK (EN 14387). Consult manufacturer for specific advice. Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use respiratory protection as specified by an industrial hygienist or other qualified professional if concentrations exceed the limits listed in Section 8.
Hand protection	Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. Gloves must be inspected prior to use. Suggested material: Nitrile rubber. Break through time: >480 minutes. Minimum layer thickness: 0.33 mm. Chloroprene. Breakthrough time: >480 minutes. Minimum layer thickness: 0.6 mm. Consult manufacturer for specific advice.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Wear appropriate clothing to prevent skin contact. Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Hygiene measures	Immediately take off any contaminated clothing and launder before re-use. Wash promptly if skin becomes contaminated. Wash hands after handling. Do not eat, drink, or smoke while using this product.
Process conditions	Ensure that eye flushing systems and safety showers are located close by in the work place.

## Section 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

mormation on basic physical and c	
Appearance	Liquid.
Colour	Various.
Odour	Faint odour.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	7.5 - 9.0
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	May start to solidify at the temperatures below 2°C.This is based on data for the following ingredient: water.
Initial boiling point and boiling range	38 °C.
Flash point	Not applicable.
Evaporation rate	No information available as testing has not been completed.
Flammability state	Non flammable.
Flammability limit - lower(%)	No information available as testing has not been completed.
Flammability limit - upper(%)	0%
Vapour pressure	Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 3.12 kPa (23.4 mm Hg) (at 20°C).

	Vapour density (air=1)	Highest known value: 7.5 (Air = 1) (isobutyric acid, monoester with 2,2, 4-trimethylpentan- $-1,3$ -diol).
	Relative density	1.02.
	Bulk density	No information available as testing has not been completed.
	Solubility	Partially soluble in water.
	Decomposition temperature	Stable under normal handling and storage conditions.
	Partition coefficient; n- Octanol/Water	No information available as testing has not been completed.
	Auto ignition temperature (°C)	Not applicable.
	Viscosity	Kinematic (40°C): >0.21 cm <sup>2</sup> /s
	Explosive properties	Not classified as explosive.
	Oxidising properties	The product does not meet the criteria to be classified as oxidising.
<u>9.2</u>	Other information	
	Molecular weight	No information available as testing has not been completed.
	Volatile organic compound	22.00 g/litre
	Other information	Volume Solids: 33.0% +/- 1.0%.
		Weight Solids: 34.0% +/- 1.0%

10.1 Reactivity	
Reactivity	Reactions may occur with strong oxidising agents.
0.2 Chemical stability	
Stability	Stable under normal temperature conditions and recommended use.
0.3 Possibility of hazardous reactions	
Hazardous reactions Hazardous polymerisation Polymerisation description	None under normal processing. Unknown. Unknown.
0.4 Conditions to Avoid	
Conditions to avoid	Protect from frost. Avoid exposure to high temperatures or direct sunlight.
0.5 Incompatible materials	
Materials to avoid	Strong oxidising substances. Do not mix with other chemicals unless listed on directions.
0.6 Hazardous decomposition products	
	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

# Section 11: Toxicological information

## **<u>11.1 Information on toxicological effects</u>**

**Toxicological information** 

No toxicological information for the overall finished product.

Acute toxicity (Oral LD50) Acute toxicity (Dermal LD50) Acute toxicity (Inhalation LD50)	No information available as testing has not been completed. No information available as testing has not been completed. No information available as testing has not been completed.
Serious eye damage/irritation	May cause temporary eye irritation.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation Skin sensitisation	The product is not classified as a respiratory hazard. The product is not classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Singl STOT - Single exposure Specific target organ toxicity - Repe STOT - Repeated exposure	The product is not classified as a single exposure specific target organ toxin.
Inhalation Ingestion Skin contact Eye contact Waste management	Inhalation of mist or vapor may cause respiratory tract irritation. May cause discomfort if swallowed. May cause stomach pain or vomiting. Prolonged contact may cause redness, irritation and dry skin. Prolonged contact may cause redness and/or tearing. When handling waste, consideration should be made to the safety precautions applying to handling of the product. The generation of waste should be avoided or minimised wherever possible. Avoid pouring into drains or waterways. Avoid contaminating the ground or water with waste. Where practical, waste or surplus material should be recovered and recycled.
Routes of entry Target organs	Eye and skin contact, ingestion or inhalation. No target organs specified.
Aspiration hazards: Reproductive toxicity:	The product is not classified as an aspiration hazard. The product is not classified as a reproductive hazard.

Name	LD50 oral	I Db0 dormal	LD50 inhalation
formaldehyde %	>200.00mg/kg Rat		
2-(2-butoxyethoxy)ethanol		2764.00mg/kg Rabbit	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol		15200.00mg/kg Rabbit	
Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo- 3.3.1]nonane-1,5-dicarboxylate-kN3,kN7]-, chloride	0.0	>2000.00mg/kg Rat	

# Section 12: Ecological information

#### 12.1 Toxicity

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrate	<b>s</b> No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic	No information available as testing has not been completed.
invertebrates	
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	Harmful to aquatic life with long lasting effects.
Eco toxilogical information	No ecological toxicity available on the overall finished product.
12.2 Persistence and degradability	

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential	
Bioaccumulative potential Bioaccumulation factor Partition coefficient; n- Octanol/Water	No data available on bioaccumulation. No information available as testing has not been completed. No information available as testing has not been completed.
<b>12.4 Mobility in soil</b>	

Mobility

No information available.

#### 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

#### **12.6 Other adverse effects**

Other adverse effects None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
2-(2-butoxyethoxy)ethanol	LC50 96 Hours 1300.00mg/l Lepomis macrochirus (Bluegill)	EC50 48 Hours >100.00mg/l Daphnia magna	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	LC50 96 Hours >19.00mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 147.80mg/l Daphnia magna	
Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo- 3.3.1]nonane-1,5-dicarboxylate-kN3,kN7]-, chloride	LC50 96 Hours >100.00mg/l Brachydanio rerio (Zebra Fish)	EC50 48 Hours 23.70mg/l Daphnia magna	
diuron (ISO) 3-(3,4-dichlorophenyl)-1,1-dimethylurea	LC50 96 Hours 14.70mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 1.40mg/l Daphnia	EC50 72 Hours 0.02mg/l Scenedesmus Subspicatus
zinc oxide	Onchorhynchus mykiss	EC50 48 Hours 0.17mg/l Daphnia magna	

Section 13: Disposal considerations	
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product. The generation of waste should be avoided or minimised wherever possible. Avoid pouring into drains or waterways. Avoid contaminating the ground or water with waste. Where practical, waste or surplus material should be recovered and recycled.
13.1 Waste treatment methods	
Disposal methods	Dispose of waste and residues in accordance with local authority requirements. Empty containers or liners may retain some product residues. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14: Transport information

#### 14.1 UN number

UN no. (ADR) UN no. (IMDG) UN no. (IATA) Not applicable. Not applicable. Not applicable.

14.2 UN proper shipping name		
ADR proper shipping name IMDG proper shipping name IATA proper shipping name	Not applicable. Not applicable. Not applicable.	
14.3 Transport hazard class(es)		
ADR class IMDG class IATA class	Not applicable. Not applicable. Not applicable.	
Transport labels	Not applicable	
14.4 Packing group		
ADR/RID/ADN packing group IMDG packing group IATA packing group	Not applicable. Not applicable. Not applicable.	
14.5 Environmental hazards		
ADR IMDG IATA	No No No	
14.6 Special precautions for user		
EMS Emergency action code Hazard no. (ADR) Tunnel restriction code	Not applicable. Not applicable. Not applicable. Not applicable.	

# 14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

#### Section 15: Regulatory information

# 15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	2018 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005).
	Workplace Exposure Limits Guidance Note EH40/2005.
Chemical safety assessment	No chemical safety assessment has been carried out.

## Section 16: Other information

General information Revision comments Revision date Revision Safety data sheet status	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010. This is a first issue. 07 November 2019 1 Approved.
Hazard statements in full	
H319	Causes serious eye irritation.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H301	Toxic if swallowed.
H317	May cause an allergic skin reaction.

H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.
H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H318	Causes serious eye damage.
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H341	Suspected of causing genetic defects .
H350	May cause cancer .

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.