


PRODUCT DESCRIPTION & USE

Fleetwood 10 Year Exterior Woodstain is a specially formulated water-based wood stain using a specialised alkyd emulsion binder. This product is designed to provide exceptional protection on all exterior hard and softwoods. It provides a hardwearing finish that enhances the natural beauty of wood accentuating the grain and giving it a warm appearance.

KEY BENEFITS

- Protects from rain, frost, snow and sunshine
- Protects from rain, frost, snow and sunshine, will not peel or flake
- Quick drying, low odour and VOC
- Shower proof in one hour

AVAILABLE IN SIZES



COLOUR & GLOSS RANGE

Fleetwood Quick Dry Interior Varnish

Available in Black Ebony, Mahogany, Antique Pine, Teak, Natural Oak & Walnut

VOC CONTENT

Contains max VOC; 22 g/l
Conforms to EU 2010 Directive (Cat A/e) 130g/l

COMPOSITION (NOMINAL)

Pigment: Lightfast Pigments. (where applicable)
Binder: Modified Alkyd Emulsion
Solvent: Water.

SOLIDS - SPECIFIC GRAVITY

Volume Solids 33.0 % (+/- 1%)
Weight Solids 34.0 % (+/- 1%)
Specific Gravity 1.02g/l (+/- 0.2)

SURFACE PREPARATION

This product should only be applied to clean, dry surfaces that are free from oil, grease and other contamination. All previously applied film forming products should be totally removed. Any discoloured wood should be sanded until an original surface is visible. As wood-stains provide a semi-transparent finish any marks, blemishes or stains in the substrate will show after treatment. Remove mould, algae, lichens and moss with a stiff brush and scraper. Repair any damaged areas; large cracks and open joints should be filled with a suitable flexible filler/stopper. Lightly abrade using fine grade abrasive paper, sanding with fine sandpaper should always be in the direction of the grain. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Temperature (air, surface, material) (at least 4°C above dew point) 10°C to 42°C. Relative Humidity 75% maximum. Wait 4 hours between coats. 3 coats required for maximum protection

SPREADING RATE



As a guide a coverage rate of up to 16m²/litre can be achieved under normal conditions.

REDUCTION

Do **not** reduce this product

SPRAY RECOMMENDATIONS

Conventional Spray: Satisfactory through most equipment.
Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lbs/in²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 1 hour
Recoat: 4 hours
This is dependent upon temperature and humidity. Darker colours may take longer. 26°C to 50% RH @ 4 Thou wet.

CLEANING UP



Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.

PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleaner. Do not take internally. If medical advice is needed, have product container or label at hand. Dispose of contents to a waste disposal facility in accordance with local/national regulations. Safety data sheet available on request. Contains no added lead.

PREVIOUSLY PAINTED SURFACES

All previously applied film forming products should be totally removed. Any discoloured wood should be sanded until an original surface is visible.

FOLLOW US ON

Online: www.fleetwood.ie
Email: info@fleetwood.ie
Phone: 049 8547209

