

Product Fleetwood Traditional Oil Based High Gloss
 Revision date 12 November 2020
 Revision 1



Safety Data Sheet (SDS)
 according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Fleetwood Traditional Oil Based High Gloss
Other means of identification PX3X-AETE-5203-ET1M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint or paint related material.
Uses advised against No uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd.
 Virginia
 Co Cavan
 Ireland
 Tel: 353 49854 7209
Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone + 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)
National emergency telephone number Outside those hours, contact National Poisons Information Centre, Beaumont Hospital.
 Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare
 Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)
 Physical and chemical hazards Flam. Liq 3- H226
 Human health Not classified
 Environment Not classified

2.2 Label elements

Contains Not applicable

Label in accordance with (EC) no. 1272/2008



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

Precautionary statements

Prevention

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.
 P233 Keep container tightly closed.
 P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon

dioxide for extinction.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/ container to a licensed hazardous waste disposal facility in accordance with all applicable regulations.

EUH statements

EUH208 Contains Butanone oxime and Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo[3.3.1]-onane-1,5-dicarboxylate-kN3,kN7]-, chloride. May produce an allergic reaction.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0002		20-30%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-XXXX	Asp. Tox - H304, Flam. Liq 3 - H226, STOT SE 3 - H336	10-20%
1-methoxypropan-2-ol	CAS-No.: 107-98-2 EC No.: 203-539-1	Flam. Liq 3 - H226, STOT SE 3 - H336	1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
propane-1,2-diol	CAS-No.: 57-55-6 EC No.: 200-338-0 REACH Reg No.: 01-2119456809-23-XXXX		0.1-0.9%
Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo-3.3.1]nonane-1,5-dicarboxylate-kN3,kN7]-, chloride	CAS-No.: 478945-46-9 EC No.:	Acute Tox 3 - H301, Skin. Sens 1 - H317, STOT RE 2 - H373, Aquatic Chronic 3 - H412	0.1-0.9%
Butanone oxime	CAS-No.: 96-29-7 EC No.: 202-496-6	Acute Tox 4 - H312, Skin. Sens 1 - H317, Eye Dam. 1 - H318, Carc. 2 - H351	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3 - H226, STOT SE 3 - H336	<0.1%
N,N-diethylhydroxylamine	CAS-No.: 3710-84-7 EC No.: 223-055-4 REACH Reg No.: 01-2119962470-39-XXXX	Aquatic Chronic 2 - H411, Acute Tox 4 - H312, Acute Tox 4 - H332, Flam. Liq 3 - H226, STOT SE 3 - H335	<0.1%

Stoddard solvent	CAS-No.: 8052-41-3 EC No.: 232-489-3	Asp. Tox - H304, Muta. 1B - H340, Carc. 1B - H350, STOT RE 1 - H372	<0.1%
------------------	---	---	-------

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures

4.1 Description of first aid measures

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	If this product is inhaled, move the exposed person to fresh air promptly. Seek medical attention if symptoms persist.
Ingestion	Rinse mouth thoroughly. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek medical advice (show the label where possible).
Skin contact	In the case of unintended skin contact or spill: Remove contaminated clothing immediately and wash skin with soap and water. Wash contaminated clothing before reuse. Get medical attention if irritation develops or persists.
Eye contact	If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Inhalation of high concentrations may cause drowsiness, headache, blurred vision, dizziness or nausea.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Fire-fighting measures

5.1 Extinguishing media

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	During fire, toxic gases (CO, CO ₂) are formed.
Unusual fire & explosion hazards	Flammable vapours may spread to sources of ignition or accumulate in confined spaces.
Specific hazards	In the event of damage to packaging, floors may become slippery, avoid falls. Do not allow run-off from fire fighting to enter drains or water courses. Vapours may be ignited by a spark, a hot surface or an ember. Flash back possible over considerable distance.

5.3 Advice for firefighters

Special fire fighting procedures	If possible, fight fire from protected position. Avoid breathing fire vapours. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so. Dike and collect extinguishing water.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. Do not touch or walk through spilled material. If necessary evacuate surrounding areas. Non sparking tools should be used. Do not smoke, eat or drink while using this product.
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions

Environmental precautions	Do not discharge into drains, water courses or onto the ground. Prevent material from entering sewers, waterways, or low areas.
----------------------------------	---

6.3 Methods and material for containment and cleaning up

Spill clean up methods	Stop leak if possible without risk. Wear appropriate personal protective equipment as specified in Section 8. Eliminate all ignition sources. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage. Floors may become slippery, avoid falls.
-------------------------------	--

6.4 Reference to other sections

Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
------------------------------------	--

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Provide good ventilation. Protect against static electricity. Avoid inhalation of vapours.
-----------------	---

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions	Keep locked up and out of reach of children. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from sources of ignition. Keep away from incompatible materials (see section 10).
Storage class	Flammable liquid storage.

7.3 Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (15mins)	Notes
titanium dioxide	OEL		10 mg/m ³	
titanium dioxide	OEL		4 mg/m ³	

titanium dioxide	WEL		10 inhalable aerosol mg/m ³			
titanium dioxide	WEL		4 respirable aerosol mg/m ³			
1-methoxypropan-2-ol	OEL	100 ppm	375 mg/m ³	150 ppm	568 mg/m ³	IOELV
1-methoxypropan-2-ol	WEL	100 ppm	375 mg/m ³	150 ppm	560 mg/m ³	Sk
propane-1,2-diol	OEL	150 ppm	470 mg/m ³			
propane-1,2-diol	OEL		10 mg/m ³			
propane-1,2-diol	WEL		10 mg/m ³			
propane-1,2-diol	WEL	150 ppm	474 mg/m ³			
Butanone oxime	OEL	3 ppm	10 mg/m ³	10 ppm	33 mg/m ³	Sens.
nonane	OEL	200 ppm	1050 mg/m ³			
N,N-diethylhydroxylamine	OEL	2 ppm				
Stoddard solvent	OEL	100 ppm	573 mg/m ³			Carc.1B Muta.1B

Ingredient comments

Ireland, Occupational Exposure Limits 2020.
Workplace Exposure Limits Guidance Note EH40/2005.

8.2 Exposure Controls**Protective equipment****Engineering measures**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours are present, and which can direct static electricity by grounding equipment.

Respiratory equipment

Respiratory protection not required in normal conditions. In case of large scale spill in confined area: Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for organic vapour/particulate (EN 141). ABEK (EN 14387). Consult manufacturer for specific advice.

Hand protection

Not normally required, however helpful for prolonged or repeated contact. (Suggested suitable materials for longer, direct contact or splash contact) Suggested material: Nitrile rubber. Layer thickness: 0.33 mm. Breakthrough time: >480 minutes. Consult manufacturer for advice. Recommended properties: Impervious gloves in accordance with standard EN374. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Eye protection

If there is a risk of eye contact: Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU). Safety glasses with side shields.

Other protection

Protective clothing not required for normal use of the product. Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures

Observe normal hygiene standards. When using do not eat, drink or smoke.

Process conditions

Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	Viscous liquid.
Colour	White
Odour	Hydrocarbon. Slight.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	Not applicable.

pH-Value, Diluted solution	Not applicable.
Melting point	May start to solidify at the following temperature: -15°C This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Weighted average: -58.56°C
Initial boiling point and boiling range	>142°C
Flash point	Closed cup 42°C
Evaporation rate	Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics) Weighted average: 0.03 compared with butyl acetate
Flammability state	Liquid.
Flammability limit - lower(%)	0.6%(Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Flammability limit - upper(%)	Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Vapour pressure	Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha(petroleum), hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20°C)
Vapour density (air=1)	Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Relative density	1.25 +/- 0.2
Bulk density	No information available as testing has not been completed.
Solubility	Insoluble in cold water.
Decomposition temperature	Stable under normal handling and storage conditions
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Viscosity	Kinematic (40°C): >0.31 cm ² /s
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	No information available as testing has not been completed.
Volatile organic compound	298.00 g/litre
Other information	Volume solids: 59.0% +/- 1.0% Weight Solids: 71. +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	See section 10.3 for further information. Keep away from incompatibles such as oxidizing agents, acids, and alkalis.
-------------------	--

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use
------------------	--

10.3 Possibility of hazardous reactions

Hazardous reactions	Flammable liquid and vapour.
Hazardous polymerisation	Unknown
Polymerisation description	Unknown.

10.4 Conditions to Avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition. Extremes of temperature and direct sunlight.
----------------------------	--

10.5 Incompatible materials

Materials to avoid	Keep away from incompatibles such as oxidizing agents, acids, alkalis.
---------------------------	--

10.6 Hazardous decomposition products

Hazardous decomposition products	Fire creates: Toxic gases/vapours/fumes of carbon monoxide (CO), and carbon dioxide (CO ₂).
---	---

Section 11: Toxicological information

11.1 Information on toxicological effects

Toxicological information	Not classified based on available information.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.
Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	May cause temporary eye irritation.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is not classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is not classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is not classified as a repeat exposure specific target organ toxin.
Inhalation	Inhalation of high concentrations may cause drowsiness, headache, blurred vision, dizziness or nausea.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product. Since emptied containers contain product residue, follow label warnings even after container is emptied.
Routes of entry	Eyes, skin, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system, central nervous system.
Aspiration hazards:	The product is not classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
nonane			3200.00ppmV Rat 4 Hours 17000.00mg/m-3 Rat 4 Hours
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat	>5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
titanium dioxide	10000.00mg/kg Rat		
1-methoxypropan-2-ol	=4016.00mg/kg Rat		=6500.00ppmV Rat 4 Hours
Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo-3.3.1nonane-1,5-dicarboxylate-kN3,kN7]-, chloride	>200.00mg/kg Rat	>2000.00mg/kg Rat	
Stoddard solvent	>5000.00mg/kg Rat	>3000.00mg/kg Rabbit	>5500.00mg/m-3

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	No ecological toxicity data available for the overall finished product.

12.2 Persistence and degradability

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No information available as testing has not been completed.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.

12.4 Mobility in soil

Mobility	Insoluble in cold water.
-----------------	--------------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 96 Hours >100.00ppm Freshwater Fish	LC50 48 Hours >100.00ppm Daphnia magna	

1-methoxypropan-2-ol	LC50 96 Hours =6812.00mg/l Leuciscus idus (Golden Orfe)	LC50 48 Hours =23000.00mg/l Daphnia magna	EC50 =1000.00mg/l Senastrum Capricornutum
Butanone oxime	LC50 48 Hours 560.00mg/l LC50 96 Hours 46.00mg/l Lepomis macrochirus (Bluegill)	LC50 48 Hours 750.00mg/l Daphnia magna	LC50 72 Hours 83.00mg/l
Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo-3.3.1]nonane-1,5-dicarboxylate-kN3,kN7]-, chloride	LC50 96 Hours >100.00mg/l Brachydanio rerio (Zebra Fish)	EC50 48 Hours 23.70mg/l Daphnia magna	
Stoddard solvent			

Section 13: Disposal considerations

Waste management

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Since emptied containers contain product residue, follow label warnings even after container is emptied.

13.1 Waste treatment methods

Disposal methods

Dispose of waste and residues in accordance with local authority requirements, and in accordance with all local, national and international regulations.

Section 14: Transport information

14.1 UN number

UN no. (ADR)	UN1263
UN no. (IMDG)	UN1263
UN no. (IATA)	UN1263

14.2 UN proper shipping name

ADR proper shipping name	PAINT or PAINT RELATED MATERIAL
IMDG proper shipping name	PAINT or PAINT RELATED MATERIAL
IATA proper shipping name	PAINT

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels



14.4 Packing group

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-E
-----	----------

Emergency action code	A3 A72 A192
Hazard no. (ADR)	30
Tunnel restriction code	(D/E)

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 830/2015 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019) Workplace Exposure Limits Guidance Note EH40/2005.
Chemical safety assessment	No chemical safety assessment has been carried out.

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a first issue.
Revision date	12 November 2020
Revision	1
Safety data sheet status	Approved.

Hazard statements in full

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child .
H301	Toxic if swallowed.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.
H312	Harmful in contact with skin.
H318	Causes serious eye damage.
H351	Suspected of causing cancer .
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H360	May damage fertility or the unborn child .
H340	May cause genetic defects .
H350	May cause cancer .
H372	Causes damage to organs through prolonged or repeated exposure .
EUH208	Contains Butanone oxime and Iron(1+), chloro[dimethyl 9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-kN)-7-[(2-pyridinyl-kN)methyl]-3,7-diazabicyclo[3.3.1]n-nane-1,5-dicarboxylate-kN3,kN7]-, chloride. May produce an allergic reaction.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of

the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.