Product METALSHIELD Silver
Revision date 22 October 2021

**Revision** 2



# **Safety Data Sheet (SDS)**

according to Regulation (EC) No. 1907/2006

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name METALSHIELD Silver Other means of identification UFI: D4CX-UESR-V20P-YG01

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint or paint related material.

Uses advised against Any other purpose.

## 1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd

Virginia Co Cavan Ireland

Tel: 353 49854 7209

Contact person info@fsw.ie

## 1.4 Emergency telephone number

Emergency telephone

National emergency telephone

number

+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

Outside those hours, contact National Poisons Information Centre, Beaumont Hospital. Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare

Professionals: +353 (1) 809 2566 (24 hour service)

### **Section 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Flam. Liq 3- H226

Human health Eye Irrit.2A - H319, STOT SE 3 - H336, Skin. Sens 1 A- H317

Environment Aquatic Chronic 2 - H411

2.2 Label elements

Contains Cobalt bis(2-ethylhexanoate)

dodecane-1-thiol

 $Hydrocarbons, C9-C11, \, n\hbox{-alkanes, isoalkanes, cyclics,} < 2\% \ aromatics$ 

Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum),

hydrodesulfurized heavy (benzene< 0,1 %)

Label in accordance with (EC) no. 1272/2008





Signal word Warning

**Hazard statements** H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements Prevention

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

## Response

P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) for extinction.

## Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

## 2.3 Other hazards

None known.

# Section 3: Composition/information on ingredients

## 3.1 Substance

Not applicable.

## 3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5	Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	40-50%
trizinc bis(orthophosphate)	CAS-No.: 7779-90-0 EC No.: 231-944-3	Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	5-10%
Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene< 0,1 %)	CAS-No.: 64742-82-1 EC No.: 919-446-0 REACH Reg No.: 01-2119458049-33	STOT SE 3 - H336, Asp. Tox - H304, Flam. Liq 3- H226, Aquatic Chronic 2 - H411	1-5%
Aluminium powder (stabilised)	CAS-No.: 7429-90-5 EC No.: 231-072-3	Flam. Sol 1- H228, Water-react 2 - H261	1-5%
1-methoxy-2-propanol	CAS-No.: 107-98-2 EC No.: 203-539-1	Flam. Liq 3- H226, STOT SE 3 - H336	1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
Isopropoxyethanol	CAS-No.: 109-59-1 EC No.: 203-685-6 REACH Reg No.: 1-2119494720-35-xxxx	Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319, Flam. Liq 3- H226	0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit.2A - H319, Skin. Sens 1 A- H317, Repr. 1B- H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
naphthalene	CAS-No.: 91-20-3 EC No.: 202-049-5	Acute Tox 4 - H302, Carc. 2 - H351, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	0.1-0.9%
Ethanol	CAS-No.: 64-17-5 EC No.: 200-578-6 REACH Reg No.: 01-2119457610-43	Eye Irrit.2A - H319, Flam. Liq 2- H225	<0.1%
dodecane-1-thiol	CAS-No.: 112-55-0 EC No.: 203-984-1	Skin Corr. 1C - H314, Skin. Sens 1 A- H317, Aquatic Chronic 1 - H410	<0.1%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

# **Composition comments**

The data shown are in accordance with the latest EC Directives.

Proprionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % <= C < 25 %, STOT SE 3; H335: C >= 10 %, Skin Corr. 1B; H314: C >= 25 %, Skin Irrit. 2; H315: 10 % <= C < 25 %.

Ethanol: Specific Concentration Limits - Eye Irrit. 2; H319: >= 50.

Cobalt bis(2-ethylhexanoate): M (acute) = 1.

#### **Section 4: First aid measures**

#### 4.1 Description of first aid measures

General information General first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if

symptoms persist, always call a doctor. NEVER induce swallowing in an unconscious person.

Show this safety data sheet or product label to medical personnel.

InhalationRemove the affected person to fresh air, obtain medical attention if symptoms persist.IngestionRinse mouth thoroughly. DO NOT induce vomiting. Get medical attention immediately.Skin contactRemove contaminated clothing immediately and wash skin with soap and water. Launder

contaminated clothing before reuse. Get medical attention if symptoms persist.

Eye contact Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes

with plenty of water while lifting the eye lids. Rinse with a gentle stream water for at least

15 minutes. Get prompt medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

**General information** The severity of the symptoms described will vary dependant of the concentration and the

length of exposure.

**Inhalation** May cause drowsiness or dizziness.

**Ingestion** Prolonged exposure to product may cause irritation to lining of the mouth.

**Skin contact** Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin

reaction.

**Eye contact** Causes serious eye irritation.

## 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to the physician** Treat symptomatically.

## **Section 5: Firefighting measures**

## 5.1 Extinguishing media

chemical or carbon dioxide (CO2) to extinguish flames.

Unsuitable extinguishing media High volume water jet.

## 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Unusual fire & explosion hazards

Specific hazards

When heated, toxic and corrosive vapours/gases may be formed

No unusual fire or explosion hazards noted. If heated, harmful vapours may be formed.

## 5.3 Advice for firefighters

**Special fire fighting procedures** Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires

from safe distance or protected location. Do not scatter spilled material with more water  $% \left( 1\right) =\left( 1\right) \left( 1\right$ 

than needed to fight the fire Do not get water inside container

**Protective equipment for firefighters** Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard

EN 469 will provide a basic level of protection for chemical incidents.

# Section 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke,

use open fire or other sources of ignition. Make safe all sources of ignition. Avoid contact

with skin and eyes.

For emergency responders Follow safe handling advice and personal protective equipment recommendations for normal

use of product.

#### **6.2 Environmental precautions**

**Environmental precautions** Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency

or other appropriate regulatory body.

## 6.3 Methods and material for containment and cleaning up

Stop leak if possible without risk. Wear necessary protective equipment. Absorb spillage with Spill clean up methods

non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled

container. Wash thoroughly after dealing with a spillage.

6.4 Reference to other sections

Reference to other sections For waste disposal, see section 13. See section 1 for emergency contact. For personal

protection, see section 8

## **Section 7: Handling and storage**

## 7.1 Precautions for safe handling

Handling

Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment. Avoid spilling, skin and eye contact. Do not use contact lenses. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Ensure adequate ventilation. Vapours are heavier than air and may spread along floors. Do not eat, drink or smoke when using the product.

## 7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Keep

> upright. Keep locked up and out of reach of children. Avoid storing for very long periods. Keep container tightly sealed when not in use. Bags or containers, which are opened, must be carefully resealed to prevent leakage. Avoid contact with oxidising agents. Store away from acids. Store separate from alkalis. Store in cool dry areas away from direct sunlight or

sources of ignition. Store away form other chemicals.

Storage class Flammable liquid storage.

7.3 Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1. Usage description

Use only according to directions. Replace and tighten cap after use.

## **Section 8: Exposure controls/Personal protection**

## **8.1 Control parameters**

Component	STD	TWA (	8 Hrs)	STEL (1	15mins)	Notes
Aluminium powder (stabilised)	OEL		1 (R) mg/m <sup>3</sup>			
1-methoxy-2-propanol	OEL	100 ppm	375 mg/m <sup>3</sup>	150 ppm	568 mg/m <sup>3</sup>	IOELV
Isopropoxyethanol	OEL	25 ppm	106 mg/m <sup>3</sup>			Sk
Ethanol	OEL			1000 ppm		
dodecane-1-thiol	OEL	0.1 ppm				Sens.
Naphthalene	OEL	10 ppm	50 mg/m <sup>3</sup>			IOELV
nonane	OEL	200 ppm	1050 mg/m <sup>3</sup>			
propionic acid	OEL	10 ppm	31 mg/m <sup>3</sup>	20 ppm	62 mg/m <sup>3</sup>	IOELV
octane	OEL	300 ppm	1450 mg/m <sup>3</sup>			

**Ingredient comments** 

Ireland, Occupational Exposure Limits 2021.

# **8.2 Exposure Controls**

Protective equipment





**Engineering measures** Provide adequate ventilation, including appropriate local extraction, to ensure that the

defined occupational exposure limit is not exceeded.

**Respiratory equipment** Where risk assessment shows air-purifying respirators are appropriate a full face respirator

conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Use type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Change filters frequently. Consult

manufacturer for specific advice.

**Hand protection** Use suitable protective gloves if there is a risk of skin contact. Use proper glove removal

technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Change gloves regularly. Suggested material: Nitrile rubber gloves. Minimum layer thickness: 0.7mm. Minimum breakthrough time / gloves: 480 min.

**Eye protection** Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment

for eye protection tested and approved under appropriate government standards such as EN

166(EU).

Other protection Protective clothing should be selected based on the task being performed and the risks

involved and should be approved by a specialist before handling this product. The selected

clothing must satisfy the European norm standard EN 943.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or

smoke.

**Process conditions** Keep container tightly sealed when not in use. Ensure that eye flushing systems are located

close by in the work place.

#### Section 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance Viscous liquid.
Colour Silver

**Odour** Faint hydrocarbon odour.

Odour threshold - lower No information available as testing has not been completed.

Odour threshold - upper No information available as testing has not been completed.

**pH-Value, Conc. Solution** Not applicable.

**pH-Value, Diluted solution** Not applicable.

**Melting point** Not applicable.

Initial boiling point and boiling

range

Not applicable.

Flash point 40.00 °C

**Evaporation rate** Not applicable.

Flammability state Liquid.

Flammability limit - lower(%) Lower: 1.48%

Flammability limit - upper(%) Upper: 13.74%

Vapour pressure Not applicable.

Vapour density (air=1) Highest known value: 1.1 kPa (8.5 mm Hg) (at 20°C)

Relative density 0.96

**Bulk density** No information available as testing has not been completed.

**Solubility** Insoluble in cold water.

**Decomposition temperature** Stable under normal handling and storage conditions

Partition coefficient; n- No information available as testing has not been completed.

Octanol/Water

Auto ignition temperature (°C) Lowest known value: 270°C

**Viscosity** Kinematic  $(25^{\circ}\text{C})$ : = 5.63 cm<sup>2</sup>/s

**Explosive properties** Formation of explosive vapour is possible.

Oxidising properties The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight No information available as testing has not been completed.

Volatile organic compound 453g/l (max)

**Other information** Volume solids: 52.0% +/- 1.0%

Weight Solids: 52.0% +/- 1.0%

## Section 10: Stability and reactivity

#### 10.1 Reactivity

**Reactivity** Reactions may occur with strong oxidising agents.

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

## 10.3 Possibility of hazardous reactions

**Hazardous reactions** For information on hazardous reaction see section 10.1.

Hazardous polymerisationUnknown.Polymerisation descriptionUnknown.

10.4 Conditions to Avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Extremes of temperature and direct

sunlight.

10.5 Incompatible materials

Materials to avoid Strong oxidising substances. Do not mix with other chemicals unless listed on directions.

## 10.6 Hazardous decomposition products

**Hazardous decomposition products** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours.

## **Section 11: Toxicological information**

# 11.1 Information on hazard classses as defined in Regulation (EC) No. 1272/2008

**Toxicological information** No toxicological information for the overall finished product.

Acute toxicity (Oral LD50)

Acute toxicity (Dermal LD50)

Acute toxicity (Inhalation LD50)

No information available as testing has not been completed.

No information available as testing has not been completed.

No information available as testing has not been completed.

**Serious eye damage/irritation** Causes serious eye irritation.

**Skin corrosion/irritation** The product is not classified as a skin corrosion/irritation hazard.

**Respiratory sensitisation**The product is not classified as a respiratory hazard. **Skin sensitisation**The product is classified as a skin sensitisation hazard.

**Germ cell mutagenicity** The product is not classified as a mutagen.

**Carcinogenicity** The product is not classified as a carcinogen hazard.

Specific target organ toxicity - Single exposure:

**STOT - Single exposure** The product is classified as a single exposure specific target organ toxin.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposure The product is not classified as a repeat exposure specific target organ toxin.

**Inhalation** May cause drowsiness or dizziness.

**Ingestion** Prolonged exposure to product may cause irritation to lining of the mouth.

Skin contact Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin

reaction.

**Eye contact** Causes serious eye irritation.

**Waste management** When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

**Routes of entry** Eyes, skin, ingestion or inhalation.

**Target organs** Eyes, skin, digestive system, respiratory system.

**Aspiration hazards:** The product is not classified as an aspiration hazard. **Reproductive toxicity:** The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
1-methoxy-2-propanol	=4016.00mg/kg Rat		=6500.00ppmV Rat 4 Hours
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat >5000.00mg/kg Rat	>5000.00mg/kg Rabbit >5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
Isopropoxyethanol	5600.00mg/kg Rat	1440.00mg/kg Rabbit	
Ethanol	7060.00mg/kg Rat		124.70mg/l (vapours) Rat 4 Hours
Naphthalene	>2000.00mg/kg Rat	>2000.00mg/kg Rabbit	

### 11.2 Information on other hazards

Information on other hazards None known.

#### **Section 12: Ecological information**

## 12.1 Toxicity

Acute toxicity - Fish
No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates
No information available as testing has not been completed.
Acute toxicity - Aquatic plants
Acute toxicity - Microorganisms
No information available as testing has not been completed.
No information available as testing has not been completed.
No information available as testing has not been completed.
Chronic toxicity - Aquatic
No information available as testing has not been completed.
No information available as testing has not been completed.

invertebrates

Chronic toxicity - Aquatic plants

No information available as testing has not been completed.

No information available as testing has not been completed.

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause

long term adverse effects in the aquatic environment.

**Eco toxilogical information** The product contains a substance which is toxic to aquatic organisms.

# 12.2 Persistence and degradability

DegradabilityThe degradability of the product has not been stated.Biological oxygen demandNo information available as testing has not been completed.Chemical oxygen demandNo information available as testing has not been completed.

## 12.3 Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Bioaccumulation factor**No information available as testing has not been completed.

Partition coefficient; n-Octanol/Water No information available as testing has not been completed.

## 12.4 Mobility in soil

**Mobility** Insoluble in cold water.

#### 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

## 12.6 Endocrine disrupting properties

**Endocrine disrupting properties** The product does not contain any substances with endocrine disrupting properties at a

concentration above or equal to 0.1%.

## 12.7 Other adverse effects

Other adverse effects None known.

Name	Acute toxicity (Fish)	3 ` 1	Acute toxicity (Aquatic plants)
1-methoxy-2-propanol		Danhnia magna	EC50 =1000.00mg/l Selenastrum Capricornutum
propionic acid	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)		EC50 96 Hours 43.00mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		LC50 48 Hours >100.00ppm Daphnia magnaLC50 48 Hours >100.00ppm Daphnia magna	
Isopropoxyethanol		EC50 48 Hours 3610.00ppm Daphnia magna	
Ethanol	LC50 96 Hours 100.00mg/l Pimephales promelas (Fat-head Minnow)		

# **Section 13: Disposal considerations**

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

## 13.1 Waste treatment methods

**Disposal methods** Dispose of waste and residues in accordance with local authority requirements, and in

accordance with all local, national and international regulations.

## **Section 14: Transport information**

## 14.1 UN number or ID number

 UN no. (ADR)
 UN1263

 UN no. (IMDG)
 UN1263

 UN no. (IATA)
 UN1263

## 14.2 UN proper shipping name

ADR proper shipping name
IMDG proper shipping name
PAINT OF PAINT RELATED MATERIAL
PAINT OF PAINT RELATED MATERIAL
PAINT OF PAINT RELATED MATERIAL
PAINT

## 14.3 Transport hazard class(es)

ADR class 3
IMDG class 3
IATA class 3

#### **Transport labels**



#### 14.4 Packing group

ADR/RID/ADN packing group III
IMDG packing group III
IATA packing group III

#### 14.5 Environmental hazards

ADR Yes IMDG Yes IATA Yes

# 14.6 Special precautions for user

**EMS** F-E, S-E **Emergency action code** A3 A72 A192

**Hazard no. (ADR)** 30 **Tunnel restriction code** (D/E)

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

## **Section 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

**EU legislation** Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Reach Regulation (EC) No 453/2010. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and

Restriction of Chemicals (REACH).

**Approved code of practice** 2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents)

Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens)

Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment No chemical safety assessment has been carried out.

## **Section 16: Other information**

**General information** This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 2020/878.

**Revision comments** [1]Information updated. [2]Information updated. [3]Information updated. [4]Information

updated. [8]Information updated. [9]Information updated. [11]Information updated.

[12]Information updated. [15]Information updated. This is a second issue.

**Revision date** 22 October 2021

Revision 2

Safety data sheet status Approved.

## **Hazard statements in full**

**EUH066** Repeated exposure may cause skin dryness or cracking.

**H226** Flammable liquid and vapour.

**H304** May be fatal if swallowed and enters airways.

**H336** May cause drowsiness or dizziness.

**H400** Very toxic to aquatic life.

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H318	Causes serious eve damage.
H302	Harmful if swallowed.
Н319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H361	Suspected of damaging fertility or the unborn child .
H312	Harmful in contact with skin.
Н332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H351	Suspected of causing cancer .
H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.

## Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.