Product Fleetwood Polyurethane Gloss Varnish

Revision date 03 February 2021

Revision 2



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Fleetwood Polyurethane Gloss Varnish

Other means of identification WV4X-WEDS-H20J-PJFA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified usesPaint or paint related material.Uses advised againstNo uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd.

Virginia Co Cavan Ireland

Tel: 353 49854 7209

Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone

National emergency telephone

number

+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

Outside those hours, contact National Poisons Information Centre, Beaumont Hospital. Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare

Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Flam. Liq 3- H226 Human health STOT SE 3 - H336 Environment Not classified

2.2 Label elements

Contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

nonane octane

Label in accordance with (EC) no. 1272/2008



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements Prevention

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

Response

P370 + P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

EUH statements

 ${\tt EUH208}$ Contains but anone oxime and Cobalt bis (2-ethylhexanoate). May produce an allergic reaction.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 64742-48-9 EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-xxxx	STOT SE 3 - H336, Asp. Tox - H304, Flam. Liq 3- H226	
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
Butanone oxime	CAS-No.: 96-29-7 EC No.: 202-496-6	Acute Tox 4 - H312, Skin. Sens 1 - H317, Eye Dam. 1 - H318, Carc. 2 - H351	0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit.2A - H319, Skin. Sens 1 A- H317, Repr. 1B- H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Proprionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % <= C < 25 %, STOT SE 3; H335: C >= 10 %, Skin Corr. 1B; H314: C >= 25 %, Skin Irrit. 2; H315: 10 % <= C < 25 %.

Butanone oxime: Acute Toxicity Estimates (ATE)- dermal: ATE = 1100 mg/kg (-) oral: ATE = 100 mg/kg (-).

Section 4: First aid measures

4.1 Description of first aid measures

General information

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue. If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing is difficult, give oxygen. If breathing has stopped or the exposed

person experiences difficulty in breathing, administer artificial respiration and seek

immediate medical assistance.

Ingestion

Inhalation

Rinse mouth thoroughly. Provide fresh air, warmth and rest. Do not induce vomiting. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness or is convulsing. Seek medical advice (show the label where possible). If vomiting occurs, the head should be kept low so that stomach content doesn't enter the lungs.

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues $\frac{1}{2}$

after rinsing.

Eye contact Do not rub eye. Avoid contaminating unaffected eye. Remove contact lenses if present and

easy to do so. Promptly wash eye(s) with plenty of water while lifting the eye lids. Rinse with

a gentle stream water for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Exposure to product spray mists may be irritating to the respiratory system. Inhalation of

vapours may cause headache, fatigue, dizziness and central nervous system effects.

Ingestion Prolonged exposure to product may cause irritation to lining of the mouth.

Skin contact May cause an allergic skin reaction. Eye contact May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician Treat symptomatically.

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media Use fire-extinguishing media appropriate for surrounding materials. Extinguish with foam,

carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet to extinguish fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Unusual fire & explosion hazards

Specific hazards

During fire, gases hazardous to health may be formed. The product is classified as a flammable liquid and vapour.

If heated, harmful vapours may be formed.

5.3 Advice for firefighters

Special fire fighting procedures

Ventilate closed spaces before entering them. Water spray should be used to cool containers. If possible, fight fire from protected position. Keep up-wind to avoid fumes.

Protective equipment for firefighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. For non-emergency personnel

Wear protective clothing as described in Section 8 of this safety data sheet. If necessary

evacuate surrounding areas. Eliminate all sources of ignition.

Avoid inhalation of vapours and contact with skin and eyes. Do not touch or walk through

spilled material. Read and follow manufacturer's recommendations.

For emergency responders Follow safe handling advice and personal protective equipment recommendations for normal

use of product.

6.2 Environmental precautions

Environmental precautions Prevent any material from entering drains or waterways.

6.3 Methods and material for containment and cleaning up

Spill clean up methods Wear appropriate personal protective equipment as specified in Section 8. Prevent further

leakage or spillage if safe to do so. Ventilate and evacuate the area. Eliminate all sources of ignition. Dam and absorb spillage using a spill kit, sand, earth or other non-combustible

Prevent entry to into sewers, water course, basement or confined areas. Use non sparking tools or equipment. Recover by pumping or with suitable absorbent. Place spilled material

into suitable labelled sealed containers. Remove waste promptly to a safe area.

6.4 Reference to other sections

Reference to other sections See section 1 for emergency contact. For personal protection, see section 8. For waste

disposal, see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling

Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear suitable personal protective equipment, as detailed in Section 8. Keep away from heat, sparks and open flame. Earth all equipment. Use only non-sparking tools. Avoid contact with skin and eyes. Avoid inhalation of vapours. Do not use contact lenses. Avoid prolonged or repeated contact. Read and follow manufacturer's recommendations. Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a cool, dry and well-ventilated place. Keep

upright, locked up and out of reach of children. Keep away from incompatible materials (see section 10). Protect against static discharge and keep away from sources of ignition.

Flammable liquid storage.

Storage class

7.3 Specific end use(s)

Specific end use(s) Usage description The identified uses for this product are detailed in Section 1.2. Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (1	(5mins)	Notes
Butanone oxime	OEL	3 ppm	10 mg/m ³	10 ppm	33 mg/m ³	Sens
nonane	OEL	200 ppm	1050 mg/m ³			
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	IOELV
octane	OEL	300 ppm	1450 mg/m ³			

Ingredient comments

Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls

Protective equipment





Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use respiratory protective components with combined A/B/E/KP filter(s) for organic/inorganic/acid/ammonia and particulates.

Hand protection

Handle in accordance with good industrial hygiene and safety practices. Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required. Nitrile rubber. Breakthrough time: > 480 min Layer thickness: 0.33 mm.

Eye protection

Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Other protection Wear suitable protective clothing as protection against splashing or contamination.

Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected

clothing must satisfy the European norm standard EN 943.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or

smoke.

Process conditions Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour Clear.

Odour Hydrocarbon, (slight).

Odour threshold - lower No information available as testing has not been completed.

Odour threshold - upperNo information available as testing has not been completed.

pH-Value, Conc. SolutionNo information available as testing has not been completed.

pH-Value, Diluted solution No information available as testing has not been completed.

Melting point May start to solidify at the following temperature: -15°C This is based on data for the

following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2%

aromatics. Weighted average: -58.56°C

Initial boiling point and boiling

range

>142°C

Flash point 40.00 °C

Evaporation rate No information available as testing has not been completed.

Flammability state Liquid.

Flammability limit - lower(%) No information available as testing has not been completed.

Flammability limit - upper(%) No information available as testing has not been completed.

Vapour pressure No information available as testing has not been completed.

Vapour density (air=1) No information available as testing has not been completed.

Relative density 0.92 +/- 0.06

Bulk density No information available as testing has not been completed.

Solubility Insoluble in cold water

Decomposition temperature Stable under normal handling and storage conditions

Partition coefficient; n-

Octanol/Water

No information available as testing has not been completed.

Auto ignition temperature (°C) Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%

aromatics).

Viscosity Kinematic (40°C): >0.27 cm²/s

Explosive properties Not classified as explosive.

Oxidising properties The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight No information available as testing has not been completed.

Volatile organic compound 353.00 g/litre

Other information Volume solids: 54.0% +/- 1.0%

Weight Solids: 61.0% +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity No specific reactivity hazards associated with this product.

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

10.3 Possibility of hazardous reactions

Hazardous reactionsFlammable liquid and vapour.Hazardous polymerisationNo information available.

Polymerisation description Unknown.

10.4 Conditions to Avoid

Conditions to avoid Heat, sparks, open flames, temperature extremes and direct sunlight.

10.5 Incompatible materials

Materials to avoid Do not mix with other chemicals unless listed on directions.

10.6 Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other harmful gases

or vapors.

Section 11: Toxicological information

11.1 Information on hazard classses as defined in Regulation (EC) No. 1272/2008

Toxicological information No toxicological information for the overall finished product.

Acute toxicity (Oral LD50)

Acute toxicity (Dermal LD50)

Acute toxicity (Inhalation LD50)

No information available as testing has not been completed.

No information available as testing has not been completed.

No information available as testing has not been completed.

Serious eye damage/irritation Product is not classified as an eye irritant.

Skin corrosion/irritation The product is not classified as a skin corrosion/irritation hazard.

Respiratory sensitisationThe product is not classified as a respiratory hazard. **Skin sensitisation**The product is not classified as a skin sensitisation hazard.

Germ cell mutagenicity The product is not classified as a mutagen.

Carcinogenicity The product is not classified as a carcinogen hazard.

Specific target organ toxicity - Single exposure:

STOT - Single exposure The product is classified as a single exposure specific target organ toxin.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposure The product is not classified as a repeat exposure specific target organ toxin.

Inhalation Exposure to product spray mists may be irritating to the respiratory system. Inhalation of

vapours may cause headache, fatique, dizziness and central nervous system effects.

Ingestion Prolonged exposure to product may cause irritation to lining of the mouth.

Skin contactMay cause an allergic skin reaction. **Eye contact**May cause temporary eye irritation.

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

Routes of entry Eyes, skin, ingestion or inhalation.

Target organs Eyes, skin, digestive system, respiratory system.

Aspiration hazards: The product is not classified as an aspiration hazard. **Reproductive toxicity:** The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat >5000.00mg/kg Rat	>5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
nonane			3200.00ppmV Rat 4 Hours17000.00mg/m-3 Rat 4 Hours
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	

11.2 Information on other hazards

Information on other hazards None known.

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish

Acute toxicity - Aquatic invertebrates

No information available as testing has not been completed.

Acute toxicity - Aquatic invertebrates

No information available as testing has not been completed.

Acute toxicity - Aquatic plants

Acute toxicity - Microorganisms

Chronic toxicity - Fish

Chronic toxicity - Aquatic

No information available as testing has not been completed.

No information available as testing has not been completed.

No information available as testing has not been completed.

inverteb rates

Chronic toxicity - Aquatic plants
Chronic toxicity - Microorganisms

No information available as testing has not been completed.
No information available as testing has not been completed.

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Eco toxilogical information No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

DegradabilityThe degradability of the product has not been stated.Biological oxygen demandNo information available as testing has not been completed.Chemical oxygen demandNo information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential
Bioaccumulation factor
Partition coefficient; nOctanol/Water

No data available on bioaccumulation.
No information available as testing has not been completed.
No information available as testing has not been completed.

12.4 Mobility in soil

Mobility Insoluble in water.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties The product does not contain any substances with endocrine disrupting properties at a

concentration above or equal to 0.1%.

12.7 Other adverse effects

Other adverse effects None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
alkanes, isoalkanes, cyclics,	1 1 1	EC50 48 Hours >1000.00ppm Daphnia magnaEC50 48 Hours >1000.00ppm Daphnia magna	
		3, 1	LC50 72 Hours 83.00mg/l
	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)		EC50 96 Hours 43.00mg/l

Section 13: Disposal considerations

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

13.1 Waste treatment methods

Disposal methods Dispose of waste and residues in accordance with local authority requirements. For waste

disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information

14.1 UN number or ID number

 UN no. (ADR)
 UN1263

 UN no. (IMDG)
 UN1263

 UN no. (IATA)
 UN1263

14.2 UN proper shipping name

ADR proper shipping name PAINT OF PAINT RELATED MATERIAL IMDG proper shipping name PAINT OF PAINT RELATED MATERIAL

IATA proper shipping name PAINT

14.3 Transport hazard class(es)

ADR class 3
IMDG class 3
IATA class 3

Transport labels



14.4 Packing group

ADR/RID/ADN packing group III
IMDG packing group III
IATA packing group III

14.5 Environmental hazards

ADR No IMDG No IATA No

14.6 Special precautions for user

EMS F-E, S-E **Emergency action code** A3 A72 A192

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH).

Approved code of practice 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents)

Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens)

Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment No chemical safety assessment has been carried out.

Section 16: Other information

General information This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.

Revision comments This is a second issue. [1]Information updated. [3]Information updated. [4]Information

updated. [8]Information updated. [9]Information updated. [11]Information updated.

[12]Information updated. [15]Information updated.

Revision date 03 February 2021

Revision 2

Safety data sheet status Approved.

Hazard statements in full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child .

H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H351 Suspected of causing cancer .
H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child .

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

H315 Causes skin irritation.

H410 Very toxic to aquatic life with long lasting effects.
H314 Causes severe skin burns and eye damage.
H225 Highly flammable liquid and vapour.

EUH208 Contains butanone oxime and Cobalt bis(2-ethylhexanoate). May produce an allergic

reaction.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.