

### PRODUCT DESCRIPTION & USE

**Fleetwood Trade Terminator (Aerosol)** is an aerosolised, pigmented shellac-based primer sealer, stain killer and bond coat. It is recommended for application to interior ceilings, walls, doors, trim, cabinets, furniture, and related paintable surfaces. Exterior uses are limited to spot priming only. May be used to block water, grease, rust, smoke, graffiti, and many other types of stains.

### KEY BENEFITS

- Dries exceptionally fast recoat in 45 minutes
- Excellent opacity blocks persistent stains
- Outstanding adhesion to glossy surfaces without the need to scuff or sand.
- Designed to permanently block odours from smoke and fire damage
- Seals porous surfaces with excellent enamel holdout

### AVAILABLE IN SIZES

400 ml



### COLOUR RANGE

**Fleetwood Trade Terminator (Aerosol)**  
White

### COMPOSITION (NOMINAL)

<b>Pigment:</b>	Lightfast Pigments.
<b>Binder:</b>	Shellac
<b>Solvent:</b>	Methylated spirits
<b>Propellant</b>	Acetone

### SOLIDS

**Percent Solids, Weight:** 13.0%  
**Percent Solids, Volume:** 10.7%

### SURFACE PREPARATION

All surfaces must be clean, dry and free from all defective or poorly adhering material. Thoroughly rub down previously painted surfaces, using 'wet' 'flattening' methods where possible, wipe off with a damp, lint free cloth. **Note:** Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain lead (Pb). Use in accordance with good painting practices

### SPREADING RATE



As a guide a coverage rate of up to 2m<sup>2</sup> per can may be achieved under normal conditions

### TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### USAGE RECOMMENDATIONS

For interior use only. Use at room temperature in a well ventilated area - avoid high humidity. **Shake can vigorously until ball inside the can rattles.** Turn upside down & continue shaking for one minute - shake occasionally during use. Spray 25-30 cm from object with short 'dusting' strokes. Surface may be painted in 30 minutes. To clear spray for future use, turn can upside down & spray until clear gas is emitted.

### DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



<b>Touch Dry:</b>	20 minutes
<b>Recoat:</b>	45 mins
<b>Hard Dry -</b>	1 - 3 days

This is dependent upon temperature and humidity.

### CLEANING UP



Clean up any overspray and drips immediately with methylated spirits and ammoniated detergent. If spills or drips have dried use methylated spirits or ammoniated detergent to soften and remove primer.

### PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. Extremely flammable keep away from heat, sparks and hot surfaces ensure container is tightly closed when not using. - No smoking. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

### PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.

### FOLLOW US ON

Online: [www.fleetwood.ie](http://www.fleetwood.ie)  
Email: [info@fleetwood.ie](mailto:info@fleetwood.ie)  
Phone: 049 8547209

