

PRODUCT DESCRIPTION & USE

Fleetwood Trade Bloxx-It (Aerosol) is an aerosolised, pigmented premium quality, modified alkyd stain blocking primer undercoat. It dries quickly has great hiding power and outstanding stain killing. It is recommended for application to fire, smoke and water damaged surfaces, including: interior ceilings, walls, doors, trim, cabinets, furniture and related paintable surfaces. Exterior fascia, soffits, trim, doors, walls, railings, and related paintable surfaces.

KEY BENEFITS

- Fast drying recoats in less than 2 hours
- Excellent for sealing damp and water-soluble stains
- Excellent opacity blocks most stains including nicotine and smoke
- Excellent for sealing water-soluble tannin bleed on resin rich woods such as cedar and redwood.
- Suitable for interior and exterior applications

AVAILABLE IN SIZES

400 ml



COLOUR RANGE

Fleetwood Trade Bloxx-It (Aerosol)
White

COMPOSITION (NOMINAL)

| | |
|-------------------|-----------------------------------|
| Pigment: | Lightfast Pigments. |
| Binder: | Modified alkyd resin |
| Solvent: | De-aromatized white spirit |
| Propellant | Acetone & Petroleum liquefied gas |

SOLIDS

Percent Solids, Weight: 15.3%

Percent Solids, Volume: 12.9%

SURFACE PREPARATION

All surfaces must be clean, dry and free from all defective or poorly adhering material. Thoroughly rub down previously painted surfaces, using 'wet' 'flattening' methods where possible, wipe off with a damp, lint free cloth. **Note:** Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain lead (Pb). Use in accordance with good painting practices

SPREADING RATE



As a guide a coverage rate of up to 3m² per can may be achieved under normal conditions

TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

USAGE RECOMMENDATIONS

Bloxx-It is recommended for exterior and interior use. Use at room temperature in a well-ventilated area - avoid high humidity. **Shake can vigorously until ball inside the can rattles.** Turn upside down & continue shaking for one minute – shake occasionally during use. Spray 25-30 cm from object with short 'dusting' strokes. Surface may be painted in 30 minutes. To clear spray for future use, turn can upside down & spray until clear gas is emitted.

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 40 minutes

Recoat: 2 hours

Hard Dry - 3 – 4 days

This is dependent upon temperature and humidity.

CLEANING UP



Clean up spills and drips with a cloth soaked in white spirits or paint thinner. If spills or drips have dried, use paint remover. Application tools may be cleaned using paint thinner – rinse tools repeatedly in white spirits or paint thinner until solvent runs clear and tool is thoroughly cleaned.

PRECAUTIONS

Keep out of reach of children. Ensure good ventilation during application and drying. Extremely flammable keep away from heat, sparks and hot surfaces ensure container is tightly closed when not using. - No smoking. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleaner. Do not take internally. **Contains no added lead.**

PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.

FOLLOW US ON

Online: www.fleetwood.ie

Email: info@fleetwood.ie

Phone: 049 8547209

