Product Bloxx IT Deep Base
Revision date 27 January 2022

Revision 1



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name

Bloxx IT Deep Base
Other means of identification

UFI: VCC0-P0GU-600A-4UH6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint or paint related material.

Uses advised against Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd.

Virginia Co Cavan Ireland

Tel: 353 49854 7209

Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone + 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Flam. Liq 3- H226

Human health STOT SE 3 - H336, Skin. Sens 1 A- H317

Environment Not classified

2.2 Label elements

Contains Cobalt bis(2-ethylhexanoate)

Label in accordance with (EC) no. 1272/2008





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

Precautionary statements Prevention

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P370 + P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for

extinction.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

EUH statements

 $\hbox{EUH211}$ Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-XXXX	Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	20-30%
Talc (Mg3H2(SiO3)4)	CAS-No.: 14807-96-6 EC No.: 238-877-9		1-5%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0002		1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
Isopropoxyethanol	CAS-No.: 109-59-1 EC No.: 203-685-6 REACH Reg No.: 1-2119494720-35-xxxx	Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319, Flam. Liq 3- H226	0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit.2A - H319, Skin. Sens 1 A- H317, Repr. 1B- H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
Ethanol	CAS-No.: 64-17-5 EC No.: 200-578-6 REACH Reg No.: 01-2119457610-43	Eye Irrit.2A - H319, Flam. Liq 2- H225	<0.1%
Naphthalene	CAS-No.: 91-20-3 EC No.: 202-049-5 REACH Reg No.: 01-2119561346-37-XXXX	Acute Tox 4 - H302, Carc. 2 - H351, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Cobalt bis(2-ethylhexanoate): M (acute) = 1.

Ethanol: Specific Concentration Limits - Eye Irrit. 2; H319: >= 50.

Proprionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % <= C < 25 %, STOT SE 3; H335: C >= 10 %, Skin Corr. 1B; H314: C >= 25 %, Skin Irrit. 2; H315: 10 % <= C < 25 %.

Section 4: First aid measures

4.1 Description of first aid measures

Inhalation

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if General information

> symptoms persist, always call a doctor. First aid personnel must be aware of own risk during rescue. Seek medical attention for all eye injuries, regardless how minor they may seem. If this product is inhaled and symptoms occur, move the exposed person to fresh air

> promptly. If breathing has stopped or the exposed person experiences difficulty in breathing,

administer artificial respiration and seek immediate medical assistance.

Ingestion If this product is ingested, remove victim immediately from source of exposure. Thoroughly

rinse the mouth with water. DO NOT induce vomiting! If swallowed, seek medical advice immediately and show the container or label. If vomiting occurs, keep head low so that stomach content doesn't enter the lungs. Never give anything by mouth to an unconscious

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

exposed area with soap and water. Continue to rinse for at least 15 minutes. Get medical

attention if any discomfort continues after rinsing.

Eye contact Avoid contaminating unaffected eye. Immediately flush eyes with plenty of water for at least

15 minutes, lifting lower and upper eyelids occasionally. Remove contact lenses if present and easy to do so. Continue to rinse for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapors may cause drowsiness and dizziness.

Ingestion May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Skin contact May cause an allergic skin reaction. Eye contact May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician Treat symptomatically.

Section 5: Firefighting measures

5.1 Extinguishing media

Use fire-extinguishing media appropriate for surrounding materials. Extinguish with foam, Extinguishing media

carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet to extinguish fire.

5.2 Special hazards arising from the substance or mixture

Combustion may lead to the release of harmful vapours, including but not limited to oxides of Hazardous combustion products

Unusual fire & explosion hazards The product is classified as a flammable liquid and vapour. Vapours are heavier than air and

may spread near ground to sources of ignition. Do not allow to enter drains, sewers, basements and workpits, or any place where its accumulation can be dangerous.

Specific hazards Vapours may be ignited by a spark, a hot surface or an ember. Flash back possible over

considerable distance.

5.3 Advice for firefighters

Special fire fighting procedures Ventilate closed spaces before entering them. Water spray should be used to cool containers.

If possible, fight fire from protected position. Keep up-wind to avoid fumes.

Protective equipment for firefighters Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard

EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all For non-emergency personnel

sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Keep unnecessary and unprotected personnel from entering. Read and follow manufacturer's

recommendations.

Follow safe handling advice and personal protective equipment recommendations for normal For emergency responders

use of product.

6.2 Environmental precautions

Environmental precautions Do not allow to enter sewers/ surface or ground water. Prevent further leakage if safe to do

so. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to

the Environmental Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Spill clean up methods Prevent further leakage or spillage if safe to do so. Ventilate and evacuate the area.

Eliminate all ignition sources.

Dam and absorb spillage using a spill kit, sand, earth or other non-combustible material. Absorb spillage with inert, damp, non-combustible material. Ensure that waste and

contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Use non sparking tools or equipment for clean up.

6.4 Reference to other sections

Reference to other sections See section 1 for emergency contact. For personal protection, see section 8. For waste

disposal, see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling Provide good ventilation. Wear suitable personal protective equipment, as detailed in Section

8. Keep away from ignition sources. Use non sparking tools. Avoid inhalation of vapours.

Avoid contact with skin and eyes.

Read and follow manufacturer's recommendations. Avoid prolonged or repeated contact. Do not wear contact lenses. Read and follow manufacturer's recommendations. Keep container

tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Keep upright, locked up and out of reach of children. Store in closed, labelled containers in a

> cool, dry, well-ventilated area away from incompatible materials. Containers once opened must be carefully resealed to prevent leakage. Protect from direct sunlight. Prohibit ignition

sources close to storage area.

Flammable liquid storage. Storage class

7.3 Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2. Usage description

Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (1	5mins)	Notes
Talc (Mg3H2(SiO3)4)	OEL		10 mg/m ³			
Talc (Mg3H2(SiO3)4)	OEL		0.8 mg/m ³			
titanium dioxide	OEL		10 mg/m ³			
titanium dioxide	OEL		4 mg/m ³			
Isopropoxyethanol	OEL	25 ppm	106 mg/m ³			Sk
Ethanol	OEL			1000 ppm		
Naphthalene	OEL	10 ppm	50 mg/m ³			IOELV
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	IOELV
nonane	OEL	200 ppm	1050 mg/m ³			
octane	OEL	300 ppm	1450 mg/m ³			

Ingredient comments

Ireland, Occupational Exposure Limits 2021.

8.2 Exposure Controls

Protective equipment



Engineering measures Provide adequate ventilation, including appropriate local extraction, to ensure that the

defined occupational exposure limit is not exceeded.

Respiratory equipmentUse respirators and components tested and approved under appropriate government

standards such as CEN (EU). If the respirator is the sole means of protection, use a supplied air self contained breathing apparatus operated in positive pressure mode. Use respiratory protective components with combined A/B/E/KP filter(s) for organic/inorganic/acid/ammonia and particulates. Use respiratory protection as specified by an industrial hygienist or other

 $qualified\ professional.\ Change\ filters\ frequently.$

Hand protection Selection of the glove material depends on consideration of the penetration times, rates of

diffusion and degradation, and concentration specific to the workplace. Where hand contact with the product may occur use gloves approved to relevant standards (e.g. Europe: EN374.)

Gloves must be inspected prior to use.

Suggested material: Nitrile. >8 hours (breakthrough time). Minimum layer thickness: 0.33 mm. Consult manufacturer for specific advice on material. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and

good laboratory practices. Change gloves regularly.

Eye protection Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment

for eye protection tested and approved under appropriate government standards such as EN

166(EU).

Other protection Wear appropriate clothing to prevent any possibility of skin contact. Protective clothing

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the

European norm standard EN 943.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice. Observe normal

hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

Wash promptly if skin becomes contaminated.

Process conditions Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Viscous liquid.
Colour White.

Odour Slight Hydrocarbon.

Odour threshold - lower No information available as testing has not been completed.

Odour threshold - upperNo information available as testing has not been completed.

pH-Value, Conc. Solution Not applicable.pH-Value, Diluted solution Not applicable.

Melting point May start to solidify at the following temperature: -15°C This is based on data for the

following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2%

aromatics. Weighted average: -54.16°C

Initial boiling point and boiling

range

>142°C

Flash point 37.00 °C

Evaporation rate Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%

aromatics) Weighted average: 0.03 compared with butyl acetate

Flammability state Liquid

Flammability limit - lower(%) Greatest known range: Lower: 0.6% (Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, <

2% aromatics)

Flammability limit - upper(%) Greatest known range: Upper: 7% (Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, <

2% aromatics)

Vapour pressure Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha(petroleum),

hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20°C)

Vapour density (air=1) Vapour density Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes,

isoalkanes, cyclics, < 2% aromatics).

Relative density 1.40 + /- 0.2

Bulk density No information available as testing has not been completed.

Solubility Insoluble in cold water

Decomposition temperature Stable under normal handling and storage conditions

Partition coefficient; n-

Octanol/Water

No information available as testing has not been completed.

Auto ignition temperature (°C) Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%

aromatics).

Viscosity Kinematic (room temperature): >4 cm²/s Kinematic (40°C): >0.21 cm²/s

Explosive properties Not classified as explosive.

Oxidising properties The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight No information available as testing has not been completed.

Volatile organic compound 379.00 g/litre

Other information Volume solids: 55.0% +/- 1.0%

Weight Solids: 73.0% + -1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity Reaction with strong acids, strong alkalis and oxidising materials.

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

10.3 Possibility of hazardous reactions

Hazardous reactions For information on hazardous reactions see section 10.1.

Hazardous polymerisationUnknown.Polymerisation descriptionUnknown.

10.4 Conditions to Avoid

Conditions to avoid Heat, sparks, open flames, temperature extremes and direct sunlight.

10.5 Incompatible materials

Materials to avoid Keep away from incompatibles such as oxidizing agents, acids, alkalis. Do not mix with other

chemicals unless listed on directions.

10.6 Hazardous decomposition products

Section 11: Toxicological information

11.1 Information on hazard classses as defined in Regulation (EC) No. 1272/2008

Toxicological information No toxicological information for the overall finished product.

Acute toxicity (Oral LD50)

Acute toxicity (Dermal LD50)

Acute toxicity (Inhalation LD50)

No information available as testing has not been completed.

No information available as testing has not been completed.

No information available as testing has not been completed.

Serious eye damage/irritation Product is not classified as an eye irritant.

Skin corrosion/irritation The product is not classified as a skin corrosion/irritation hazard.

Respiratory sensitisationThe product is not classified as a respiratory hazard. **Skin sensitisation**The product is classified as a skin sensitisation hazard.

Germ cell mutagenicity The product is not classified as a mutagen.

Carcinogenicity The product is not classified as a carcinogen hazard.

Specific target organ toxicity - Single exposure:

STOT - Single exposure The product is classified as a single exposure specific target organ toxin.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposure The product is classified as a repeat exposure specific target organ toxin.

Inhalation Vapors may cause drowsiness and dizziness.

Ingestion May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Skin contactMay cause an allergic skin reaction.Eye contactMay cause temporary eye irritation.

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

Routes of entry Eyes, skin, ingestion or inhalation.

Target organs Eyes, skin, digestive system, respiratory system.

Aspiration hazards: The product is not classified as an aspiration hazard. **Reproductive toxicity:** The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	>5000.00mg/kg Rat >5000.00mg/kg Rat	>5000.00mg/kg Rabbit 3160.00mg/kg Rabbit	>4.95mg/l (vapours) Rat 4 Hours>4950.00mg/m-3 Rat 4 Hours
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	>15000.00mg/kg Rat	>3400.00mg/kg Rabbit	
Isopropoxyethanol	5600.00mg/kg Rat	1440.00mg/kg Rabbit	
Ethanol	7060.00mg/kg Rat		124.70mg/l (vapours) Rat 4 Hours
Naphthalene	>2000.00mg/kg Rat	>2000.00mg/kg Rabbit	
titanium dioxide	10000.00mg/kg Rat		

11.2 Information on other hazards

Information on other hazards None known.

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish No information available as testing has not been completed.

Acute toxicity - Aquatic invertebrates No information available as testing has not been completed.

Acute toxicity - Aquatic plants

Acute toxicity - Microorganisms

Chronic toxicity - Fish

Chronic toxicity - Aquatic

No information available as testing has not been completed.

No information available as testing has not been completed.

No information available as testing has not been completed.

invertebrates

Chronic toxicity - Aquatic plants

Chronic toxicity - Microorganisms

No information available as testing has not been completed.

No information available as testing has not been completed.

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Eco toxilogical information Not classified as dangerous for the environment according to the criteria of Regulation (EC)

No 1272/2008.

12.2 Persistence and degradability

DegradabilityThe degradability of the product has not been stated.Biological oxygen demandNo information available as testing has not been completed.Chemical oxygen demandNo information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential
Bioaccumulation factor
Partition coefficient; nOctanol/Water

No data available on bioaccumulation.
No information available as testing has not been completed.
No information available as testing has not been completed.

12.4 Mobility in soil

Mobility Insoluble in water.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting propertiesThe product does not contain any substances with endocrine disrupting properties at a

concentration above or equal to 0.1%.

12.7 Other adverse effects

Other adverse effects None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
propionic acid	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 22.70ppm Daphnia magna	EC50 96 Hours 43.00mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 96 Hours >100.00ppm Freshwater FishLC50 96 Hours >100.00ppm Freshwater Fish	LC50 48 Hours >100.00ppm Daphnia magnaLC50 48 Hours >100.00ppm Daphnia magna	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LC50 96 Hours 20.00mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 15.00mg/l Daphnia magna	
Isopropoxyethanol		EC50 48 Hours 3610.00ppm Daphnia magna	
Ethanol	LC50 96 Hours 100.00mg/l Pimephales promelas (Fat-head Minnow)		

Section 13: Disposal considerations

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

13.1 Waste treatment methods

Disposal methods

Dispose of waste and residues in accordance with local authority requirements, and in accordance with the European Directives on waste and hazardous waste.

Section 14: Transport information

14.1 UN number or ID number

 UN no. (ADR)
 UN1263

 UN no. (IMDG)
 UN1263

 UN no. (IATA)
 UN1263

14.2 UN proper shipping name

ADR proper shipping name
PAINT OF PAINT RELATED MATERIAL
PAINT OF PAINT RELATED MATERIAL
PAINT RELATED MATERIAL
PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR class 3
IMDG class 3
IATA class 3

Transport labels



14.4 Packing group

ADR/RID/ADN packing group III
IMDG packing group III
IATA packing group III

14.5 Environmental hazards

ADR No IMDG No IATA No

14.6 Special precautions for user

EMS F-E, S-E
Emergency action code A3 A72 A192
Hazard no. (ADR) <none>
Tunnel restriction code (E)

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information

$\underline{\textbf{15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture}$

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH).

Approved code of practice 2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents)

Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens)

Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment No chemical safety assessment has been carried out.

Section 16: Other information

General information This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 2020/878.

Revision commentsThis is a first issue. **Revision date**27 January 2022

Revision 1

Safety data sheet status Approved.

Hazard statements in full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

H315 Causes skin irritation.

 ${\bf H361} \hspace{1.5cm} {\bf Suspected\ of\ damaging\ fertility\ or\ the\ unborn\ child\ }.$

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H225 Highly flammable liquid and vapour.

 $\mbox{ \begin{tabular}{ll} \begin{tabular}{l$

H410 Very toxic to aquatic life with long lasting effects.H314 Causes severe skin burns and eye damage.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray

or mist.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.