

Ceiling Paint

A high-opacity, water-based matt paint specifically formulated for interior ceilings, delivering a smooth, uniform finish with minimal effort. Its low-odour, quick-drying formula is easy to apply, while the anti-drip properties and one-coat coverage ensure excellent opacity and a bright, brilliant white finish.



PRODUCT DESCRIPTION

A high-opacity, water-based matt ceiling paint designed for easy application and a smooth, uniform finish. Features one-coat coverage, anti-drip formulation, and excellent whiteness.

CHARACTERISTICS / ADVANTAGES

- LRV Rating 88
- Quick drying
- Low VOC and odour
- Easy application by spray, or roller
- Great opacity
- Flat deep rich matt finish

USES

- Interior walls & ceilings
- Good as a first coat on new builds and on new plaster

APPROVALS / STANDARDS

VOC Content

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 7g/l VOC.

Quality Control

- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)

Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Colour

Colours Brilliant White & Tinted To Pastel Colours

Colour Collections Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



SHERWIN
WILLIAMS

PANTONE®



Specification

Composition	Water-based vinyl acrylic. co-polymer
Number of Components	1
Recommended number of coats	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
Usage Interior/Exterior	Interior only
Application Tools	Brush, roller or spray.
Coverage	Approx. 14m ² per litre, per coat.
Overcoat Times	Recoat after 4 hours.
Curing Time	Touch dry in 30 minutes, fully cured after 7 to 10 days.
Suitable For	New or previously painted drywall, plaster, cement, concrete and other paintable surfaces.
Min. application temperature	4°C
Pack Size	2.5 - 5 & 10 litres
Shelf Life	3 years in unopened container.
Storage	Do not allow to freeze.
Cleaning Tools	Wash application tools in warm, soapy water immediately after use. .
Principle Limitations Please contact us regarding applications not described here	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.

Product Information

Colour Range: Brilliant White - tintable to pastel colours using the Fleetwood Colour Answers tinting system.

LRV Range: 88

VOC Content: Contains max VOC; 7g/l
Conforms to EU 2010 Directive (Cat A/a) 30g/l

Composition:
Pigment: Lightfast Pigments
Binder: Vinyl Acrylic Copolymer Emulsion.
Solvent: Water

Solids & Specific Gravity :
Volume Solids:: 26.0% (+/- 2%)
Weight Solids: 42.0% (+/- 2%)
Specific Gravity:: 1.28 g/ml (+/- 0.15)
Gloss @ 60°: < 8.0
pH -Value : > 8.2

Product Information Cont.

Surface Preparation:	Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material. Remove oil, grease and flaking material, feather edges of sound paint. Fill and fix any holes, cracks and shallow surface defects with a suitable filler, such as Fleetwood Ready Made Filler. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues and allow to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.				
Application:	Brush, roller, spray & airless spray. As with other water-based paints, do not apply in temperatures below 5°C				
Spreading Rate:	As a guide, a coverage rate of up to 14m ² /litre can be achieved under normal conditions				
Reduction:	Reduce by up to 20% with clean water as required by application and or equipment. When applying over previously painted matt surfaces, it is good practice to apply the 1st coat at 10% dilutions.				
Spray Recommendations:	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/in ²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60.				
Drying Time:	<table><tr><td>Touch Dry:</td><td>30 minutes</td></tr><tr><td>Recoat:</td><td>2 – 4 hours</td></tr></table> <p>This is dependent upon temperature and humidity. Darker colours may take longer 26°C to 50% RH @ 100 µm</p>	Touch Dry:	30 minutes	Recoat:	2 – 4 hours
Touch Dry:	30 minutes				
Recoat:	2 – 4 hours				
Cleaning Up:	Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.				
Tinting Instructions:	Tint only with Fleetwood Tinting systems				
Previously Painted Surfaces:	Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.				
Precautions:	If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly deteriorated, clean to sound substrate and treat as new. Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport all containers in upright position. Select sensible working clothes that cover as much of the body as possible. Always wear gloves and use eye protection. Do not touch your mouth or eyes with your gloves. Do not take internally. If medical advice is required ensure product container or label is at hand.				
Limitations:	The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application on +353 49 854 7209 technical@fleetwood.ie				

Technical Data Sheet

Ceiling Paint
F323
April 2026
Issue 1