

Trade Vinyl Matt

Formulated for the professional painter and is known throughout the industry for its trusted formula



PRODUCT DESCRIPTION

Fleetwood Trade Vinyl Matt goes on fast and dries to a smooth and reliable finish, time after time. It is formulated using the latest technology and materials, and manufactured to internationally accepted quality standards to provide emulsion products with outstanding performance. Trade Vinyl Matt finish has a non reflective appearance that helps hide imperfections and smooths lumps and bumps. This product is ideal for interior walls & ceilings and will extend the maintenance of any decorating project.

USES

- All interior walls & ceilings
- Excellent
- Breathable and Permeability makes it ideal for period and historic buildings
- All interior walls and ceilings

CHARACTERISTICS / ADVANTAGES

- Excellent durability
- LRV Rating 92
- Class 'O' Flame retardance on a class 'O' surface in accordance with BS476 part 6: 1989
- Quick drying
- Low VOC and odour
- Easy application by spray
- Excellent coverage and opacity
- Flat matt finish
- Water vapour permeable

[Click here for MSDS](#)

APPROVALS / STANDARDS

VOC Content

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 1g/l VOC.

Child Friendly

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 1g/l VOC.

Microporous


- Water Vapour

Indoor Air Quality

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 1g/l VOC.

Indoor Air Quality

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 1g/l VOC.




Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)

Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Colour

Colours Brilliant White & Tinted To Pastal Colours

Colour Collections Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



SHERWIN
WILLIAMS.

PANTONE®



Specification

Composition	Water-based acrylic.
Number of Components	1
Recommended number of coats	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
Usage Interior/Exterior	Interior.
Application Tools	Brush, roller or spray.
Coverage	Approx. 10m ² per litre, per coat.
Overcoat Times	Recoat after 2 hours.
Curing Time	Touch dry in 30 minutes, fully cured after 7 to 10 days.
Suitable For	New or previously painted drywall, plaster, cement, concrete, ceramic tile, primed or previously painted wood and metal, paintable plastics, aluminium, laminates and other paintable surfaces.
Min. application temperature	10°C
Pack Size	10L
Shelf Life	3 years in unopened container.
Storage	Do not allow to freeze.
Cleaning Tools	Wash application tools in warm, soapy water immediately after use. .
Principle Limitations Please contact us regarding applications not described here.	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.

Product Information

Pack Sizes:	10L
Colour Range:	Brilliant White
LRV Range:	90
VOC Content:	Contains max VOC; 4g/l Conforms to EU 2010 Directive (Cat A/c) 40g/l
Composition:	Pigment: Lightfast Pigments Binder: Acrylic Modified Copolymer Emulsion. Solvent: Water
Solids:	Volume Solids 32.0 % (+/- 2%) Weight Solids 45.0 % (+/- 2%) Specific Gravity 1.2 g/l (+/- 0.15)

Product Information Cont.

Surface Preparation:

Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Treat powdery surfaces with Fleetwood Masonry Primer. Use in accordance with good painting practices

Application:

Brush, roller, spray & airless spray.
As with other water-based paints, do not apply in temperatures below 5°C

Spreading Rate:

As a guide, a coverage rate of up to 12m²/litre can be achieved under normal conditions

Reduction:

Reduce by up to 10% as required by application and or equipment

Spray Recommendations:

Conventional Spray: Satisfactory through most equipment.
Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lb/in²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

Drying Time:

Touch Dry: 2 hours
Recoat: 2 – 4 hours
This is dependent upon temperature and humidity. Darker colours may take longer

Cleaning Up:

Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.

Tinting Instructions:

Tint only with Fleetwood Tinting systems

Precautions/limitations:

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practicaexperience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold gurantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application on +353 49 854 7209 technical@fleetwood.ie

Technical Data Sheet

Pro-Clean Non-Reflective

Matt

November 2024

Version 01.02