

Traditional Undercoat

The perfect base for a flawless, long-lasting finish.



PRODUCT DESCRIPTION

Traditional Undercoat is a high-quality solvent-based primer coat that ensures excellent adhesion, opacity, and a smooth surface for finishing coats. Suitable for interior and exterior wood and metal, it helps maximise the performance and durability of gloss, satin, or other topcoats. Its quick-drying, easy-to-apply formula ensures professional results every time.

USES

- Interior and exterior woodwork
- Metal gates and railings (with compatible primer where needed)
- Doors, frames, and skirting boards
- Shop fittings and displays****
- Furniture restoration
- Can be applied to PVC doors, windows and downpipes if properly prepared.

CHARACTERISTICS / ADVANTAGES

- Ideal for either water or solvent based trim finishes.
- Less prone to yellowing
- Easy application by brush, roller or spray
- Excellent coverage
- Low-sheen finish
- Excellent opacity and obliteration qualities
- Provides excellent flow, leveling and sag resistance
- Great enamel hold out

APPROVALS / STANDARDS

VOC Content

- 2004/42/EC EU limit value for this product (cat.A/g SB): 350g/l (2010) This product contains max. 350g/l VOC.

Quality Control

- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



NBS



NBS Chorus




Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)

Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Colour

Colours Brilliant White & Various Pre-Packaged Colours.

Colour Collections Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



Specification

Composition	Hybrid of acrylic and alkyd emulsions
Number of Components	1
Recommended number of coats	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
Usage Interior/Exterior	Interior/Exterior.
Application Tools	Brush, roller or spray.
Coverage	As a guide, a coverage rate of up to 16m ² per litre can be achieved under normal conditions.
Overcoat Times	Recoat after 16 - 24 hours.
Curing Time	Touch dry in 2 - 4 hours, fully cured after 7 to 10 days.
Suitable For	All interior/exterior wood and metal surfaces. Also suitable to apply on correctly prepared PVC.
Min. application temperature	5°C
Pack Size	250ml, 1L, 2.5L and 5L.
Shelf Life	3 years in unopened container.
Storage	Do not allow to freeze.
Cleaning Tools	Clean equipment immediately after use with white spirit or turpentine solution.
Principle Limitations	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.
Please contact us regarding applications not described here	

Product Information

Pack Sizes:	250ml, 1L, 2.5L and 5L.	
Colour Range:	Brilliant White & Various Pre-Packaged Colours.	
LRV Range:	90 (White)	
VOC Content:	Contains max VOC; 350g/l Conforms to EU 2010 Directive (Cat A/g) 350g/l	
Composition:	Pigment: Binder: Solvent:	Lightfast Pigments Long oil alkyd resin De-aromatized white spirit
Solids:	Volume Solids: Weight Solids: Specific Gravity: Gloss:	43% (+/- 2%) 66% (+/- 2%) 1.48 g/l (+/- 0.15) </= 5 at 60°, </= 10 at 85°

Product Information Cont.

Surface Preparation:	All surfaces to be painted must be clean, dry and free from all defective or poorly adhering material. Thoroughly rub down previously painted surfaces, using "wet flattening" methods where possible. Wipe off with a damp, lint-free cloth. Treat knots with a suitable knotting solution. New or bare surfaces should be primed with an appropriate primer. Note: Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain lead (Pb) . Use in accordance with good painting practices.						
Application:	Brush, roller, spray & airless spray. However, for H&S reasons related to all solvent-based based, spray application is not recommended. Do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).						
Spreading Rate:	As a guide, a coverage rate of up to 16m ² per litre can be achieved under normal conditions.						
Transportation & Storage:	Do not use or store in extremes of temperature. Protect from frost. To protect from spillage, please store and transport upright.						
Spray Recommendations:	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/in ²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60						
Drying Time:	<table><tr><td>Touch Dry:</td><td>5 - 6 hours</td></tr><tr><td>Recoat:</td><td>16 - 24 hours</td></tr><tr><td>Hard Dry:</td><td>48 hours</td></tr></table> <p>* This is dependent upon temperature and humidity. Darker colours may take longer. 26°C and 50% relative humidity at 4 Thou wet.</p>	Touch Dry:	5 - 6 hours	Recoat:	16 - 24 hours	Hard Dry:	48 hours
Touch Dry:	5 - 6 hours						
Recoat:	16 - 24 hours						
Hard Dry:	48 hours						
Cleaning Up:	Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with white spirit or turpentine substitute. Dispose of cans and waste paint in accordance with local authority guidelines.						
Tinting Instructions:	Tint only with Fleetwood Tinting systems						
Previously Painted Surfaces:	If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.						
Precautions:	Keep out of reach of children. Ensure good ventilation during application and drying. Flammable - keep away from sources of ignition. If the product comes in contact with the eyes, rinse immediately with plenty of water. To remove splashes from skin, use soap and water, or a recognised skin cleanser. Do not take internally. Contains no added lead.						

Limitations:

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application at +353 49 854 7209 or technical@fleetwood.ie