

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Fleetwood Traditional Undercoat Brilliant White
UFI : UFD0-80G0-500S-R931

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Consumer applications
Professional applications
Used by spraying
Application by non-spray methods,
Use of the substance/mixture : Paint

Uses advised against

Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

FSW Coatings Ltd.
Ballaghanea
A82 N267 Virginia, Co Cavan
Ireland
T +353 49854 7209
info@fleetwood.ie

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP)

: Warning

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H226 - Flammable liquid and vapour.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium dioxide substance with national workplace exposure limit(s) (IE)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	> 20 - < 25	Carc. 2, H351
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 919-857-5 REACH-no: 01-2119463258-33	> 10 - < 20	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 918-481-9 REACH-no: 01-2119457273-39	> 0.1 - < 2	Asp. Tox. 1, H304
1-methoxy-2-propanol substance with national workplace exposure limit(s) (IE); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	> 0.1 - < 1	Flam. Liq. 3, H226 STOT SE 3, H336
Propane-1,2-diol substance with national workplace exposure limit(s) (IE)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809-23	< 0.25	Not classified
Propylidynetrimethanol	CAS-No.: 77-99-6 EC-No.: 201-074-9 REACH-no: 01-2119486799-10	< 0.15	Repr. 2, H361fd
N,N-diethylhydroxylamine substance with national workplace exposure limit(s) (IE)	CAS-No.: 3710-84-7 EC-No.: 223-055-4 REACH-no: 01-2119962470-39	< 0.1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 STOT SE 3, H335 Aquatic Chronic 2, H411

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Maleic anhydride substance with national workplace exposure limit(s) (IE)	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9	< 0.0001	Acute Tox. 4 (Oral), H302 STOT RE 1, H372 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (Conc.)
Maleic anhydride	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9	(0.001 ≤ C ≤ 100) Skin Sens. 1A; H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Get medical attention if symptoms occur.
First-aid measures after eye contact	: Rinse opened eye for several minutes under running water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: At high concentrations, the vapours can be irritating to the respiratory system.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: In the event of contact with the liquid: Redness. Itching. Lacrimation. Blurred vision.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. Abdominal pain.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Alcohol-resistant foam. Carbon dioxide (CO ₂). Water spray. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Heating will cause a rise in pressure with a risk of bursting. In case of fire and/or explosion do not breathe fumes.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide. Nitrogen oxides.

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

- | | |
|--------------------------------|--|
| Firefighting instructions | : Evacuate the danger area. Eliminate all ignition sources if safe to do so. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Wear fire/flammable resistant/retardant clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges. Avoid all contact with skin, eyes, or clothing. |
|------------------|---|

For non-emergency personnel

- | | |
|----------------------|--|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing vapours. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. No action shall be taken without appropriate training or involving any personal risk. |

For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Use non-sparking tools. Ventilate area. |

6.2. Environmental precautions

Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not touch or walk on the spilled product. Remove ignition sources. |
| Methods for cleaning up | : Caution : this product can cause the floor to be slippery. Move containers from spill area. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Clean contaminated surfaces with an excess of water. Prevent entry to sewers and public waters. Use non-sparking tools. |
| Other information | : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques. |

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-----------------------------------|---|
| Additional hazards when processed | : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Precautions for safe handling | : Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Provide local exhaust or general room ventilation. Avoid breathing vapours. Wear personal protective equipment. Avoid contact with skin and eyes. Empty containers retain product residue and can be hazardous. Do not re-use container for any purpose. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge. Use explosion-proof equipment. Use non-sparking tools. |

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area. Keep away from food, drink and animal feedingstuffs. Keep only in the original container. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Store in accordance with local, regional, national or international regulation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible products : Strong acids. Strong bases. Strong oxidizing agents.

Incompatible materials : Direct sunlight. Heat sources. Ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 3
IOEL TWA	116 mg/m ³
	20 ppm
IOEL STEL	290 mg/m ³
	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 3
IOEL TWA	116 mg/m ³
	20 ppm
IOEL STEL	290 mg/m ³
	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
Maleic anhydride (108-31-6)	
Ireland - Occupational Exposure Limits	
Local name	Maleic anhydride
OEL TWA	0.01 ppm IFV (Inhlabl Fraction and Vapour)

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Maleic anhydride (108-31-6)	
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values), Sens (In the workplace, respiratory or dermal exposures to sensitising agents may occur. Sensitisers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The "sens" notation alone does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitisers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2024
Titanium dioxide (13463-67-7)	
Ireland - Occupational Exposure Limits	
Local name	Titanium dioxide
OEL TWA	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
N,N-diethylhydroxylamine (3710-84-7)	
Ireland - Occupational Exposure Limits	
Local name	N, N-Diethylhydroxylamine
OEL TWA	2 ppm
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
Propane-1,2-diol (57-55-6)	
Ireland - Occupational Exposure Limits	
Local name	Propane-1,2-diol [Propylene glycol]
OEL TWA	470 mg/m ³ total (vapour and particulates) 10 mg/m ³ particulates
	150 ppm total (vapour and particulates)
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
1-methoxy-2-propanol (107-98-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m ³
	100 ppm
IOEL STEL	568 mg/m ³
	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Propylene glycol monomethyl ether [1-Methoxypropan2-ol]

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol (107-98-2)	
OEL TWA	375 mg/m ³
	100 ppm
OEL STEL	568 mg/m ³
	150 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024

Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Workplace atmospheres. Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy. Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

DNEL and PNEC

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	208 mg/kg bw/day
Long-term - systemic effects, inhalation	871 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	125 mg/kg bw/day
Long-term - systemic effects, inhalation	185 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bw/day
Long-term - local effects, inhalation	178.57 mg/m ³
Titanium dioxide (13463-67-7)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	1.25 mg/m ³
Long-term - local effects, inhalation	10 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	700 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	1 mg/l
PNEC aqua (marine water)	0.127 mg/l
PNEC aqua (intermittent, freshwater)	0.61 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1000 mg/kg dwt
PNEC sediment (marine water)	100 mg/kg dwt
PNEC (Soil)	
PNEC soil	100 mg/kg dwt

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium dioxide (13463-67-7)	
PNEC (Oral)	
PNEC oral (secondary poisoning)	1667 kg/kg food
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
Propylidynetrimehanol (77-99-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.94 mg/kg bw/day
Long-term - systemic effects, inhalation	3.3 mg/m ³
Propane-1,2-diol (57-55-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	168 mg/m ³
Long-term - local effects, inhalation	10 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	50 mg/m ³
Long-term - local effects, inhalation	10 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	260 mg/l
PNEC aqua (marine water)	26 mg/l
PNEC aqua (intermittent, freshwater)	183 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	572 mg/kg dwt
PNEC sediment (marine water)	57.2 mg/kg dwt
PNEC (Soil)	
PNEC soil	50 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	20000 mg/l
1-methoxy-2-propanol (107-98-2)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	553.5 mg/m ³
Long-term - systemic effects, dermal	50.6 mg/kg bw/day
Long-term - systemic effects, inhalation	369 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	3.3 mg/kg bw/day
Long-term - systemic effects, inhalation	43.9 mg/m ³
Long-term - systemic effects, dermal	18.1 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	10 mg/l
PNEC aqua (marine water)	1 mg/l

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol (107-98-2)	
PNEC aqua (intermittent, freshwater)	100 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	52.3 mg/kg dwt
PNEC sediment (marine water)	5.2 mg/kg dwt
PNEC (Soil)	
PNEC soil	4.59 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Handle in accordance with good industrial hygiene and safety procedures. Provide local exhaust or general room ventilation. Avoid all unnecessary exposure. Ensure exposure is below occupational exposure limits (where available). Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

Eye and face protection

Eye protection:

Use splash goggles when eye contact due to splashing is possible. ISO 16321-1

Skin protection

Skin and body protection:

Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided

Hand protection:

Chemical resistant gloves (according to European standard ISO 374-1 or equivalent). Recommended materials. Nitrile rubber. Thickness 0.33 mm. Breakthrough time: 6 (> 480 minutes). Chloroprene rubber. Thickness 0.6 mm. Breakthrough time: 6 (> 480 minutes). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Do not allow large quantities, as are, to spread into the environment. Do not discharge into drains or rivers.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Appearance	: Viscous.
Odour	: slightly. Hydrocarbon-like.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: -15 °C
Boiling point	: > 145 °C
Flammability	: Flammable liquid and vapour.

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lower explosion limit	: 0.6 vol %
Upper explosion limit	: 7 vol %
Flash point	: 42 °C (closed cup)
Auto-ignition temperature	: > 230 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: > 21 mm²/s (40 °C)
Solubility	: Insoluble in: cold water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.16 kPa (20 °C)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.48 ± 0.2
Relative vapour density at 20°C	: 4.5
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

Relative evaporation rate (butylacetate=1)	: 0.03
VOC content	: 298 g/l
Volume solids	: 43.0 % ±1.0
Weight solids	: 66.0 % ±1.0

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour. Can form explosive mixtures with air. Heating may cause a fire or explosion.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerisation: Will not occur.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating. Extremely high or low temperatures. Heat and ignition sources. Do not freeze.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rabbit	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	4951 mg/m³ (4 h, OECD 403)

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LC50 Inhalation - Rat (Vapours)	> 6.1 mg/l/4h
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
LD50 oral rat	5000 mg/kg (OECD 401)
LD50 dermal rabbit	2000 mg/kg (OECD 402)
LC50 Inhalation - Rat	5.9 mg/l/4h (OECD 403)
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 Inhalation - Rat	> 6.82 mg/l/4h
Propylidynetrimehanol (77-99-6)	
LD50 oral rat	14700 mg/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 Inhalation - Rat	> 0.85 mg/l/4h
N,N-diethylhydroxylamine (3710-84-7)	
LD50 oral	2190 mg/kg
LD50 dermal	1300 mg/kg
LC50 Inhalation - Rat (Vapours)	11.42 mg/l/4h
Propane-1,2-diol (57-55-6)	
LD50 oral rat	22000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	41 mg/l
1-methoxy-2-propanol (107-98-2)	
LD50 oral rat	4016 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25.8 mg/l (6 h)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Fleetwood Traditional Undercoat Brilliant White	
Viscosity, kinematic	> 21 mm²/s (40 °C)

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Other information

Other information

: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Not classified (Based on available data, the classification criteria are not met)

Additional information

: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

LC50 - Fish [1]	> 1000 mg/l (96 h, Oncorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	> 1000 mg/l (48 h, Daphnia magna, OECD 202)
EC50 72h - Algae [1]	> 1000 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)
NOEC chronic fish	0.131 mg/l (28 d, Oncorhynchus mykiss, QSAR)
NOEC chronic crustacea	0.23 mg/l (21 d, Daphnia magna, QSAR)
NOEC chronic algae	3 – 100 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

LC50 - Fish [1]	> 1000 mg/l (96 h, Oncorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	> 1000 mg/l (48 h, Daphnia magna, OECD 202)
EC50 72h - Algae [1]	> 1000 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)
NOEC chronic algae	1000 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)

Titanium dioxide (13463-67-7)

LC50 - Fish [1]	> 1000 mg/l (96 h, Pimephales promelas)
LC50 - Fish [2]	> 10000 mg/l (96 h, Cyprinodon variegatus variegatus, OECD 203)
EC50 - Crustacea [1]	> 1000 mg/l (48 h, Daphnia magna, OECD 202)
EC50 - Crustacea [2]	> 10000 mg/l (48 h, Acartia tonsa, ISO 14669, ISO 5667-16)
EC50 - Other aquatic organisms [1]	> 10000 mg/l (3 h, activated sludge, OECD 209)
EC50 72h - Algae [1]	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)
EC50 72h - Algae [2]	> 1000 mg/l (72 h, Skeletoma costatum, ISO 10253)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata)

Propylidynetrimethanol (77-99-6)

LC50 - Fish [1]	> 1000 mg/l (96 h)
-----------------	--------------------

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propylidynetrimethanol (77-99-6)	
EC50 - Crustacea [1]	13000 mg/l (48 h, Daphnia sp.)
EC50 - Crustacea [2]	10330 – 16360 mg/l (48 h, Daphnia magna)
EC50 - Other aquatic organisms [1]	> 10000 mg/l (3 h, activated sludge, OECD 209)
EC50 72h - Algae [1]	> 1000 mg/l (72 h, Pseudokirchneriella subcapitata)

N,N-diethylhydroxylamine (3710-84-7)	
EC50 - Crustacea [1]	8.2 mg/l (48 h, Daphnia magna)

Propane-1,2-diol (57-55-6)	
LC50 - Fish [1]	40613 mg/l (96 h, Oncorhynchus mykiss, OECD 203)
LC50 - Fish [2]	55770 mg/l (96 h, Pimephales promelas)
EC50 - Crustacea [1]	> 4000 mg/l (48 h, Daphnia magna)
EC50 - Crustacea [2]	18340 mg/l (48 h, Ceriodaphnia dubia, OECD 202)
EC50 96h - Algae [1]	19000 mg/l (96 h, Scenedesmus subspicatus)
EC50 96h - Algae [2]	19100 mg/l (96 h, Skeletonema costatum)
ErC50 algae	19000 mg/l (96 h, Pseudokirchneriella subcapitata, OECD 201)
NOEC chronic crustacea	13020 mg/l (7 d, Daphnia magna)
NOEC chronic algae	15000 mg/l (96 h, Scenedesmus subspicatus)

1-methoxy-2-propanol (107-98-2)	
LC50 - Fish [1]	6812 mg/l (96 h, Leuciscus idus, DIN 38412)
LC50 - Fish [2]	20800 mg/l (96 h, Pimephales promelas, ASTM)
LC50 - Other aquatic organisms [1]	≥ 1000 mg/l (96 h, Oncorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	21100 – 25900 mg/l (48 h, Daphnia magna)
EC50 - Other aquatic organisms [1]	1000 mg/l (3 h, activated sludge, OECD 209)
ErC50 algae	> 1000 mg/l (7 d, Pseudokirchneriella subcapitata)
NOEC chronic fish	> 1000 mg/l (96 h, Oncorhynchus mykiss)
NOEC chronic algae	> 1000 mg/l (7 d)

12.2. Persistence and degradability

Fleetwood Traditional Undercoat Brilliant White	
Persistence and degradability	Biodegradability in water: no data available.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
Persistence and degradability	Biodegradable.
Biodegradation	80 % (28 d, OECD 301 F)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
Persistence and degradability	Readily biodegradable.
Biodegradation	80 % (28 d, OECD 301 F)

Propylidynetrimethanol	
Biodegradation	100 % (28 d, OECD 302B)

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propane-1,2-diol (57-55-6)	
Persistence and degradability	Rapidly degradable
Biochemical oxygen demand (BOD)	1.17 g O ₂ /l
Chemical oxygen demand (COD)	4.7 g O ₂ /l
Biodegradation	> 81 % (28 d, OECD 301F)

1-methoxy-2-propanol (107-98-2)	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % (28 d, OECD 301 E)

12.3. Bioaccumulative potential

Fleetwood Traditional Undercoat Brilliant White	
Bioaccumulative potential	No data available.

Hydrocarbons, C ₉ -C ₁₁ , n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
BCF - Fish [1]	10 – 2500
Partition coefficient n-octanol/water (Log K _{ow})	> 4

Propylidynetrimechanol (77-99-6)	
Partition coefficient n-octanol/water (Log P _{ow})	-0.47

N,N-diethylhydroxylamine (3710-84-7)	
Partition coefficient n-octanol/water (Log P _{ow})	0.5 (23 °C)

Propane-1,2-diol (57-55-6)	
BCF - Fish [1]	< 0.09
Partition coefficient n-octanol/water (Log K _{ow})	-1.07

1-methoxy-2-propanol (107-98-2)	
BCF - Fish [1]	< 100
Partition coefficient n-octanol/water (Log K _{ow})	-0.437

12.4. Mobility in soil

Fleetwood Traditional Undercoat Brilliant White	
Ecology - soil	Adsorbs into the soil.

Hydrocarbons, C ₁₀ -C ₁₃ , n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
Mobility in soil	0.05 kPa (20 °C)

Propane-1,2-diol (57-55-6)	
Organic Carbon Normalized Adsorption Coefficient (Log K _{oc})	0.46 (20 °C)

1-methoxy-2-propanol (107-98-2)	
Organic Carbon Normalized Adsorption Coefficient (Log K _{oc})	0.2 – 1

12.5. Results of PBT and vPvB assessment

No additional information available

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Other adverse effects : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information : Avoid release to the environment.
European List of Waste (LoW, EC 2000/532) : Disposal must be carried out using appropriate EWC code

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 163, 367, 650

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Limited quantities (ADR)	: 5L
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
-------------------------------	-------

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Naphtha (petroleum), hydrotreated heavy (64742-48-9), Naphtha (petroleum), hydrotreated heavy (64742-48-9)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 298 g/l

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
TLM	Median Tolerance Limit
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative

Data sources : ECHA (European Chemicals Agency). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 and all its amendments and modifications. Supplier's safety documents.

Training advice : Training staff on good practice.

Fleetwood Traditional Undercoat Brilliant White

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.