

Pro-Clean Scuff Defence

Formulated for the professional painter, the ultimate washable paint that stands up to scuffs, scrubs, and everyday wear.



PRODUCT DESCRIPTION

Pro-Clean Scuff Defence is a tough, low-sheen emulsion designed with professional decorators in mind. Engineered for durability, it resists scuffs, marks, and stains – even in high-traffic areas. Easy to apply with excellent coverage and flow, it delivers a flawless, low-sheen finish that lasts. Trusted by professionals nationwide, it's the go-to choice for projects where performance matters.

USES

- Hallways, stairwells and other high traffic areas.
- All interior walls & ceilings.
- Hospital or dental waiting rooms
- Care homes, and hospital rooms

CHARACTERISTICS / ADVANTAGES

- Excellent durability
- Class 1 scrubability EN13300 & ISO11998
- LRV Rating 90
- Quick drying
- Low VOC and odour
- Easy application by spray
- Excellent coverage and opacity
- Flat matt finish
- Good resistance to everyday stains: tea, coffee, hand fats.
- Scuff and scratch resistant

APPROVALS / STANDARDS

VOC Content

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 23.5g/l VOC.

Durability

- Class 1 scrubability EN13300 & ISO11998

Quality Control

- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



NBS



NBS Chorus




Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)

Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Colour

Colours	Brilliant White & Tinted To Pastal Colours
Colour Collections	Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



Specification

Composition	Water-based acrylic.
Number of Components	1
Recommended number of coats	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
Usage Interior/Exterior	Interior.
Application Tools	Brush, roller or spray.
Coverage	Approx. 12m ² per litre, per coat.
Overcoat Times	Recoat after 4 hours.
Curing Time	Touch dry in 30 minutes, fully cured after 7 to 10 days.
Suitable For	New or previously painted drywall, plaster, cement, concrete and other paintable surfaces.
Min. application temperature	4°C
Pack Size	10L
Shelf Life	3 years in unopened container.
Storage	Do not allow to freeze.
Cleaning Tools	Wash application tools in warm, soapy water immediately after use. .
Principle Limitations	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.
Please contact us regarding applications not described here	

Product Information

Pack Sizes:	10L
Colour Range:	Brilliant White
LRV Range:	90
VOC Content:	Contains max VOC; 23.5g/l Conforms to EU 2010 Directive (Cat A/a) 30g/l
Composition:	Pigment: Lightfast Pigments Binder: Acrylic Modified Copolymer Emulsion. Solvent: Water
Solids:	Volume Solids (P Base) 34.5% (+/- 2%) Weight Solids 49.3% (+/- 2%) Specific Gravity 1.30 g/l (+/- 0.15) Gloss < 4.5 @ 85° & < 2.5 @ 60° pH -Value > 8.2

Product Information Cont.

Surface Preparation:	Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease and flaking material. Treat powdery surfaces with Fleetwood Masonry Primer. Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken
Application:	Brush, roller, spray & airless spray. As with other water-based paints, do not apply in temperatures below 5°C
Spreading Rate:	As a guide, a coverage rate of up to 15m ² /litre can be achieved under normal conditions
Reduction:	Reduce by up to 20% as required by application and or equipment. When applying over previously painted matt surfaces, it is good practice to apply the 1st coat at 105 dilutions.
Spray Recommendations:	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/in ²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60
Drying Time:	Touch Dry: 2 hours Recoat: 2 – 4 hours This is dependent upon temperature and humidity. Darker colours may take longer 26°C to 50% RH @ 100 µm
Cleaning Up:	Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.
Tint Instructions:	Tint only with Fleetwood Tinting systems
Previously Painted Surfaces:	Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.
Precautions:	If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new. Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport all containers in upright position. Select sensible working clothes that cover as much of the body as possible. Always wear gloves and use eye protection. Do not touch your mouth or eyes with your gloves.

Limitations:

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application on +353 49 854 7209 technical@fleetwood.ie