

Weather Guard Xtreme

Fleetwood Weather Guard® Xtreme is formulated with Permacyl technology that provides outstanding durability against the harshest weather Ireland has to offer.



PRODUCT DESCRIPTION

Fleetwood Weather Guard® Xtreme contains powerful anti mould and algae properties that resist the growth of mould and fungus whilst protecting the surface. Once applied, Fleetwood Weather Guard® Xtreme offers outstanding adhesion and colour retention - resisting frost in cold conditions, and fading, chalking and blistering in hot and humid conditions. This product contains a Pliolite® resin which enables application at temperatures as low as -5°C, and becomes showerproof in 20 minutes, allowing year-round exterior decoration. Fleetwood Weather Guard® has been tested in Ireland to resist mould, algae and moss growth and has been the decorators choice in exterior paint for over 40 years.

USES

- Suitable for or exterior use on cement rendering, rough cast, brick and concrete
- Can be used on pebble-dash and brickwork which is normally suitable for painting, eg. rustic or sand-faced bricks
- Internal exposed surfaces

CHARACTERISTICS / ADVANTAGES

- Excellent coverage makes Fleetwood Weather Guard® Xtreme ideal for pebble and stone dashing
- Exceptional UV & fade resistance ensuring your colour lasts longer
- Excellent durability
- High opacity
- LRV Rating 90
- Quick drying - shower resistant in 20 minutes
- Easy application by spray and roller
- Smooth matt finish
- Water vapour permeability (ISO 7783:2018) – breathability classified as V1 – Very high
- Prolonged resistance to microbial attack
- Hybrid product - as good internally as it is externally
- Excellent adhesion to previously painted or untreated porous surfaces

APPROVALS / STANDARDS

VOC Content

- 2004/42/EC EU limit value for this product (cat.A/c SB): 430g/l (2010) This product contains max. 430g/l VOC.

Quality Control


- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)
Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Colour

Colours	Brilliant White & Tinted to Pastel Colours. Dark colours available on request.
Colour Collections	Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



Specification

Composition	Solvent-based alkyd
Number of Components	1
Recommended number of coats	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
Usage Interior/Exterior	Exterior/Interior
Application Tools	Brush, roller or spray.
Coverage	Approx. 6.5m ² per litre, per coat, depending on the smoothness of the substrate.
Overcoat Times	Recoat after 16 - 24 hours.
Curing Time	Touch dry in 20 - 30 minutes, fully cured after 7 to 10 days.
Suitable For	New or previously painted drywall, plaster, cement, concrete, brick and other paintable surfaces.
Min. application temperature	5°C
Pack Size	5 L
Shelf Life	3 years in unopened container.
Storage	Do not allow to freeze.
Cleaning Tools	Wash application tools in warm, soapy water immediately after use.
Principle Limitations	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.
Please contact us regarding applications not described here	

Product Information

Colour Range:	Brilliant White & Tinted to Pastel Colours. Dark colours available on request.
LRV Range:	90
VOC Content:	Contains max VOC; 430g/l Conforms to EU 2010 Directive (Cat A/c) 430g/l

Composition:	Pigment:	Lightfast Pigments
	Binder:	Pliolite® Binder
	Solvent:	White Spirit
Solids:	Volume Solids: 39% (+/- 2%) Weight Solids: 66% (+/- 2%) Specific Gravity: 1.47 g/ml (+/- 0.15) Gloss: <= 3 at 60°	

Product Information Cont.

Surface Preparation:	Use in accordance with good painting practice. Remove oil, grease and flaking material. Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Treat powdery surfaces with Fleetwood Masonry Primer. Repair cracks and defective areas, and treat fungal or algal growth with Fleetwood Fungicidal Wash as required.
Application:	Brush, roller, spray & spray. However, for H&S reasons related to all solvent-based paints, spray application is not recommended.
Spreading Rate:	As a guide, a coverage rate of up to 6.5m ² per litre, per coat, depending on the smoothness of the substrate.
Reduction:	Reduce by up to 15% as required by application and/or equipment.
Spray Recommendations:	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 153 kg/cm ² (2180 lb/in ²) with a spray tip size of 0.46mm spray tip angle 65°. Filter mesh 60.
Drying Time:	Touch Dry: 20 – 30 mins Recoat: 16 – 24 hours * Shower resistant after 20 minutes. This is dependent upon temperature and humidity @ 26°C and 50% relative humidity at a wet film thickness of 100 µm.. Darker colours may take longer.
Cleaning Up:	Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with white spirit or turpentine substitute. Dispose of cans and waste paint in accordance with local authority guidelines.
Tinting Instructions:	Tint only with Fleetwood Tinting systems
Previously Painted Surfaces:	If in sound condition, clean the surface of all foreign material. If paint is peeling or badly weathered, clean to sound substrate and treat as new.
Precautions:	Keep out of reach of children. Ensure good ventilation during application and drying. Flammable - keep away from sources of ignition. If the product comes in contact with the eyes, rinse immediately with plenty of water. To remove splashes from skin, use soap and water, or a recognised skin cleanser. Do not take internally. Contains no added lead.

Limitations:

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application on +353 49 854 7209 technical@fleetwood.ie