

Weather Guard® Fungicidal Wash Plus



Weather Guard® Fungicidal Wash Plus is formulated to remove Green Algae, Red Discolouration, Mould and Lichen from Concrete Walkways, Interior and Exterior Walls, Kerbs, Patios, Decking, Tarmacadam, Headstones, Tiles & Slate Roofs. Used for the preservation of masonry, composite materials, or other construction materials other than wood.

PRODUCT DESCRIPTION

An advanced formulation for the treatment of common growth of algae and lichen. An ideal first step before painting.

USES

- Masonry Walls
- Paths and driveways
- Exterior walls, capping, pre-cast concrete
- Windowsills
- Patios & decking

CHARACTERISTICS / ADVANTAGES

- 10x tougher than standard formulations
- Biodegradable under aerobic conditions
- Pet Friendly
- Cleans and treats masonry surfaces, preparing them for over for coating.
- Controls red & green algae and lichen
- Ready for use or can be dilute up to 10 x1 depending on contamination and requirements.

APPROVALS / STANDARDS

Quality Control

- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)

Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Product Information

Composition	Didecyldimethylammonium chloride (DDAC) 11%w/w - solvent : water
Typical use	Suitable for use on masonry walls, pats, driveways, exterior window sills, pier and wall cappings, patios and decking
Pack Size	5 litres
Colour	Bright pink liquid
Practical Coverage	As a guide to coverage one can expect to achieve up to 25m ² per litre. This may vary considerably depending on the substrate treated and the absorbency of the surface
Drying Time	Single coat at standard thickness - Touch dry: 2 - 4 hours. Leave in place for a minimum of 24 hours to ensure that the product has sufficient time to work. The surface can then be washed to remove dead growth and residues.
Application	Always read the label before use and wear suitable protective equipment. Apply liberally with a nylon bristle brush, roller, or non-atomising spray, scrub into surface, leave to dry. Leave in place for a minimum of 24 hours to ensure that the product has sufficient time to work. All signs of organic growth should then be removed with a scraper or stiff, bristle brush. If desired wash surfaces and allow to dry. Heavy long established organic growth is best removed by pressure washing between 1500-2000 psi (102-136 bar), wet or dry grit blasting. Care must be taken not to damage the underlying surface. Take care not to allow residues to run directly into fresh watercourses..
Health & Safety	Please refer to the Safety, Health and Environmental Information on the container. For further information download the product safety datasheet (SDS) from our website. Wear suitable protective gloves/ protective clothing/ eye protection/ face protection when using this product. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.
Storage	Store in an upright and secure manner. Keep in a cool, dry, well-ventilated area. Keep containers tightly closed. Do not store below 5°C or above 40°C.
Shelf Life	3 years in unopened container.
Cleaning Up:	After use remove material as possible from the equipment, then clean up with soap and water. Dispose of container in accordance with local authority guidelines.
Precautions:	If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly deteriorated, clean to sound substrate and treat as new. Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport all containers in upright position. Select sensible working clothes that cover as much of the body as possible. Always wear gloves and use eye protection. Do not touch your mouth or eyes with your gloves. Do not take internally. If medical advice is required ensure product container or label is at hand.
Limitations:	The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application on +353 49 854 7209 technical@fleetwood.ie

Technical Data Sheet

Weather Guard® Fungicidal Wash Plus

F 118

February 2026 Issue 1

FLEETWOOD
PAINTMAKERS of IRELAND

Hand crafted in Ireland by Fleetwood Paints,
Virginia, Co. Cavan, A82 N267, Ireland.
☎ + 353 49 854 7209 🌐 fleetwood.ie ✉ info@fleetwood.ie
Follow us online for infinite inspiration 